



# SPEC® MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## SGI

SPECmpiL\_peak2007 = Not Run

SGI ICE X (Intel Xeon E5-2690 v2, 3.0 GHz)

SPECmpiL\_base2007 = 3.90

MPI2007 license: 4


Test date: Dec-2013

Test sponsor: SGI

Hardware Availability: Sep-2013

Tested by: SGI

Software Availability: Nov-2013



## Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
121.pop2	80	994	3.92	987	3.94	<b>989</b>	<b>3.94</b>							
122.tachyon	80	845	2.30	842	2.31	<b>842</b>	<b>2.31</b>							
125.RAxML	80	978	2.98	<b>981</b>	<b>2.98</b>	981	2.98							
126.lammps	80	<b>856</b>	<b>2.87</b>	856	2.87	858	2.87							
128.GAPgeofem	80	1159	5.12	<b>1161</b>	<b>5.11</b>	1169	5.08							
129.tera_tf	80	415	2.65	414	2.65	<b>415</b>	<b>2.65</b>							
132.zeusmp2	80	<b>554</b>	<b>3.83</b>	553	3.83	555	3.82							
137.lu	80	<b>926</b>	<b>4.54</b>	925	4.54	931	4.51							
142.dmilc	80	649	5.68	649	5.67	<b>649</b>	<b>5.68</b>							
143.dleslie	80	639	4.85	631	4.91	<b>636</b>	<b>4.87</b>							
145.lGemsFDTD	80	904	4.88	<b>903</b>	<b>4.88</b>	903	4.88							
147.l2wrf2	80	1640	5.00	<b>1640</b>	<b>5.00</b>	1642	5.00							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/



# SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## SGI

SPECmpiL\_peak2007 = Not Run

SGI ICE X (Intel Xeon E5-2690 v2, 3.0 GHz)

SPECmpiL\_base2007 = 3.90

MPI2007 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: Dec-2013

Hardware Availability: Sep-2013

Software Availability: Nov-2013

### Hardware Summary

Type of System: Homogeneous  
 Compute Node: SGI ICE X IP-113 Compute Node  
 Interconnect: InfiniBand (MPI and I/O)  
 File Server Node: SGI Modular InfiniteStorage Server  
 Total Compute Nodes: 4  
 Total Chips: 8  
 Total Cores: 80  
 Total Threads: 160  
 Total Memory: 256 GB  
 Base Ranks Run: 80  
 Minimum Peak Ranks: --  
 Maximum Peak Ranks: --

### Software Summary

C Compiler: Intel C++ Composer XE 2011 for Linux, Version 14.0.0.080 Build 20130728  
 C++ Compiler: Intel C++ Composer XE 2011 for Linux, Version 14.0.0.080 Build 20130728  
 Fortran Compiler: Intel Fortran Composer XE 2011 for Linux, Version 14.0.0.080 Build 20130728  
 Base Pointers: 64-bit  
 Peak Pointers: 64-bit  
 MPI Library: SGI MPT 2.09  
 Other MPI Info: OFED 1.5.2  
 Pre-processors: None  
 Other Software: None

## Node Description: SGI ICE X IP-113 Compute Node

### Hardware

Number of nodes: 4  
 Uses of the node: compute  
 Vendor: SGI  
 Model: SGI ICE X IP-113 (Intel Xeon E5-2690 v2, 3.0 GHz)  
 CPU Name: Intel Xeon E5-2690 v2  
 CPU(s) orderable: 1-2 chips  
 Chips enabled: 2  
 Cores enabled: 20  
 Cores per chip: 10  
 Threads per core: 2  
 CPU Characteristics: Ten Core, 3.0 GHz, 8.0 GT/s QPI  
 Intel Turbo Boost Technology up to 3.60 GHz  
 Hyper-Threading Technology enabled  
 CPU MHz: 3000  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 25 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 64 GB (8 x 8 GB 2Rx4 PC3-14900R-13, ECC)  
 Disk Subsystem: None  
 Other Hardware: None  
 Adapter: Mellanox MT27500 with ConnectX-3 ASIC (PCIe x8 Gen3 8 GT/s)  
 Number of Adapters: 2  
 Slot Type: PCIe x8 Gen3  
 Data Rate: InfiniBand 4x FDR  
 Ports Used: 2  
 Interconnect Type: InfiniBand

### Software

Adapter: Mellanox MT27500 with ConnectX-3 ASIC (PCIe x8 Gen3 8 GT/s)  
 Adapter Driver: OFED-1.5.2  
 Adapter Firmware: 2.11.312  
 Operating System: SUSE Linux Enterprise Server 11 SP2, Kernel 3.0.80-0.7-default  
 Local File System: NFSv3  
 Shared File System: NFSv3 IPoIB  
 System State: Multi-user, run level 3  
 Other Software: SGI Tempo Compute Node 2.7.3, Build 708rp14.sles11sp2-1305311204



# SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## SGI

SPECmpiL\_peak2007 = Not Run

SGI ICE X (Intel Xeon E5-2690 v2, 3.0 GHz)

SPECmpiL\_base2007 = 3.90

MPI2007 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: Dec-2013

Hardware Availability: Sep-2013

Software Availability: Nov-2013

### Node Description: SGI Modular InfiniteStorage Server

#### Hardware

Number of nodes: 1  
 Uses of the node: fileserver  
 Vendor: SGI  
 Model: SGI Modular InfiniteStorage Server  
 CPU Name: Intel Xeon E5-2670  
 CPU(s) orderable: 1-2 chips  
 Chips enabled: 2  
 Cores enabled: 16  
 Cores per chip: 8  
 Threads per core: 2  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.33 GHz  
 Hyper-Threading Technology enabled  
 CPU MHz: 2600  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per chip  
 L3 Cache: 20 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 128 GB (8 \* 16 GB 2Rx4 PC3-12800R-11, ECC)  
 Disk Subsystem: 64.8 TB RAID 6  
 72 x 900 GB SAS (Western Digital, 10K RPM)  
 Other Hardware: None  
 Adapter: Mellanox MT27500 with ConnectX-3 ASIC  
 (PCIe x8 Gen3 8 GT/s)  
 Number of Adapters: 2  
 Slot Type: PCIe x8 Gen3  
 Data Rate: InfiniBand 4x FDR  
 Ports Used: 2  
 Interconnect Type: InfiniBand

#### Software

Adapter: Mellanox MT27500 with ConnectX-3 ASIC  
 (PCIe x8 Gen3 8 GT/s)  
 Adapter Driver: OFED-1.5.0  
 Adapter Firmware: 2.11.312  
 Operating System: SUSE Linux Enterprise Server 11 SP3  
 Kernel  
 Local File System: xfs  
 Shared File System: --  
 System State: Multi-user, run level 3  
 Other Software: SGI Foundation Software 2.9,  
 Build 700r3.sles11-1004061553

### Interconnect Description: InfiniBand (MPI and I/O)

#### Hardware

Vendor: Mellanox Technologies and SGI  
 Model: None  
 Switch Model: SGI FDR Integrated IB Switch Blade 2SW9x27 with  
 Mellanox SwitchX device 51000  
 Number of Switches: 2  
 Number of Ports: 36  
 Data Rate: InfiniBand 4x FDR  
 Firmware: 07130007\_LL2 and 08130007\_LL2  
 Topology: Enhanced Hypercube  
 Primary Use: MPI and I/O traffic

#### Software



# SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

**SGI**

SPECmpiL\_peak2007 = Not Run

SGI ICE X (Intel Xeon E5-2690 v2, 3.0 GHz)

SPECmpiL\_base2007 = 3.90

MPI2007 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: Dec-2013

Hardware Availability: Sep-2013

Software Availability: Nov-2013

## Submit Notes

The config file option 'submit' was used.

## General Notes

130.socorro (base): "nullify\_ptrs" src.alt was used.

Software environment:

```
export MPI_REQUEST_MAX=65536
export MPI_TYPE_MAX=32768
export MPI_BUFS_THRESHOLD=1
export MPI_IB_RAILS=2
ulimit -s unlimited
```

BIOS settings:

```
AMI BIOS version 3.0
Hyper-Threading Technology enabled (default)
Intel Turbo Boost Technology enabled (default)
Intel Turbo Boost Technology activated in the OS via
/etc/init.d/acpid start
/etc/init.d/powersaved start
powersave -f
```

Job Placement:

Each MPI job was assigned to a topologically compact set of nodes, i.e. the minimal needed number of switches was used for each job: 2 switches for up to 180 ranks, 4 switches for up to 320 ranks, 8 switches for 640 ranks, 10 switches for 800 ranks, 16 switches for 1280 ranks, 22 switches for 1920 ranks, and 30 switches for 2560 ranks.

Additional notes regarding interconnect:

The Infiniband network consists of two independent planes, with half the switches in the system allocated to each plane. I/O traffic is restricted to one plane, while MPI traffic can use both planes.

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

126.lammps: icpc

Fortran benchmarks:

ifort

Continued on next page



# SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

**SGI**

SPECmpiL\_peak2007 = Not Run

SGI ICE X (Intel Xeon E5-2690 v2, 3.0 GHz)

SPECmpiL\_base2007 = 3.90

MPI2007 license: 4

Test date: Dec-2013

Test sponsor: SGI

Hardware Availability: Sep-2013

Tested by: SGI

Software Availability: Nov-2013

## Base Compiler Invocation (Continued)

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

121.pop2: -DSPEC\_MPI\_CASE\_FLAG

## Base Optimization Flags

C benchmarks:

-O3 -xAVX -no-prec-div

C++ benchmarks:

126.lammps: -O3 -xAVX -no-prec-div -ansi-alias

Fortran benchmarks:

-O3 -xAVX -no-prec-div

Benchmarks using both Fortran and C:

-O3 -xAVX -no-prec-div

## Base Other Flags

C benchmarks:

-lmpi

C++ benchmarks:

126.lammps: -lmpi

Fortran benchmarks:

-lmpi

Benchmarks using both Fortran and C:

-lmpi

The flags file that was used to format this result can be browsed at

[http://www.spec.org/mpi2007/flags/SGI\\_x86\\_64\\_Intel14\\_flags.html](http://www.spec.org/mpi2007/flags/SGI_x86_64_Intel14_flags.html)

You can also download the XML flags source by saving the following link:

[http://www.spec.org/mpi2007/flags/SGI\\_x86\\_64\\_Intel14\\_flags.xml](http://www.spec.org/mpi2007/flags/SGI_x86_64_Intel14_flags.xml)



# SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## SGI

SPECmpiL\_peak2007 = Not Run

SGI ICE X (Intel Xeon E5-2690 v2, 3.0 GHz)

SPECmpiL\_base2007 = 3.90

MPI2007 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: Dec-2013

Hardware Availability: Sep-2013

Software Availability: Nov-2013

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC MPI2007 v2.0.1.  
Report generated on Tue Jul 22 13:48:05 2014 by SPEC MPI2007 PS/PDF formatter v1463.  
Originally published on 22 January 2014.