



SPEC® OMPG2012 Result

Copyright 2012-2024 Standard Performance Evaluation Corporation

Cisco Systems

SPECompG_peak2012 = 108

Cisco UCS C245 M8 (AMD EPYC 9754, 2.25GHz)

SPECompG_base2012 = 104

OMP2012 license:9019


Test date: Apr-2023

Test sponsor: Cisco Systems

Hardware Availability: Jun-2024

Tested by: Cisco Systems

Software Availability: Feb-2024



Hardware

CPU Name: AMD EPYC 9754
 CPU Characteristics: Max Boost Clock up to 3.1 GHz
 CPU MHz: 2250
 CPU MHz Maximum: 3100
 FPU: Integrated
 CPU(s) enabled: 256 cores, 2 chips, 128 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: 256 MB I+D on chip per chip, 32 MB shared 8 cores
 Other Cache: None
 Memory: 1536 GB (24 x 64 GB 2Rx4 PC5-5600B-R, running at 4800 MHz)
 Disk Subsystem: 1 x 960 GB NVMe SSD
 Other Hardware: None
 Base Threads Run: 512

Continued on next page

Software

Operating System: SUSE Linux Enterprise Server 15 SP5, Kernel 5.14.21-150500.53-default
 Compiler: C/C++/Fortran: Version 2024.0.2.0 of Intel oneAPI DPC/C++
 Auto Parallel: Yes
 File System: xfs
 System State: Multi-user, run level 3
 Base Pointers: 64-bit
 Peak Pointers: 64-bit
 Other Software: None



SPEC OMPG2012 Result

Copyright 2012-2024 Standard Performance Evaluation Corporation

Cisco Systems

SPECompG_peak2012 = 108

Cisco UCS C245 M8 (AMD EPYC 9754, 2.25GHz)

SPECompG_base2012 = 104

OMP2012 license:9019
Test sponsor: Cisco Systems
Tested by: Cisco Systems

Test date: Apr-2023
Hardware Availability: Jun-2024
Software Availability: Feb-2024

Minimum Peak Threads: 256
Maximum Peak Threads: 512

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
350.md	512	9.41	492	<u>8.72</u>	<u>531</u>	8.65	535	512	<u>8.66</u>	<u>535</u>	8.65	535	8.67	534
351.bwaves	512	<u>63.7</u>	<u>71.1</u>	63.6	71.2	63.9	70.9	512	63.7	71.2	<u>63.8</u>	<u>71.0</u>	63.9	70.9
352.nab	512	67.7	57.5	<u>67.5</u>	<u>57.6</u>	67.4	57.7	512	<u>67.5</u>	<u>57.7</u>	67.2	57.9	67.5	57.7
357.bt331	512	41.4	115	<u>41.5</u>	<u>114</u>	41.8	114	512	41.9	113	<u>41.7</u>	<u>114</u>	41.0	115
358.botsalgn	512	39.5	110	39.4	110	<u>39.5</u>	<u>110</u>	512	39.4	110	<u>39.5</u>	<u>110</u>	39.5	110
359.botsspar	512	30.2	174	<u>30.4</u>	<u>173</u>	30.6	172	256	19.2	274	<u>19.2</u>	<u>274</u>	19.2	274
360.ilbdc	512	67.9	52.4	<u>67.9</u>	<u>52.5</u>	67.8	52.5	256	67.2	53.0	<u>67.1</u>	<u>53.1</u>	67.0	53.1
362.fma3d	512	72.6	52.3	<u>72.0</u>	<u>52.7</u>	71.4	53.3	512	71.8	52.9	<u>72.4</u>	<u>52.5</u>	74.5	51.0
363.swim	512	88.4	51.3	88.4	51.2	<u>88.4</u>	<u>51.2</u>	512	88.4	51.3	87.9	51.6	<u>88.0</u>	<u>51.4</u>
367.imagick	512	<u>53.9</u>	<u>131</u>	54.1	130	53.6	131	512	54.3	129	<u>53.9</u>	<u>130</u>	53.8	131
370.mgrid331	512	91.8	48.2	<u>91.8</u>	<u>48.1</u>	91.9	48.1	256	86.8	50.9	<u>86.7</u>	<u>51.0</u>	86.6	51.1
371.applu331	512	30.2	201	30.1	201	<u>30.1</u>	<u>201</u>	512	30.2	201	30.0	202	<u>30.1</u>	<u>201</u>
372.smithwa	512	<u>23.3</u>	<u>230</u>	23.3	230	23.6	227	512	23.3	230	23.3	230	<u>23.3</u>	<u>230</u>
376.kdtree	512	<u>49.4</u>	<u>91.1</u>	49.8	90.3	49.2	91.5	512	49.2	91.4	46.4	96.9	<u>48.6</u>	<u>92.5</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

Sysinfo program /home/omp2012/Docs/sysinfo
Revision 563 of 2016-06-10 (097295389cf6073d8c3b03fa376740a5)
running on localhost Fri Apr 21 18:23:25 2023

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/omp2012/Docs/config.html#sysinfo>

From /proc/cpuinfo

```
model name : AMD EPYC 9754 128-Core Processor
2 "physical id"s (chips)
512 "processors"
```

cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

```
cpu cores : 128
siblings : 256
physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 28 29 30 31 32 33
34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58
59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83
84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105
106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123
```

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2024 Standard Performance Evaluation Corporation

Cisco Systems

SPECompG_peak2012 = 108

Cisco UCS C245 M8 (AMD EPYC 9754, 2.25GHz)

SPECompG_base2012 = 104

OMP2012 license:9019

Test date: Apr-2023

Test sponsor: Cisco Systems

Hardware Availability: Jun-2024

Tested by: Cisco Systems

Software Availability: Feb-2024

Platform Notes (Continued)

```

124 125 126 127
physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 28 29 30 31 32 33
34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58
59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83
84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105
106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123
124 125 126 127
cache size : 1024 KB

```

From /proc/meminfo

```

MemTotal:      1584758888 kB
HugePages_Total:      0
Hugepagesize:      2048 kB

```

From /etc/*release* /etc/*version*

```

os-release:
NAME="SLES"
VERSION="15-SP4"
VERSION_ID="15.4"
PRETTY_NAME="SUSE Linux Enterprise Server 15 SP4"
ID="sles"
ID_LIKE="suse"
ANSI_COLOR="0;32"
CPE_NAME="cpe:/o:suse:sles:15:sp4"

```

uname -a:

```

Linux localhost 5.14.21-150400.22-default #1 SMP PREEMPT_DYNAMIC Wed May 11
06:57:18 UTC 2022 (49db222) x86_64 x86_64 x86_64 GNU/Linux

```

run-level 3 Apr 21 18:21

SPEC is set to: /home/omp2012

```

Filesystem      Type      Size      Used Avail Use% Mounted on
/dev/sdc2        xfs       893G      69G  825G   8% /

```

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS Cisco Systems, Inc. C245M8.4.3.4.270.0418240316 04/18/2024

Memory:

24x 0xCE00 M321R8GA0PB0-CWMCH 64 GB 2 rank 5600 MT/s

(End of data from sysinfo program)



SPEC OMPG2012 Result

Copyright 2012-2024 Standard Performance Evaluation Corporation

Cisco Systems

SPECompG_peak2012 = 108

Cisco UCS C245 M8 (AMD EPYC 9754, 2.25GHz)

SPECompG_base2012 = 104

OMP2012 license:9019

Test sponsor: Cisco Systems

Tested by: Cisco Systems

Test date: Apr-2023

Hardware Availability: Jun-2024

Software Availability: Feb-2024

General Notes

General OMP Library Settings

```

OMP_DYNAMIC           = FALSE
KMP_SCHEDULE          = static
KMP_LIBRARY           = turnaround
KMP_STACKSIZE         = 256M
KMP_BLOCKTIME         = infinite
KMP_AFFINITY          = granularity=fine,proclist=[0-7,8-15,16-23,24-31,32-39,
40-47,48-55,56-63,64-71,72-79,80-87,88-95,96-103,104-111,112-119,120-127,
128-135,136-143,144-151,152-159,160-167,168-175,176-183,184-191,192-199,
200-207,208-215,216-223,224-231,232-239,240-247,248-255,256-263,264-271,
272-279,280-287,288-295,296-303,304-311,312-319,320-327,328-335,336-343,
344-351,352-359,360-367,368-375,376-383,384-391,392-399,400-407,408-415,
416-423,424-431,432-439,440-447,448-455,456-463,464-471,472-479,480-487,
488-495,496-503,504-511],explicit

```

uEFI Setting notes:

Choose "Maximum Performance" operating mode and changed to "Custom" operating mode. Below items also configured:

- NUMA Nodes per Socket = NPS2
- DRAM Scrub Time = Disabled
- CPPC = Disabled
- Global C-state control = Disabled
-
-

Yes: The test sponsor attests, as of date of publication, the CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, the CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Spectre variant 2) is mitigated in the system as tested and documented.

OS tuning:

ulimit -s unlimited

Base Compiler Invocation

C benchmarks:

icx

C++ benchmarks:

icpx

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2024 Standard Performance Evaluation Corporation

Cisco Systems

SPECompG_peak2012 = 108

Cisco UCS C245 M8 (AMD EPYC 9754, 2.25GHz)

SPECompG_base2012 = 104

OMP2012 license:9019

Test date: Apr-2023

Test sponsor: Cisco Systems

Hardware Availability: Jun-2024

Tested by: Cisco Systems

Software Availability: Feb-2024

Base Compiler Invocation (Continued)

Fortran benchmarks:
ifx

Base Portability Flags

350.md: -FR
357.bt331: -mcmmodel=medium
363.swim: -mcmmodel=medium

Base Optimization Flags

C benchmarks:

352.nab: -w -m64 -std=c11 -Wno-implicit-function-declaration -Ofast
-mprefer-vector-width=512 -march=common-avx512 -ipo
-fopenmp -qopt-zmm-usage=high -ffast-math -fstrict-enums
-fstrict-vtable-pointers -fvirtual-function-elimination

358.botsalgn: Same as 352.nab

359.botsspar: Same as 352.nab

367.imagick: -w -m64 -std=c11 -Wno-implicit-function-declaration -Ofast
-mprefer-vector-width=512 -march=common-avx512 -ipo
-fopenmp -qopt-zmm-usage=high -ffast-math -fstrict-enums
-fstrict-vtable-pointers -fvirtual-function-elimination
-std=c99(*)

372.smithwa: Same as 352.nab

C++ benchmarks:

-w -m64 -std=c++14 -Ofast -mprefer-vector-width=512
-march=common-avx512 -ipo -fopenmp -qopt-zmm-usage=high -ffast-math
-fstrict-enums -fstrict-vtable-pointers

Fortran benchmarks:

-w -m64 -Ofast -mprefer-vector-width=512 -march=common-avx512 -ipo
-fopenmp -qopt-zmm-usage=high -align array128byte -ffinite-math-only
-fno-omit-frame-pointer -ipo1 -foptimize-sibling-calls -vec

(*) Indicates an optimization flag that was found in a portability variable.



SPEC OMPG2012 Result

Copyright 2012-2024 Standard Performance Evaluation Corporation

Cisco Systems

SPECompG_peak2012 = 108

Cisco UCS C245 M8 (AMD EPYC 9754, 2.25GHz)

SPECompG_base2012 = 104

OMP2012 license:9019

Test date: Apr-2023

Test sponsor: Cisco Systems

Hardware Availability: Jun-2024

Tested by: Cisco Systems

Software Availability: Feb-2024

Peak Compiler Invocation

C benchmarks:

icx

C++ benchmarks:

icpx

Fortran benchmarks:

ifx

Peak Portability Flags

350.md: -FR
357.bt331: -mcmmodel=medium
363.swim: -mcmmodel=medium

Peak Optimization Flags

C benchmarks:

352.nab: -w -m64 -std=c11 -Wno-implicit-function-declaration -Ofast
-mprefer-vector-width=512 -march=common-avx512 -ipo
-fopenmp -qopt-zmm-usage=high -ffast-math -fstrict-enums
-fstrict-vtable-pointers -fvirtual-function-elimination

358.botsalgn: Same as 352.nab

359.botsspar: Same as 352.nab

367.imagick: -w -m64 -std=c11 -Wno-implicit-function-declaration -Ofast
-mprefer-vector-width=512 -march=common-avx512 -ipo
-fopenmp -qopt-zmm-usage=high -ffast-math -fstrict-enums
-fstrict-vtable-pointers -fvirtual-function-elimination
-std=c99(*)

372.smithwa: Same as 352.nab

C++ benchmarks:

-w -m64 -std=c++14 -Ofast -mprefer-vector-width=512
-march=common-avx512 -ipo -fopenmp -qopt-zmm-usage=high -ffast-math
-fstrict-enums -fstrict-vtable-pointers

Fortran benchmarks:

-w -m64 -Ofast -mprefer-vector-width=512 -march=common-avx512 -ipo
-fopenmp -qopt-zmm-usage=high -align array128byte -ffinite-math-only
-fno-omit-frame-pointer -ipo1 -foptimize-sibling-calls -vec

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2024 Standard Performance Evaluation Corporation

Cisco Systems

SPECompG_peak2012 = 108

Cisco UCS C245 M8 (AMD EPYC 9754, 2.25GHz)

SPECompG_base2012 = 104

OMP2012 license:9019

Test date: Apr-2023

Test sponsor: Cisco Systems

Hardware Availability: Jun-2024

Tested by: Cisco Systems

Software Availability: Feb-2024

Peak Optimization Flags (Continued)

Fortran benchmarks (continued):

(*) Indicates an optimization flag that was found in a portability variable.

The flags files that were used to format this result can be browsed at

<http://www.spec.org/omp2012/flags/Intel-ic2024.2.0-OMP2012-linux64.html>

<http://www.spec.org/omp2012/flags/Cisco-Platform-Settings-AMD-v3-revA.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/omp2012/flags/Intel-ic2024.2.0-OMP2012-linux64.xml>

<http://www.spec.org/omp2012/flags/Cisco-Platform-Settings-AMD-v3-revA.xml>

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.

For other inquiries, please contact webmaster@spec.org.

Tested with SPEC OMP2012 v1.1.

Report generated on Wed May 29 12:16:51 2024 by SPEC OMP2012 PS/PDF formatter v541.

Originally published on 29 May 2024.

Standard Performance Evaluation Corporation

info@spec.org

<http://www.spec.org/>