



SPEC® CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECfp®_rate2006 = 25.9

ProLiant DL585 (AMD Opteron 854)

SPECfp_rate_base2006 = 24.1

CPU2006 license: 3


Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Apr-2006

Hardware Availability: Oct-2005

Software Availability: Mar-2006



Hardware

CPU Name: AMD Opteron 854
 CPU Characteristics: 2.8GHz, 1MB L2 cache
 CPU MHz: 2800
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 2,4 chips
 Primary Cache: 64 KB I + 64 KB D on chip per chip
 Secondary Cache: 1 MB I+D on chip per chip

Continued on next page

Software

Operating System: SuSE Linux Enterprise Server 9 (x86_64) SP 3
 SuSE kernel 2.6.5-7.244-smp
 Compiler: PathScale EKO Compiler Suite, Release 2.4
 PGI C Compiler 6.1-3 for Linux (64-bit)
 PGI Fortran Compiler 6.1-3 for Linux (64-bit)
 Auto Parallel: No
 File System: ext2
 System State: Multi-user run level 3
 Base Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECfp_rate2006 = 25.9

ProLiant DL585 (AMD Opteron 854)

SPECfp_rate_base2006 = 24.1

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Apr-2006

Hardware Availability: Oct-2005

Software Availability: Mar-2006

L3 Cache: None
Other Cache: None
Memory: 16 GB (8x2048 MB PC3200 CL3.0)
Disk Subsystem: 1x146GB 10K Ultra320 SCSI
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	2	782	34.7	<u>787</u>	<u>34.6</u>	788	34.5	2	<u>724</u>	<u>37.6</u>	718	37.9	726	37.4
416.gamess	2	1464	26.8	<u>1463</u>	<u>26.8</u>	1463	26.8	2	<u>1210</u>	<u>32.4</u>	1210	32.4	1210	32.4
433.milc	2	828	22.2	<u>822</u>	<u>22.3</u>	821	22.4	2	<u>812</u>	<u>22.6</u>	811	22.6	818	22.5
434.zeusmp	2	789	23.1	<u>790</u>	<u>23.0</u>	792	23.0	2	714	25.5	<u>714</u>	<u>25.5</u>	716	25.4
435.gromacs	2	610	23.4	<u>609</u>	<u>23.5</u>	608	23.5	2	548	26.1	<u>547</u>	<u>26.1</u>	547	26.1
436.cactusADM	2	1206	19.8	1217	19.6	<u>1208</u>	<u>19.8</u>	2	1175	20.3	1178	20.3	<u>1177</u>	<u>20.3</u>
437.leslie3d	2	876	21.5	<u>877</u>	<u>21.4</u>	880	21.4	2	<u>878</u>	<u>21.4</u>	877	21.4	878	21.4
444.namd	2	666	24.1	<u>666</u>	<u>24.1</u>	666	24.1	2	645	24.9	<u>645</u>	<u>24.9</u>	645	24.9
447.dealII	2	<u>634</u>	<u>36.1</u>	634	36.1	633	36.2	2	<u>541</u>	<u>42.3</u>	542	42.2	540	42.4
450.soplex	2	874	19.1	883	18.9	<u>882</u>	<u>18.9</u>	2	779	21.4	<u>781</u>	<u>21.4</u>	784	21.3
453.povray	2	334	31.9	334	31.9	<u>334</u>	<u>31.9</u>	2	297	35.8	<u>297</u>	<u>35.8</u>	297	35.8
454.calculix	2	1111	14.9	<u>1112</u>	<u>14.8</u>	1113	14.8	2	1067	15.5	1071	15.4	<u>1069</u>	<u>15.4</u>
459.GemsFDTD	2	1265	16.8	<u>1248</u>	<u>17.0</u>	1246	17.0	2	1020	20.8	<u>1020</u>	<u>20.8</u>	1021	20.8
465.tonto	2	<u>720</u>	<u>27.3</u>	718	27.4	722	27.3	2	708	27.8	707	27.9	<u>707</u>	<u>27.8</u>
470.lbm	2	1103	24.9	<u>1123</u>	<u>24.5</u>	1131	24.3	2	1122	24.5	<u>1127</u>	<u>24.4</u>	1130	24.3
481.wrf	2	814	27.5	<u>815</u>	<u>27.4</u>	815	27.4	2	814	27.5	<u>815</u>	<u>27.4</u>	815	27.4
482.sphinx3	2	1428	27.3	1448	26.9	<u>1440</u>	<u>27.1</u>	2	1359	28.7	<u>1361</u>	<u>28.6</u>	1363	28.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

BIOS Configuration Notes

Node Interleaving is Disabled

Other Configuration Notes

Taskset utility used to bind process to CPU(s)

Base Compiler Invocation

C benchmarks:
pathcc

C++ benchmarks:
pathCC

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECfp_rate2006 = 25.9

ProLiant DL585 (AMD Opteron 854)

SPECfp_rate_base2006 = 24.1

CPU2006 license: 3

Test date: Apr-2006

Test sponsor: Hewlett-Packard Company

Hardware Availability: Oct-2005

Tested by: Hewlett-Packard Company

Software Availability: Mar-2006

Base Compiler Invocation (Continued)

Fortran benchmarks:

pathf95

Benchmarks using both Fortran and C:

pathcc pathf95

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64
 436.cactusADM: -DSPEC_CPU_LP64 -fno-second-underscore
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64 -DSPEC_CPU_TABLE_WORKAROUND
 450.soplex: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX -fno-second-underscore
 482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-Ofast

C++ benchmarks:

-Ofast

Fortran benchmarks:

-Ofast

Benchmarks using both Fortran and C:

-Ofast

Peak Compiler Invocation

C benchmarks (except as noted below):

pgcc

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECfp_rate2006 = 25.9

ProLiant DL585 (AMD Opteron 854)

SPECfp_rate_base2006 = 24.1

CPU2006 license: 3

Test date: Apr-2006

Test sponsor: Hewlett-Packard Company

Hardware Availability: Oct-2005

Tested by: Hewlett-Packard Company

Software Availability: Mar-2006

Peak Compiler Invocation (Continued)

470.lbm: pathcc

C++ benchmarks:

pathCC

Fortran benchmarks (except as noted below):

pathf95

434.zeusmp: pgf90

459.GemsFDTD: pgf90

Benchmarks using both Fortran and C (except as noted below):

pathcc pathf95

454.calculix: pgcc pgf90

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64
 436.cactusADM: -DSPEC_CPU_LP64 -fno-second-underscore
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.deall: -DSPEC_CPU_LP64 -DSPEC_CPU_TABLE_WORKAROUND
 450.soplex: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -Mnomain
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX -fno-second-underscore
 482.sphinx3: -DSPEC_CPU_LP64

Peak Optimization Flags

C benchmarks:

433.milc: -c9x -Mphi(pass 1) -Mipa=fast(pass 2) -Mipa=inline(pass 2)
 -Mipa=nolocalarg(pass 2) -Mipa=vestigial(pass 2)
 -Mpfo(pass 2) -tp k8-64 -fastsse

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECfp_rate2006 = 25.9

ProLiant DL585 (AMD Opteron 854)

SPECfp_rate_base2006 = 24.1

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Apr-2006

Hardware Availability: Oct-2005

Software Availability: Mar-2006

Peak Optimization Flags (Continued)

470.lbm: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast

482.sphinx3: -c9x -tp k8-64 -fastsse -Mfprelaxed -Mipa=fast
-Mipa=inline -Msignextend

C++ benchmarks:

444.namd: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast

447.dealII: -Ofast -m32 -fno-exceptions

450.soplex: -m32 -O3 -OPT:IEEE_arith=3 -CG:load_exe=0 -CG:movnti=1
-LNO:minvariant=off -fno-exceptions

453.povray: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
-fno-fast-math

Fortran benchmarks:

410.bwaves: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
-OPT:Ofast -OPT:IEEE_arith=3 -LNO:blocking=off
-LNO:ignore_feedback=off

416.gamess: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O2
-OPT:Ofast -OPT:ro=3 -OPT:unroll_size=256

434.zeusmp: -Mpfi(pass 1) -Mipa=fast(pass 2) -Mipa=inline(pass 2)
-Mpfo(pass 2) -tp k8-64 -fastsse -Mfprelaxed -Mvect=fuse

437.leslie3d: -O3 -OPT:Ofast

459.GemsFDTD: -tp k8-64 -fastsse -Munroll=n:4

465.tonto: -Ofast -CG:local_fwd_sched=on -IPA:plimit=525

Benchmarks using both Fortran and C:

435.gromacs: -O3 -OPT:rsqrt=2 -OPT:ro=3

436.cactusADM: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
-LNO:prefetch_ahead=5 -LNO:ou_prod_max=10 -LNO:full_unroll=5
-ipa

454.calculix: -c9x -tp k8-64 -fastsse -Mnolre -Mipa=fast -Mipa=inline

481.wrf: basepeak = yes



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECfp_rate2006 = 25.9

ProLiant DL585 (AMD Opteron 854)

SPECfp_rate_base2006 = 24.1

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Apr-2006

Hardware Availability: Oct-2005

Software Availability: Mar-2006

Peak Other Flags

C benchmarks (except as noted below):

-w

470.lbm: No flags used

Fortran benchmarks:

434.zeusmp: -w

459.GemsFDTD: -w

Benchmarks using both Fortran and C:

454.calculix: -w

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090715.04.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090715.04.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v91.
Report generated on Tue Sep 13 11:16:48 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 24 August 2006.