



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint®2006 = 12.9

CELSIUS V840, AMD Opteron 2218

SPECint_base2006 = 11.6

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jan-2007

Hardware Availability: Nov-2006

Software Availability: Aug-2006



Hardware

CPU Name: AMD Opteron 2218
 CPU Characteristics: Dual Core, 2.6 GHz, 2 MB L2-cache
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8x2GB DDR2-667 CL5 dual rank ECC DIMMs registered)
 Disk Subsystem: SATA II, 80 GB
 Other Hardware: None

Software

Operating System: SLES 10 for AMD64/EM64T
 Compiler: QLogic PathScale Compiler Suite, Release 2.5
 SmartHeap 8.0 32 bit Library for Linux
 Auto Parallel: No
 File System: ext3
 System State: Multi-User SuSE Run Level 3
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: None



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint2006 = 12.9

CELSIUS V840, AMD Opteron 2218

SPECint_base2006 = 11.6

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jan-2007

Hardware Availability: Nov-2006

Software Availability: Aug-2006

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	862	11.3	842	11.6	837	11.7	698	14.0	680	14.4	678	14.4
401.bzip2	989	9.76	999	9.66	991	9.74	974	9.91	971	9.94	975	9.89
403.gcc	866	9.30	864	9.32	866	9.30	722	11.1	721	11.2	721	11.2
429.mcf	1228	7.43	1228	7.42	1228	7.42	858	10.6	859	10.6	858	10.6
445.gobmk	797	13.2	796	13.2	795	13.2	687	15.3	688	15.3	686	15.3
456.hmmmer	761	12.3	761	12.3	756	12.3	610	15.3	633	14.7	639	14.6
458.sjeng	1003	12.1	1006	12.0	1004	12.1	930	13.0	931	13.0	929	13.0
462.libquantum	1314	15.8	1309	15.8	1324	15.7	1304	15.9	1307	15.9	1307	15.9
464.h264ref	1112	19.9	1120	19.8	1118	19.8	1054	21.0	1055	21.0	1057	20.9
471.omnetpp	657	9.52	665	9.40	661	9.46	656	9.53	656	9.53	656	9.52
473.astar	754	9.31	753	9.32	752	9.33	724	9.69	724	9.70	722	9.72
483.xalancbmk	498	13.9	497	13.9	498	13.9	488	14.1	484	14.2	486	14.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

powersave -f is applied to set CPU to maximum frequency prior to run
stacksize is set to unlimited prior to run

General Notes

Binaries supplied by AMD
Compilation done on an Opteron-based system
running SuSE 9.3 (Kernel 2.6.5.7)

BIOS default settings with
Node memory interleave disabled, SRAT enabled

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>

Base Compiler Invocation

C benchmarks:
pathcc

C++ benchmarks:
pathCC



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint2006 = 12.9

CELSIUS V840, AMD Opteron 2218

SPECint_base2006 = 11.6

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jan-2007

Hardware Availability: Nov-2006

Software Availability: Aug-2006

Base Portability Flags

```

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

```

Base Optimization Flags

```

C benchmarks:
-Ofast

C++ benchmarks:
-Ofast -m32
-L/spec/mpaton/6v1.0/amd512K8.lib/microquill/lib -lsmartheap

```

Base Other Flags

```

C benchmarks:
-IPA:max_jobs=2

C++ benchmarks:
-IPA:max_jobs=2

```

Peak Compiler Invocation

```

C benchmarks:
pathcc

C++ benchmarks:
pathCC

```

Peak Portability Flags

```

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64

```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint2006 = 12.9

CELSIUS V840, AMD Opteron 2218

SPECint_base2006 = 11.6

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jan-2007

Hardware Availability: Nov-2006

Software Availability: Aug-2006

Peak Portability Flags (Continued)

456.hmmer: -DSPEC_CPU_LP64
 458.sjeng: -DSPEC_CPU_LP64
 462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
 464.h264ref: -DSPEC_CPU_LP64
 483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
 401.bz2: -O3 -LNO:ou_prod_max=10 -OPT:Ofast -OPT:alias=disjoint
 403.gcc: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -m32 -O3
 -OPT:Ofast
 429.mcf: -m32 -O2 -ipa
 -L/spec/mpaton/6v1.0/amd512K8.lib/microquill/lib -lsmarheap
 445.gobmk: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
 -OPT:alias=disjoint -LNO:simd=0 -LNO:minvariant=off
 -WOPT:retype_expr=on
 456.hmmer: -O2 -OPT:alias=disjoint -WOPT:aggstr=0 -CG:cflow=0
 458.sjeng: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
 -IPA:plimit=50000 -IPA:pu_reorder=2
 462.libquantum: -O3 -ipa -CG:local_fwd_sched=on -IPA:space=1000
 464.h264ref: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
 -IPA:plimit=20000 -OPT:alias=disjoint -LNO:prefetch=0

C++ benchmarks:

471.omnetpp: -Ofast -IPA:pu_reorder=2 -CG:gcm=off -m32
 -L/spec/mpaton/6v1.0/amd512K8.lib/microquill/lib -lsmarheap
 473.astar: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
 -m32
 -L/spec/mpaton/6v1.0/amd512K8.lib/microquill/lib -lsmarheap
 483.xalancbmk: -Ofast -m32 -OPT:unroll_times_max=8
 -L/spec/mpaton/6v1.0/amd512K8.lib/microquill/lib -lsmarheap



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint2006 = 12.9

CELSIUS V840, AMD Opteron 2218

SPECint_base2006 = 11.6

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jan-2007

Hardware Availability: Nov-2006

Software Availability: Aug-2006

Peak Other Flags

C benchmarks:

-IPA:max_jobs=2

C++ benchmarks:

-IPA:max_jobs=2

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.25.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.25.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:26:34 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 20 February 2007.