



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

SPECfp<sup>®</sup>\_rate2006 = 54.1

ProLiant ML350 G5  
(2.66 GHz, Intel Xeon processor X5355)

SPECfp\_rate\_base2006 = 53.3

CPU2006 license: 3


Test date: Feb-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Jan-2007

Tested by: Hewlett-Packard Company

Software Availability: Nov-2006



### Hardware

CPU Name: Intel Xeon X5355  
 CPU Characteristics: 2.66 GHz, 2x4 MB L2 shared, 1333 MHz bus  
 CPU MHz: 2666  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

### Software

Operating System: SuSE Linux Enterprise Server 10 EM64T kernel 2.6.16.21-0.8-smp  
 Compiler: Intel C++ Compiler for Intel EM64T-based applications, Version 9.1  
 Package ID l\_cc\_c\_9.1.045 Build no 20061101  
 Intel Fortran Compiler for Intel EM64T-based applications, Version 9.1  
 Package ID l\_fc\_c\_9.1.040 Build no 20061101  
 Auto Parallel: No

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

SPECfp\_rate2006 = 54.1

ProLiant ML350 G5  
(2.66 GHz, Intel Xeon processor X5355)

SPECfp\_rate\_base2006 = 53.3

CPU2006 license: 3  
Test sponsor: Hewlett-Packard Company  
Tested by: Hewlett-Packard Company

Test date: Feb-2007  
Hardware Availability: Jan-2007  
Software Availability: Nov-2006

L3 Cache: None  
Other Cache: None  
Memory: 8 GB (4x2 GB PC2-5300 CL5)  
Disk Subsystem: 4x36 GB 10 K SAS  
Other Hardware: None

File System: ext2  
System State: Multi-user run level 3  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3303	32.9	3315	32.8	<b>3305</b>	<b>32.9</b>	8	<b>3312</b>	<b>32.8</b>	3302	32.9	3316	32.8
416.gamess	8	1072	146	<b>1073</b>	<b>146</b>	1075	146	8	1162	135	1170	134	<b>1165</b>	<b>134</b>
433.milc	8	<b>3462</b>	<b>21.2</b>	3455	21.3	3467	21.2	8	<b>3472</b>	<b>21.2</b>	3468	21.2	3475	21.1
434.zeusmp	8	1263	57.7	<b>1263</b>	<b>57.7</b>	1261	57.8	8	1273	57.2	<b>1274</b>	<b>57.2</b>	1279	56.9
435.gromacs	8	<b>454</b>	<b>126</b>	454	126	455	125	8	440	130	441	130	<b>440</b>	<b>130</b>
436.cactusADM	8	1533	62.3	1521	62.9	<b>1533</b>	<b>62.4</b>	8	<b>1552</b>	<b>61.6</b>	1555	61.5	1547	61.8
437.leslie3d	8	3426	22.0	<b>3431</b>	<b>21.9</b>	3440	21.9	8	3426	22.0	<b>3426</b>	<b>21.9</b>	3427	21.9
444.namd	8	575	112	<b>576</b>	<b>111</b>	576	111	8	584	110	586	110	<b>584</b>	<b>110</b>
447.dealII	8	719	127	733	125	<b>728</b>	<b>126</b>	8	738	124	<b>729</b>	<b>126</b>	708	129
450.soplex	8	2361	28.3	<b>2364</b>	<b>28.2</b>	2367	28.2	8	2335	28.6	<b>2335</b>	<b>28.6</b>	2338	28.5
453.povray	8	292	146	<b>293</b>	<b>145</b>	293	145	8	<b>221</b>	<b>192</b>	222	192	221	192
454.calculix	8	<b>645</b>	<b>102</b>	655	101	644	102	8	636	104	631	105	<b>632</b>	<b>104</b>
459.GemsFDTD	8	4300	19.7	4302	19.7	<b>4300</b>	<b>19.7</b>	8	4304	19.7	<b>4303</b>	<b>19.7</b>	4302	19.7
465.tonto	8	1161	67.8	<b>1168</b>	<b>67.4</b>	1169	67.4	8	1130	69.6	1151	68.4	<b>1139</b>	<b>69.1</b>
470.lbm	8	6969	15.8	<b>6962</b>	<b>15.8</b>	6962	15.8	8	6956	15.8	<b>6956</b>	<b>15.8</b>	6972	15.8
481.wrf	8	2178	41.0	<b>2177</b>	<b>41.0</b>	2175	41.1	8	<b>2182</b>	<b>41.0</b>	2188	40.8	2178	41.0
482.sphinx3	8	3585	43.5	<b>3581</b>	<b>43.5</b>	3578	43.6	8	3556	43.9	<b>3556</b>	<b>43.9</b>	3554	43.9

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Platform Notes

Power Regulator set to Static High Performance Mode in BIOS.  
Adjacent Sector Prefetch Disabled in BIOS.  
"ulimit -s unlimited" set

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECfp\_rate2006 = 54.1**

ProLiant ML350 G5  
(2.66 GHz, Intel Xeon processor X5355)

**SPECfp\_rate\_base2006 = 53.3**

**CPU2006 license:** 3

**Test date:** Feb-2007

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Jan-2007

**Tested by:** Hewlett-Packard Company

**Software Availability:** Nov-2006

## Base Compiler Invocation (Continued)

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
 416.gamess: -DSPEC\_CPU\_LP64  
 433.milc: -DSPEC\_CPU\_LP64  
 434.zeusmp: -DSPEC\_CPU\_LP64  
 435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
 436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
 437.leslie3d: -DSPEC\_CPU\_LP64  
 444.namd: -DSPEC\_CPU\_LP64  
 447.dealII: -DSPEC\_CPU\_LP64  
 450.soplex: -DSPEC\_CPU\_LP64  
 453.povray: -DSPEC\_CPU\_LP64  
 454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
 459.GemsFDTD: -DSPEC\_CPU\_LP64  
 465.tonto: -DSPEC\_CPU\_LP64  
 470.lbm: -DSPEC\_CPU\_LP64  
 481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
 482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast

## Peak Compiler Invocation

C benchmarks:

icc

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECfp\_rate2006 = 54.1**

ProLiant ML350 G5  
(2.66 GHz, Intel Xeon processor X5355)

**SPECfp\_rate\_base2006 = 53.3**

**CPU2006 license:** 3

**Test date:** Feb-2007

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Jan-2007

**Tested by:** Hewlett-Packard Company

**Software Availability:** Nov-2006

## Peak Compiler Invocation (Continued)

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:  
-prof\_gen(pass 1) -prof\_use(pass 2) -fast -auto\_ilp32

C++ benchmarks:  
-prof\_gen(pass 1) -prof\_use(pass 2) -fast -auto\_ilp32

Fortran benchmarks:  
-prof\_gen(pass 1) -prof\_use(pass 2) -fast -auto\_ilp32

Benchmarks using both Fortran and C:  
-prof\_gen(pass 1) -prof\_use(pass 2) -fast -auto\_ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/hp-ic91-flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/hp-ic91-flags.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 10:27:12 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 20 February 2007.