



SPEC[®] CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint[®]_rate2006 = 61.0

ProLiant BL460c
(1.86 GHz, Intel Xeon processor E5320)

SPECint_rate_base2006 = 59.2

CPU2006 license: 3


Test date: Feb-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Jan-2007

Tested by: Hewlett-Packard Company

Software Availability: Nov-2006



Hardware

CPU Name: Intel Xeon E5320
 CPU Characteristics: 1.86 GHz, 2x4 MB L2 shared, 1066 MHz system bus
 CPU MHz: 1860
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8x2 GB PC2-5300 CL5)
 Disk Subsystem: 1x72 GB 10k SAS
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise x64 Edition SP1
 Compiler: Intel C++ Compiler for 32-bit applications, Version 9.1, Build 20061103Z
 Package ID: W_CC_C_9.1.033
 Microsoft Visual Studio .NET 2003 (v7.1.3088, for libraries)
 Auto Parallel: No
 File System: NTFS
 System State: Default
 Base Pointers: 32-bit
 Peak Pointers: 32-bit
 Other Software: MicroQuill SmartHeap Library 8.0



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 61.0

ProLiant BL460c
(1.86 GHz, Intel Xeon processor E5320)

SPECint_rate_base2006 = 59.2

CPU2006 license: 3

Test date: Feb-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Jan-2007

Tested by: Hewlett-Packard Company

Software Availability: Nov-2006

Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	750	104	750	104	752	104	8	687	114	689	114	687	114
401.bzip2	8	1324	58.3	1320	58.5	1323	58.3	8	1300	59.4	1297	59.5	1300	59.4
403.gcc	8	2346	27.5	2410	26.7	2411	26.7	8	2440	26.4	2421	26.6	2471	26.1
429.mcf	8	1463	49.9	1466	49.8	1460	50.0	8	1463	49.9	1466	49.8	1460	50.0
445.gobmk	8	889	94.4	888	94.5	889	94.4	8	791	106	791	106	791	106
456.hammer	8	1200	62.2	1207	61.9	1206	61.9	8	1175	63.5	1173	63.6	1173	63.6
458.sjeng	8	1071	90.4	1078	89.8	1078	89.8	8	989	97.8	989	97.8	991	97.7
462.libquantum	8	7083	23.4	7076	23.4	7067	23.5	8	7071	23.4	7074	23.4	7074	23.4
464.h264ref	8	1165	152	1174	151	1173	151	8	1154	153	1151	154	1153	154
471.omnetpp	8	1418	35.2	1423	35.1	1420	35.2	8	1404	35.6	1405	35.6	1403	35.6
473.astar	8	1170	48.0	1170	48.0	1170	48.0	8	1176	47.8	1175	47.8	1174	47.8
483.xalancbmk	8	756	73.0	760	72.6	761	72.5	8	741	74.5	745	74.1	744	74.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

Power Regulator set to Static High Performance Mode in BIOS.
Adjacent Sector Prefetch disabled in BIOS.

Base Compiler Invocation

C benchmarks:
icl -Qvc7.1 -Qc99
C++ benchmarks:
icl -Qvc7.1

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

Base Optimization Flags

C benchmarks:
-fast /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 61.0

ProLiant BL460c
(1.86 GHz, Intel Xeon processor E5320)

SPECint_rate_base2006 = 59.2

CPU2006 license: 3

Test date: Feb-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Jan-2007

Tested by: Hewlett-Packard Company

Software Availability: Nov-2006

Base Optimization Flags (Continued)

C++ benchmarks:

```
-fast -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

Peak Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Peak Portability Flags

```
403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
```

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000
shlw32m.lib -link /FORCE:MULTIPLE
```

```
401.bzip2: Same as 400.perlbench
```

```
403.gcc: Same as 400.perlbench
```

```
429.mcf: basepeak = yes
```

```
445.gobmk: Same as 400.perlbench
```

```
456.hmmmer: Same as 400.perlbench
```

```
458.sjeng: Same as 400.perlbench
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 61.0

ProLiant BL460c
(1.86 GHz, Intel Xeon processor E5320)

SPECint_rate_base2006 = 59.2

CPU2006 license: 3

Test date: Feb-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Jan-2007

Tested by: Hewlett-Packard Company

Software Availability: Nov-2006

Peak Optimization Flags (Continued)

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 400.perlbench

C++ benchmarks:

-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/hp-ic91-flags.20090715.02.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/hp-ic91-flags.20090715.02.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:38:06 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 6 March 2007.