



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B260 (Intel Xeon processor E5335, 2.00GHz)

SPECfp®_rate2006 = 44.8

SPECfp_rate_base2006 = 43.8

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Feb-2007

Hardware Availability: Jan-2007

Software Availability: Dec-2006



Hardware

CPU Name: Intel Xeon E5335
CPU Characteristics: 2.00 GHz, 8MB L2, 1333MHz bus
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1 to 2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores

Software

Operating System: Windows Server 2003 Enterprise Edition (32 bits)
Service Pack1
Compiler: Intel C++ Compiler for IA32 version 9.1
Package ID W_CC_C_9.1.033 Build no 20061103Z
Intel Fortran Compiler for IA32 version 9.1
Package ID W_FC_C_9.1.033 Build no 20061103Z
Microsoft Visual Studio .NET 2003 (lib & linker)
Auto Parallel: No
File System: NTFS
System State: Default

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B260 (Intel Xeon processor E5335, 2.00GHz)

SPECfp_rate2006 = 44.8

SPECfp_rate_base2006 = 43.8

CPU2006 license: 20

Test date: Feb-2007

Test sponsor: Bull SAS

Hardware Availability: Jan-2007

Tested by: Bull SAS

Software Availability: Dec-2006

L3 Cache:	None	Base Pointers:	32-bit
Other Cache:	None	Peak Pointers:	32-bit
Memory:	8 GB (2GB DIMMx4, FB-DIMM PC2-5300F ECC CL5)	Other Software:	MicroQuill SmartHeap Library 8.0 (shlw32M.lib)
Disk Subsystem:	73 GB SAS, 10000RPM		
Other Hardware:	None		

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3568	30.5	3565	30.5	3565	30.5	8	3560	30.5	3567	30.5	3563	30.5
416.gamess	8	1665	94.1	1665	94.1	1665	94.1	8	1670	93.8	1670	93.8	1669	93.8
433.milc	8	4122	17.8	4123	17.8	4125	17.8	8	4116	17.8	4119	17.8	4117	17.8
434.zeusmp	8	1363	53.4	1371	53.1	1354	53.8	8	1364	53.4	1375	53.0	1381	52.7
435.gromacs	8	629	90.8	628	90.9	630	90.7	8	621	92.0	621	92.0	622	91.9
436.cactusADM	8	1616	59.2	1615	59.2	1615	59.2	8	1611	59.3	1611	59.3	1611	59.4
437.leslie3d	8	3637	20.7	3639	20.7	3631	20.7	8	3638	20.7	3639	20.7	3633	20.7
444.namd	8	796	80.6	796	80.7	797	80.5	8	784	81.9	783	81.9	784	81.8
447.dealII	8	1013	90.4	983	93.1	991	92.4	8	892	103	919	99.6	904	101
450.soplex	8	2710	24.6	2718	24.6	2715	24.6	8	2675	24.9	2676	24.9	2658	25.1
453.povray	8	375	113	375	114	375	113	8	296	144	296	144	296	144
454.calculix	8	929	71.1	928	71.1	935	70.6	8	922	71.6	921	71.6	922	71.6
459.GemsFDTD	8	4664	18.2	4653	18.2	4658	18.2	8	4671	18.2	4669	18.2	4668	18.2
465.tonto	8	1982	39.7	2006	39.2	1988	39.6	8	1929	40.8	1941	40.6	1955	40.3
470.lbm	8	7049	15.6	7050	15.6	7056	15.6	8	7057	15.6	7056	15.6	7060	15.6
481.wrf	8	2379	37.6	2379	37.6	2365	37.8	8	2372	37.7	2382	37.5	2379	37.6
482.sphinx3	8	3672	42.5	3670	42.5	3671	42.5	8	3770	41.4	3767	41.4	3770	41.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Base Compiler Invocation

C benchmarks:

 icl -Qvc7.1 -Qc99

C++ benchmarks:

 icl -Qvc7.1

Fortran benchmarks:

 ifort

Benchmarks using both Fortran and C:

 icl -Qvc7.1 -Qc99 ifort



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B260 (Intel Xeon processor E5335, 2.00GHz)

SPECfp_rate2006 = 44.8

SPECfp_rate_base2006 = 43.8

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Feb-2007

Hardware Availability: Jan-2007

Software Availability: Dec-2006

Base Portability Flags

```
436.cactusADM: -Qlowercase /assume:underscore  
444.namd: -TP  
447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG  
             -DBOOST_NO_INTRINSIC_WCHAR_T  
453.povray: -DSPEC_CPU_WINDOWS_ICL  
454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase  
481.wrf: -DSPEC_CPU_WINDOWS_ICL
```

Base Optimization Flags

C benchmarks:

```
-fast /F9500000000 shlw32m.lib           -link /FORCE:MULTIPLE
```

C++ benchmarks:

```
-fast -Qcxx_features /F9500000000 shlw32m.lib  
      -link /FORCE:MULTIPLE
```

Fortran benchmarks:

```
-fast /F9500000000           -link /FORCE:MULTIPLE
```

Benchmarks using both Fortran and C:

```
-fast /F9500000000           -link /FORCE:MULTIPLE
```

Peak Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Fortran benchmarks:

```
ifort
```

Benchmarks using both Fortran and C:

```
icl -Qvc7.1 -Qc99 ifort
```

Peak Portability Flags

```
436.cactusADM: -Qlowercase /assume:underscore  
444.namd: -TP  
447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG  
             -DBOOST_NO_INTRINSIC_WCHAR_T
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B260 (Intel Xeon processor
E5335, 2.00GHz)

SPECfp_rate2006 = 44.8

SPECfp_rate_base2006 = 43.8

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Feb-2007

Hardware Availability: Jan-2007

Software Availability: Dec-2006

Peak Portability Flags (Continued)

453.povray: -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase
481.wrf: -DSPEC_CPU_WINDOWS_ICL

Peak Optimization Flags

C benchmarks:

```
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F9500000000 shlw32m.lib  
-link /FORCE:MULTIPLE
```

C++ benchmarks:

```
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features  
/F9500000000 shlw32m.lib -link /FORCE:MULTIPLE
```

Fortran benchmarks:

```
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F9500000000  
-link /FORCE:MULTIPLE
```

Benchmarks using both Fortran and C:

```
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F9500000000  
-link /FORCE:MULTIPLE
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/flags.20090714.00.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/flags.20090714.00.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 10:45:07 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 20 March 2007.