



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint_rate2006 = Not Run

PowerEdge 2970 (AMD Opteron 2212 HE, 2.00GHz)

SPECint_rate_base2006 = 36.0

CPU2006 license: 55


Test date: Mar-2007

Test sponsor: Dell Inc.

Hardware Availability: Apr-2007

Tested by: Dell Inc.

Software Availability: Aug-2006



Hardware

CPU Name: AMD Opteron 2212 HE
 CPU Characteristics:
 CPU MHz: 2000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8x2GB, DDR2-667 CL5 ECC Dual Rank)
 Disk Subsystem: SAS, 73 GB
 Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Server 10 64-bit kernel
 Compiler: QLogic PathScale Compiler Suite, Release 2.5
 Auto Parallel: No
 File System: ReiserFS
 System State: Multi-user, run level 3
 Base Pointers: 32/64-bit
 Peak Pointers: Not Applicable
 Other Software: SmartHeap 8.0 32 bit Library for Linux



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint_rate2006 = Not Run

PowerEdge 2970 (AMD Opteron 2212 HE, 2.00GHz)

SPECint_rate_base2006 = 36.0

CPU2006 license: 55

Test date: Mar-2007

Test sponsor: Dell Inc.

Hardware Availability: Apr-2007

Tested by: Dell Inc.

Software Availability: Aug-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	1077	36.3	1084	36.1	<u>1078</u>	<u>36.2</u>							
401.bzip2	4	1270	30.4	<u>1272</u>	<u>30.3</u>	1273	30.3							
403.gcc	4	<u>1127</u>	<u>28.6</u>	1120	28.8	1130	28.5							
429.mcf	4	1484	24.6	<u>1485</u>	<u>24.6</u>	1486	24.6							
445.gobmk	4	1029	40.8	<u>1029</u>	<u>40.8</u>	1029	40.8							
456.hammer	4	989	37.7	<u>989</u>	<u>37.7</u>	987	37.8							
458.sjeng	4	<u>1295</u>	<u>37.4</u>	1296	37.4	1295	37.4							
462.libquantum	4	<u>1823</u>	<u>45.5</u>	1822	45.5	1829	45.3							
464.h264ref	4	1449	61.1	<u>1480</u>	<u>59.8</u>	1481	59.8							
471.omnetpp	4	822	30.4	816	30.6	<u>820</u>	<u>30.5</u>							
473.astar	4	962	29.2	<u>962</u>	<u>29.2</u>	960	29.2							
483.xalancbmk	4	632	43.7	<u>632</u>	<u>43.6</u>	634	43.5							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Taskset utility used to bind CPU(s) to processes
Binaries were built on SuSE Linux Enterprise Server 9 SP3 64-bit

Base Compiler Invocation

C benchmarks:
pathcc

C++ benchmarks:
pathCC

Base Portability Flags

```
400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hammer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX
```



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint_rate2006 = Not Run

PowerEdge 2970 (AMD Opteron 2212 HE, 2.00GHz)

SPECint_rate_base2006 = 36.0

CPU2006 license: 55

Test date: Mar-2007

Test sponsor: Dell Inc.

Hardware Availability: Apr-2007

Tested by: Dell Inc.

Software Availability: Aug-2006

Base Optimization Flags

C benchmarks:
-Ofast

C++ benchmarks:
-Ofast -m32
-L/spec/mpaton/6v1.0/amd512K8.lib/microquill/lib -lsmartheap

Base Other Flags

C benchmarks:
-IPA:max_jobs=2

C++ benchmarks:
-IPA:max_jobs=2

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.25.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.25.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:54:06 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 3 April 2007.