



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 2900 (Intel Xeon processor 5130,
2.00GHz)

SPECint_rate2006 = Not Run

SPECint_rate_base2006 = 41.6

CPU2006 license: 55


Test date: Mar-2007

Test sponsor: Dell Inc.

Hardware Availability: Jul-2006

Tested by: Dell Inc.

Software Availability: Nov-2006



Hardware

CPU Name: Intel Xeon 5130
CPU Characteristics: 1333 MHz Bus Speed
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4 MB I+D on chip per chip
L3 Cache: None
Other Cache: None
Memory: 16 GB (8 x 2 GB 667MHz CL5 DDR2 FB-DIMM SDRAM)
Disk Subsystem: 1 x 73 GB SAS 15k RPM
Other Hardware: None

Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler: Intel C++ Compiler 9.1 for IA32 (20061103Z)
Microsoft Visual Studio 2005
Auto Parallel: No
File System: NTFS
System State: Default
Base Pointers: 32-bit
Peak Pointers: Not Applicable
Other Software: MicroQuill SmartHeap Library 8.0



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 2900 (Intel Xeon processor 5130,
2.00GHz)

SPECint_rate2006 = Not Run

SPECint_rate_base2006 = 41.6

CPU2006 license: 55

Test date: Mar-2007

Test sponsor: Dell Inc.

Hardware Availability: Jul-2006

Tested by: Dell Inc.

Software Availability: Nov-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	685	57.0	685	57.0	686	57.0							
401.bzip2	4	1027	37.6	1024	37.7	1025	37.6							
403.gcc	4	1399	23.0	1395	23.1	1409	22.9							
429.mcf	4	805	45.3	805	45.3	805	45.3							
445.gobmk	4	810	51.8	809	51.8	810	51.8							
456.hmmer	4	1117	33.4	1116	33.4	1117	33.4							
458.sjeng	4	996	48.6	996	48.6	996	48.6							
462.libquantum	4	2673	31.0	2682	30.9	2683	30.9							
464.h264ref	4	1067	83.0	1066	83.0	1066	83.0							
471.omnetpp	4	784	31.9	784	31.9	784	31.9							
473.astar	4	818	34.3	816	34.4	818	34.3							
483.xalancbmk	4	545	50.6	545	50.6	545	50.6							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

Snoop Filter enabled in BIOS

General Notes

32-bit binaries were built on Windows XP Professional x64 Edition

Base Compiler Invocation

C benchmarks:
icl -Qc99

C++ benchmarks:
icl

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32

464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

483.xalancbmk: -Qoption,cpp, --no_wchar_t_keyword



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 2900 (Intel Xeon processor 5130,
2.00GHz)

SPECint_rate2006 = Not Run

SPECint_rate_base2006 = 41.6

CPU2006 license: 55

Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Mar-2007

Hardware Availability: Jul-2006

Software Availability: Nov-2006

Base Optimization Flags

C benchmarks:

-fast /F512000000 shlw32M.lib

-link /FORCE:MULTIPLE

C++ benchmarks:

-fast -Qcxx_features /F512000000 shlw32M.lib
-link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/dell.cpu2006.ic91.flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/dell.cpu2006.ic91.flags.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 11:57:14 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 17 April 2007.