



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon processor 5150,
2.66 GHz

SPECint_rate2006 = 55.3

SPECint_rate_base2006 = 52.7

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Apr-2007

Hardware Availability: Jul-2006

Software Availability: Feb-2007



Hardware

CPU Name: Intel Xeon 5150
CPU Characteristics: 1333 MHz system bus
CPU MHz: 2667
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4 MB I+D on chip per chip
L3 Cache: None
Other Cache: None
Memory: 8 GB (8x1 GB DDR2 PC2-5300F, 2 rank, CAS 5-5-5, with ECC)
Disk Subsystem: SAS (36GB 10000 rpm)
Other Hardware: None

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp on an x86_64
Compiler: Intel C++ Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package-ID: l_cc_p_9.1.047
Auto Parallel: No
File System: ext2
System State: Multiuser, Runlevel 3
Base Pointers: 32-bit
Peak Pointers: 32/64-bit
Other Software: Smart Heap Library, Version 8.1



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon processor 5150,
2.66 GHz

SPECint_rate2006 = 55.3

SPECint_rate_base2006 = 52.7

CPU2006 license: 22

Test date: Apr-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Jul-2006

Tested by: Fujitsu Siemens Computers

Software Availability: Feb-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	567	69.0	560	69.8	557	70.1	4	511	76.5	511	76.5	513	76.2
401.bzip2	4	911	42.4	918	42.1	916	42.1	4	871	44.3	867	44.5	872	44.2
403.gcc	4	621	51.9	621	51.8	622	51.7	4	621	51.9	621	51.8	622	51.7
429.mcf	4	765	47.7	763	47.8	763	47.8	4	782	46.7	782	46.7	783	46.6
445.gobmk	4	618	67.9	615	68.2	617	68.0	4	562	74.7	564	74.4	566	74.1
456.hammer	4	834	44.8	834	44.8	836	44.7	4	698	53.5	696	53.6	697	53.5
458.sjeng	4	756	64.0	758	63.8	756	64.0	4	699	69.3	694	69.8	696	69.6
462.libquantum	4	2786	29.8	2783	29.8	2785	29.8	4	2739	30.3	2739	30.3	2733	30.3
464.h264ref	4	822	108	825	107	823	108	4	816	109	817	108	816	108
471.omnetpp	4	685	36.5	685	36.5	685	36.5	4	636	39.3	636	39.3	634	39.4
473.astar	4	698	40.2	699	40.1	699	40.2	4	689	40.7	690	40.7	690	40.7
483.xalancbmk	4	400	68.9	402	68.7	402	68.7	4	400	68.9	402	68.7	402	68.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs

General Notes

The system bus runs at 1333 MHz

All binaries were built with 32-bit Intel compiler except:
401.bzip2, 456.hammer and 462.libquantum in peak were built with
64-bit Intel compiler by changing the path for include and library files.

BIOS configuration:
Adjacent Sector Prefetch = Disable

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon processor 5150,
2.66 GHz

SPECint_rate2006 = 55.3

SPECint_rate_base2006 = 52.7

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Apr-2007

Hardware Availability: Jul-2006

Software Availability: Feb-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_X64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-xP -O3 -ipo -no-prec-div -L/opt/SmartHeap_8_1/lib -lsmartheap

Peak Compiler Invocation

C benchmarks (except as noted below):
icc

401.bzip2: /opt/intel/cce/9.1.047/bin/icc
-I/opt/intel/cce/9.1.047/include
-L/opt/intel/cce/9.1.047/lib

456.hmmr: /opt/intel/cce/9.1.047/bin/icc
-I/opt/intel/cce/9.1.047/include
-L/opt/intel/cce/9.1.047/lib

462.libquantum: /opt/intel/cce/9.1.047/bin/icc
-I/opt/intel/cce/9.1.047/include
-L/opt/intel/cce/9.1.047/lib

C++ benchmarks:
icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
456.hmmr: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon processor 5150,
2.66 GHz

SPECint_rate2006 = 55.3

SPECint_rate_base2006 = 52.7

CPU2006 license: 22

Test date: Apr-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Jul-2006

Tested by: Fujitsu Siemens Computers

Software Availability: Feb-2007

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof_gen(pass 1) -prof_use(pass 2) -fast

401.bzip2: -fast

403.gcc: basepeak = yes

429.mcf: -prof_gen(pass 1) -prof_use(pass 2) -fast
-L/opt/SmartHeap_8_1/lib -lsmartheap

445.gobmk: Same as 429.mcf

456.hmmer: Same as 400.perlbench

458.sjeng: Same as 429.mcf

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 429.mcf

C++ benchmarks:

471.omnetpp: -prof_gen(pass 1) -prof_use(pass 2) -xP -O3 -ipo
-no-prec-div -L/opt/SmartHeap_8_1/lib -lsmartheap

473.astar: -prof_gen(pass 1) -prof_use(pass 2) -fast
-L/opt/SmartHeap_8_1/lib -lsmartheap

483.xalancbmk: basepeak = yes

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 11:37:46 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 2 May 2007.