



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro Motherboard PDSBA+

SPECint®_rate2006 = 18.7

SPECint_rate_base2006 = 17.9

CPU2006 license: 001176


Test sponsor: Supermicro

Tested by: Supermicro

Test date: May-2007

Hardware Availability: Apr-2007

Software Availability: Apr-2007



Hardware

CPU Name: Intel Core 2 Duo E4300
 CPU Characteristics: 1.8GHz, 800MHz bus
 CPU MHz: 1800
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 2 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: None
 Memory: 2 GB (2X 1GB ECC, CL4, 533MHz, UnBuffer)
 Disk Subsystem: 150GB SATA, 7200RPM
 Other Hardware: None

Software

Operating System: Windows XP Professional w/ SP2
 Compiler: Intel C++ Compiler for IA32 version 9.1
 Build no 20070322Z
 Auto Parallel: No
 File System: NTFS
 System State: Default
 Base Pointers: 32-bit
 Peak Pointers: 32-bit
 Other Software: SmartHeap Library Version 8.0 from
<http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro Motherboard PDSBA+

SPECint_rate2006 = 18.7

SPECint_rate_base2006 = 17.9

CPU2006 license: 001176
Test sponsor: Supermicro
Tested by: Supermicro

Test date: May-2007
Hardware Availability: Apr-2007
Software Availability: Apr-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	2	787	24.8	785	24.9	787	24.8	2	707	27.6	708	27.6	709	27.6
401.bzip2	2	1531	12.6	1564	12.3	1561	12.4	2	1512	12.8	1511	12.8	1513	12.8
403.gcc	2	1537	10.5	1531	10.5	1553	10.4	2	1506	10.7	1506	10.7	1490	10.8
429.mcf	2	993	18.4	996	18.3	994	18.4	2	993	18.4	996	18.3	994	18.4
445.gobmk	2	912	23.0	914	23.0	910	23.1	2	833	25.2	834	25.2	835	25.1
456.hammer	2	1248	14.9	1248	14.9	1248	15.0	2	1223	15.3	1222	15.3	1223	15.3
458.sjeng	2	1103	21.9	1102	22.0	1099	22.0	2	1036	23.4	1037	23.3	1039	23.3
462.libquantum	2	2464	16.8	2461	16.8	2465	16.8	2	2439	17.0	2439	17.0	2440	17.0
464.h264ref	2	1258	35.2	1258	35.2	1266	35.0	2	1228	36.0	1225	36.1	1223	36.2
471.omnetpp	2	889	14.1	889	14.1	890	14.0	2	827	15.1	827	15.1	827	15.1
473.astar	2	1110	12.6	1110	12.6	1113	12.6	2	1041	13.5	1045	13.4	1041	13.5
483.xalancbmk	2	581	23.8	580	23.8	580	23.8	2	575	24.0	575	24.0	575	24.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Tested systems can be used with SC733T-645 case,
To ensure system stability, a 450W (minimum) ATX power supply [4-pin +12V AND (20 or 24-pin)] is required.
Product description located as of <http://www.supermicro.com/products/motherboard/Core2Duo/965/PDSBA+.cfm>
The system bus runs at 800 MHz

Base Compiler Invocation

C benchmarks:
icl -Qvc7.1 -Qc99
C++ benchmarks:
icl -Qvc7.1

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

Base Optimization Flags

C benchmarks:
-fast /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro
Motherboard PDSBA+

SPECint_rate2006 = 18.7

SPECint_rate_base2006 = 17.9

CPU2006 license: 001176
Test sponsor: Supermicro
Tested by: Supermicro

Test date: May-2007
Hardware Availability: Apr-2007
Software Availability: Apr-2007

Base Optimization Flags (Continued)

C++ benchmarks:
-fast -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:
icl -Qvc7.1 -Qc99
C++ benchmarks:
icl -Qvc7.1

Peak Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

Peak Optimization Flags

C benchmarks:
400.perlbench: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000
shlw32m.lib -link /FORCE:MULTIPLE
401.bzip2: Same as 400.perlbench
403.gcc: Same as 400.perlbench
429.mcf: basepeak = yes
445.gobmk: Same as 400.perlbench
456.hmmmer: Same as 400.perlbench
458.sjeng: Same as 400.perlbench

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Supermicro
Motherboard PDSBA+**

SPECint_rate2006 = 18.7

SPECint_rate_base2006 = 17.9

CPU2006 license: 001176
Test sponsor: Supermicro
Tested by: Supermicro

Test date: May-2007
Hardware Availability: Apr-2007
Software Availability: Apr-2007

Peak Optimization Flags (Continued)

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 400.perlbench

C++ benchmarks:

471.omnetpp: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

473.astar: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxP -O2 -Qipo
-Qprec-div- -Qunroll14 -Ob2 -Qsfa16 -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

483.xalancbmk: Same as 471.omnetpp

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic91-ia32-flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic91-ia32-flags.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.1.
Report generated on Tue Jul 22 11:52:00 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 29 May 2007.