



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

**SPECint®\_rate2006 = 50.0**

NovaScale R480 (2.60 GHz, Intel Xeon 7110M)

**SPECint\_rate\_base2006 = 46.9**

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

**Test date:** Apr-2007

**Hardware Availability:** Sep-2006

**Software Availability:** Nov-2006



## Hardware

CPU Name: Intel Xeon 7110M  
CPU Characteristics: 2.6 GHz, 800 MHz bus  
CPU MHz: 2600  
FPU: Integrated  
CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip, 2 threads/core  
CPU(s) orderable: 1,2,4 chips  
Primary Cache: 12 K micro-ops I + 16 KB D on chip per core  
Secondary Cache: 1 MB I+D on chip per core  
L3 Cache: 4 MB I+D on chip per chip  
Other Cache: None  
Memory: 32 GB (16x2 GB) DDR2 400 PC2-3200R-333  
Disk Subsystem: 2x36 GB SAS 15000 RPM  
Other Hardware: None

## Software

Operating System: Windows Server 2003 Enterprise X64 Edition  
Compiler: Intel C++ Compiler for IA32 version 9.1  
Package ID W\_CC\_C\_9.1.033 Build no 20061103Z  
Microsoft Visual Studio .NET 2003 (lib & linker)  
Auto Parallel: No  
File System: NTFS  
System State: Default  
Base Pointers: 32-bit  
Peak Pointers: 32-bit  
Other Software: MicroQuill SmartHeap Library 8.0 (shlw32M.lib)



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

**SPECint\_rate2006 = 50.0**

NovaScale R480 (2.60 GHz, Intel Xeon 7110M)

**SPECint\_rate\_base2006 = 46.9**

CPU2006 license: 20

Test date: Apr-2007

Test sponsor: Bull SAS

Hardware Availability: Sep-2006

Tested by: Bull SAS

Software Availability: Nov-2006

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	16	2166	72.2	2170	72.0	<b><u>2169</u></b>	<b><u>72.1</u></b>	16	1938	80.6	<b><u>1939</u></b>	<b><u>80.6</u></b>	1940	80.6
401.bzip2	16	<b><u>3699</u></b>	<b><u>41.7</u></b>	3698	41.8	3701	41.7	16	3674	42.0	<b><u>3665</u></b>	<b><u>42.1</u></b>	3664	42.1
403.gcc	16	<b><u>5831</u></b>	<b><u>22.1</u></b>	5852	22.0	5811	22.2	16	5882	21.9	<b><u>5892</u></b>	<b><u>21.9</u></b>	5897	21.8
429.mcf	16	3525	41.4	<b><u>3527</u></b>	<b><u>41.4</u></b>	3530	41.3	16	3525	41.4	<b><u>3527</u></b>	<b><u>41.4</u></b>	3530	41.3
445.gobmk	16	2537	66.2	2533	66.3	<b><u>2535</u></b>	<b><u>66.2</u></b>	16	2311	72.6	<b><u>2314</u></b>	<b><u>72.5</u></b>	2316	72.5
456.hmmer	16	3016	49.5	<b><u>3016</u></b>	<b><u>49.5</u></b>	3044	49.0	16	<b><u>2390</u></b>	<b><u>62.5</u></b>	2388	62.5	2409	62.0
458.sjeng	16	<b><u>3849</u></b>	<b><u>50.3</u></b>	3853	50.2	3695	52.4	16	3382	57.3	<b><u>3377</u></b>	<b><u>57.3</u></b>	3365	57.5
462.libquantum	16	11007	30.1	11013	30.1	<b><u>11010</u></b>	<b><u>30.1</u></b>	16	11014	30.1	11001	30.1	<b><u>11005</u></b>	<b><u>30.1</u></b>
464.h264ref	16	2900	122	2910	122	<b><u>2906</u></b>	<b><u>122</u></b>	16	2800	126	<b><u>2794</u></b>	<b><u>127</u></b>	2789	127
471.omnetpp	16	3703	27.0	<b><u>3702</u></b>	<b><u>27.0</u></b>	3702	27.0	16	<b><u>3636</u></b>	<b><u>27.5</u></b>	3637	27.5	3635	27.5
473.astar	16	2427	46.3	2424	46.3	<b><u>2425</u></b>	<b><u>46.3</u></b>	16	2381	47.2	<b><u>2377</u></b>	<b><u>47.2</u></b>	2374	47.3
483.xalancbmk	16	2009	55.0	2012	54.9	<b><u>2010</u></b>	<b><u>54.9</u></b>	16	1803	61.2	1810	61.0	<b><u>1808</u></b>	<b><u>61.1</u></b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

### Other Configuration Notes

The NovaScale T880 and the NovaScale R480 models are electronically equivalent.

The results have been measured on a NovaScale R480 model.

## Base Compiler Invocation

C benchmarks:

  icl -Qvc7.1 -Qc99

C++ benchmarks:

  icl -Qvc7.1

## Base Portability Flags

403.gcc: -DSPEC\_CPU\_WIN32

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R480 (2.60 GHz, Intel Xeon 7110M)

**SPECint\_rate2006 = 50.0**

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Apr-2007

Hardware Availability: Sep-2006

Software Availability: Nov-2006

## Base Portability Flags (Continued)

464.h264ref: -DSPEC\_CPU\_NO\_INTTYPES -DWIN32

## Base Optimization Flags

C benchmarks:

-fast /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

C++ benchmarks:

-fast -Qcxx\_features /F512000000 shlw32m.lib  
-link /FORCE:MULTIPLE

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks:

icl -Qvc7.1 -Qc99

C++ benchmarks:

icl -Qvc7.1

## Peak Portability Flags

403.gcc: -DSPEC\_CPU\_WIN32

464.h264ref: -DSPEC\_CPU\_NO\_INTTYPES -DWIN32

## Peak Optimization Flags

C benchmarks:

400.perlbench: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast /F512000000  
shlw32m.lib -link /FORCE:MULTIPLE

401.bzip2: Same as 400.perlbench

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

**SPECint\_rate2006 = 50.0**

NovaScale R480 (2.60 GHz, Intel Xeon 7110M)

**SPECint\_rate\_base2006 = 46.9**

**CPU2006 license:** 20

**Test sponsor:** Bull SAS

**Tested by:** Bull SAS

**Test date:** Apr-2007

**Hardware Availability:** Sep-2006

**Software Availability:** Nov-2006

## Peak Optimization Flags (Continued)

403.gcc: Same as 400.perlbench

429.mcf: basepeak = yes

445.gobmk: Same as 400.perlbench

456.hmmr: Same as 400.perlbench

458.sjeng: Same as 400.perlbench

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 400.perlbench

C++ benchmarks:

-Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qcxx\_features  
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/flags.20090714.00.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/flags.20090714.00.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 11:48:02 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 29 May 2007.