



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX100 S4, Intel Xeon processor 3060, 2.40 GHz

**SPECfp®\_rate2006 = 24.3**

**SPECfp\_rate\_base2006 = 23.7**

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Apr-2007

Hardware Availability: Sep-2006

Software Availability: Feb-2007



### Hardware

CPU Name: Intel Xeon 3060  
 CPU Characteristics: 1067 MHz system bus  
 CPU MHz: 2400  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 4 MB I+D on chip per chip

Continued on next page

### Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp on an x86\_64  
 Compiler: Intel C++ Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package-ID: l\_cc\_p\_9.1.047  
 Intel Fortran Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package ID: l\_fc\_p\_9.1.043  
 Auto Parallel: No  
 File System: ReiserFS

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX100 S4, Intel Xeon processor 3060,  
2.40 GHz

SPECfp\_rate2006 = 24.3

SPECfp\_rate\_base2006 = 23.7

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Apr-2007

Hardware Availability: Sep-2006

Software Availability: Feb-2007

L3 Cache: None  
Other Cache: None  
Memory: 8 GB (4x2 GB DDR2 PC2-4200E, 2 rank, CAS 4-4-4, with ECC)  
Disk Subsystem: SATA (160 GB, 7200 rpm)  
Other Hardware: None

System State: Multiuser, Runlevel 3  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	2	1064	25.6	<b>1078</b>	<b>25.2</b>	1080	25.2	2	1064	25.6	<b>1078</b>	<b>25.2</b>	1080	25.2
416.gamess	2	1190	32.9	<b>1191</b>	<b>32.9</b>	1192	32.9	2	1190	32.9	<b>1191</b>	<b>32.9</b>	1192	32.9
433.milc	2	1139	16.1	<b>1151</b>	<b>16.0</b>	1151	16.0	2	1217	15.1	<b>1218</b>	<b>15.1</b>	1219	15.1
434.zeusmp	2	711	25.6	717	25.4	<b>715</b>	<b>25.5</b>	2	<b>715</b>	<b>25.5</b>	714	25.5	721	25.2
435.gromacs	2	490	29.2	<b>489</b>	<b>29.2</b>	488	29.3	2	475	30.1	474	30.1	<b>475</b>	<b>30.1</b>
436.cactusADM	2	<b>749</b>	<b>31.9</b>	748	32.0	758	31.5	2	<b>749</b>	<b>31.9</b>	748	32.0	758	31.5
437.leslie3d	2	1237	15.2	<b>1196</b>	<b>15.7</b>	1195	15.7	2	1237	15.2	<b>1196</b>	<b>15.7</b>	1195	15.7
444.namd	2	<b>635</b>	<b>25.2</b>	635	25.2	635	25.3	2	<b>635</b>	<b>25.2</b>	635	25.2	635	25.3
447.dealII	2	549	41.7	552	41.4	<b>552</b>	<b>41.4</b>	2	<b>540</b>	<b>42.4</b>	541	42.3	539	42.5
450.soplex	2	904	18.5	<b>915</b>	<b>18.2</b>	919	18.2	2	862	19.4	<b>861</b>	<b>19.4</b>	859	19.4
453.povray	2	<b>325</b>	<b>32.8</b>	325	32.8	325	32.7	2	247	43.1	247	43.1	<b>247</b>	<b>43.1</b>
454.calculix	2	655	25.2	<b>656</b>	<b>25.1</b>	656	25.1	2	<b>642</b>	<b>25.7</b>	643	25.7	642	25.7
459.GemsFDTD	2	1515	14.0	<b>1515</b>	<b>14.0</b>	1516	14.0	2	1515	14.0	<b>1515</b>	<b>14.0</b>	1516	14.0
465.tonto	2	850	23.2	<b>840</b>	<b>23.4</b>	839	23.5	2	815	24.1	<b>817</b>	<b>24.1</b>	817	24.1
470.lbm	2	2070	13.3	2077	13.2	<b>2071</b>	<b>13.3</b>	2	1996	13.8	<b>1997</b>	<b>13.8</b>	1998	13.8
481.wrf	2	884	25.3	887	25.2	<b>884</b>	<b>25.3</b>	2	884	25.3	887	25.2	<b>884</b>	<b>25.3</b>
482.sphinx3	2	<b>1458</b>	<b>26.7</b>	1459	26.7	1454	26.8	2	1368	28.5	1363	28.6	<b>1367</b>	<b>28.5</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
'/usr/bin/taskset' used to bind processes to CPUs

## General Notes

The system bus runs at 1067 MHz

All binaries were built with 64-bit Intel compiler except:  
433.milc, 434.zeusmp, 450.soplex, 470.lbm and 482.sphinx3 in peak were built with  
32-bit Intel compiler by changing the path for include and library files.

For information about Fujitsu Siemens Computers in your country please see:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY RX100 S4, Intel Xeon processor 3060,  
2.40 GHz

**SPECfp\_rate2006 = 24.3**

**SPECfp\_rate\_base2006 = 23.7**

**CPU2006 license:** 22

**Test sponsor:** Fujitsu Siemens Computers

**Tested by:** Fujitsu Siemens Computers

**Test date:** Apr-2007

**Hardware Availability:** Sep-2006

**Software Availability:** Feb-2007

## General Notes (Continued)

<http://www.fujitsu-siemens.com/countries>

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

```

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

## Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY RX100 S4, Intel Xeon processor 3060,  
2.40 GHz

**SPECfp\_rate2006 = 24.3**

**SPECfp\_rate\_base2006 = 23.7**

**CPU2006 license:** 22

**Test sponsor:** Fujitsu Siemens Computers

**Tested by:** Fujitsu Siemens Computers

**Test date:** Apr-2007

**Hardware Availability:** Sep-2006

**Software Availability:** Feb-2007

## Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

-fast

## Peak Compiler Invocation

C benchmarks:

```
/opt/intel/cc/9.1.047/bin/icc -I/opt/intel/cc/9.1.047/include  
-L/opt/intel/cc/9.1.047/lib
```

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/cc/9.1.047/bin/icpc  
-I/opt/intel/cc/9.1.047/include -L/opt/intel/cc/9.1.047/lib
```

Fortran benchmarks (except as noted below):

ifort

```
434.zeusmp: /opt/intel/fc/9.1.043/bin/ifort  
-I/opt/intel/fc/9.1.043/include -L/opt/intel/fc/9.1.043/lib
```

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64  
416.gamess: -DSPEC_CPU_LP64  
435.gromacs: -DSPEC_CPU_LP64 -nofor_main  
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main  
437.leslie3d: -DSPEC_CPU_LP64  
444.namd: -DSPEC_CPU_LP64  
447.dealII: -DSPEC_CPU_LP64  
453.povray: -DSPEC_CPU_LP64  
454.calculix: -DSPEC_CPU_LP64 -nofor_main  
459.GemsFDTD: -DSPEC_CPU_LP64  
465.tonto: -DSPEC_CPU_LP64  
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

## Peak Optimization Flags

C benchmarks:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY RX100 S4, Intel Xeon processor 3060,  
2.40 GHz

**SPECfp\_rate2006 = 24.3**

**SPECfp\_rate\_base2006 = 23.7**

**CPU2006 license:** 22

**Test sponsor:** Fujitsu Siemens Computers

**Tested by:** Fujitsu Siemens Computers

**Test date:** Apr-2007

**Hardware Availability:** Sep-2006

**Software Availability:** Feb-2007

## Peak Optimization Flags (Continued)

433.milc: -prof\_gen(pass 1) -prof\_use(pass 2) -fast

470.lbm: Same as 433.milc

482.sphinx3: -fast

C++ benchmarks:

444.namd: basepeak = yes

447.dealII: -prof\_gen(pass 1) -prof\_use(pass 2) -fast

450.soplex: Same as 447.dealII

453.povray: Same as 447.dealII

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: -fast

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -prof\_gen(pass 1) -prof\_use(pass 2) -fast

Benchmarks using both Fortran and C:

435.gromacs: -prof\_gen(pass 1) -prof\_use(pass 2) -fast

436.cactusADM: basepeak = yes

454.calculix: Same as 435.gromacs

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

[http://www.spec.org/cpu2006/flags/CPU2006\\_flags.20090714.09.html](http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.html)

You can also download the XML flags source by saving the following link:

[http://www.spec.org/cpu2006/flags/CPU2006\\_flags.20090714.09.xml](http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.xml)



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX100 S4, Intel Xeon processor 3060,  
2.40 GHz

**SPECfp\_rate2006 = 24.3**

**SPECfp\_rate\_base2006 = 23.7**

**CPU2006 license:** 22

**Test sponsor:** Fujitsu Siemens Computers

**Tested by:** Fujitsu Siemens Computers

**Test date:** Apr-2007

**Hardware Availability:** Sep-2006

**Software Availability:** Feb-2007

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 11:42:22 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 29 May 2007.