



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7130M, 3.20 GHz

SPECint®_rate2006 = 40.8

SPECint_rate_base2006 = 38.2

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: May-2007

Hardware Availability: Aug-2006

Software Availability: Mar-2007



Hardware

CPU Name: Intel Xeon 7130M
 CPU Characteristics: 800 MHz system bus
 CPU MHz: 3200
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2,4 chips
 Primary Cache: 12 K micro-ops I + 16 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: 8 MB I+D on chip per chip
 Other Cache: None
 Memory: 32 GB (16x2 GB DDR2 PC2-3200R, 2 rank, CAS 3-3-3, with ECC)
 Disk Subsystem: Seagate ST973401SS (SAS 73GB 10 krpm)
 Other Hardware: None

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp on an x86_64
 Compiler: Intel C++ Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package-ID: l_cc_p_9.1.047
 Auto Parallel: No
 File System: ReiserFS
 System State: Multiuser Runlevel 3
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: Smart Heap Library, Version 8.1



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7130M,
3.20 GHz

SPECint_rate2006 = 40.8

SPECint_rate_base2006 = 38.2

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: May-2007

Hardware Availability: Aug-2006

Software Availability: Mar-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	1810	43.2	1809	43.2	1776	44.0	8	1586	49.3	1663	47.0	1586	49.3
401.bzip2	8	2221	34.8	2224	34.7	2211	34.9	8	2121	36.4	2105	36.7	2111	36.6
403.gcc	8	1486	43.3	1496	43.1	1484	43.4	8	1486	43.3	1496	43.1	1484	43.4
429.mcf	8	1722	42.4	1730	42.2	1730	42.2	8	1819	40.1	1821	40.1	1819	40.1
445.gobmk	8	2158	38.9	2169	38.7	2161	38.8	8	1973	42.5	1984	42.3	1986	42.3
456.hmmmer	8	2400	31.1	2389	31.2	2401	31.1	8	1721	43.4	1716	43.5	1718	43.5
458.sjeng	8	3054	31.7	3055	31.7	3052	31.7	8	2713	35.7	2710	35.7	2572	37.6
462.libquantum	8	5720	29.0	5710	29.0	5718	29.0	8	5682	29.2	5684	29.2	5678	29.2
464.h264ref	8	2283	77.5	2308	76.7	2283	77.5	8	2340	75.7	2336	75.8	2339	75.7
471.omnetpp	8	1907	26.2	1907	26.2	1915	26.1	8	1737	28.8	1735	28.8	1734	28.8
473.astar	8	1629	34.5	1628	34.5	1625	34.6	8	1556	36.1	1555	36.1	1556	36.1
483.xalancbmk	8	1212	45.5	1214	45.5	1214	45.5	8	1212	45.5	1214	45.5	1214	45.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs

General Notes

The system bus runs at 800 MHz

All binaries were built with 32-bit Intel compiler except:
401.bzip2, 456.hmmmer and 462.libquantum in peak were built with
64-bit Intel compiler by changing the path for include and library files.

BIOS configuration:
Hardware Prefetch = Enable

This result was measured on the PRIMERGY RX600 S3. The PRIMERGY RX600 S3 and
the PRIMERGY TX600 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>

Base Compiler Invocation

C benchmarks:
icc

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7130M,
3.20 GHz

SPECint_rate2006 = 40.8

SPECint_rate_base2006 = 38.2

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: May-2007

Hardware Availability: Aug-2006

Software Availability: Mar-2007

Base Compiler Invocation (Continued)

C++ benchmarks:
icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_X64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-xP -O3 -ipo -no-prec-div -L/opt/SmartHeap_8_1/lib -lsmarheap

Peak Compiler Invocation

C benchmarks (except as noted below):
icc

401.bzip2: /opt/intel/cce/9.1.047/bin/icc
-I/opt/intel/cce/9.1.047/include
-L/opt/intel/cce/9.1.047/lib

456.hmmer: /opt/intel/cce/9.1.047/bin/icc
-I/opt/intel/cce/9.1.047/include
-L/opt/intel/cce/9.1.047/lib

462.libquantum: /opt/intel/cce/9.1.047/bin/icc
-I/opt/intel/cce/9.1.047/include
-L/opt/intel/cce/9.1.047/lib

C++ benchmarks:
icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7130M,
3.20 GHz

SPECint_rate2006 = 40.8

SPECint_rate_base2006 = 38.2

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: May-2007

Hardware Availability: Aug-2006

Software Availability: Mar-2007

Peak Portability Flags (Continued)

456.hmmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof_gen(pass 1) -prof_use(pass 2) -fast

401.bzip2: -fast

403.gcc: basepeak = yes

429.mcf: -prof_gen(pass 1) -prof_use(pass 2) -fast
-L/opt/SmartHeap_8_1/lib -lsmarheap

445.gobmk: Same as 429.mcf

456.hmmmer: Same as 400.perlbench

458.sjeng: Same as 429.mcf

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 429.mcf

C++ benchmarks:

471.omnetpp: -prof_gen(pass 1) -prof_use(pass 2) -xP -O3 -ipo
-no-prec-div -L/opt/SmartHeap_8_1/lib -lsmarheap

473.astar: -prof_gen(pass 1) -prof_use(pass 2) -fast
-L/opt/SmartHeap_8_1/lib -lsmarheap

483.xalancbmk: basepeak = yes

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.xml



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7130M,
3.20 GHz

SPECint_rate2006 = 40.8

SPECint_rate_base2006 = 38.2

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: May-2007

Hardware Availability: Aug-2006

Software Availability: Mar-2007

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:00:04 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 12 June 2007.