



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint®_rate2006 = 95.0

IBM System x3755 (AMD Opteron 8218)

SPECint_rate_base2006 = 84.7

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jul-2007

Hardware Availability: Oct-2006

Software Availability: Mar-2007



Hardware

CPU Name: AMD Opteron 8218
 CPU Characteristics:
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip
 CPU(s) orderable: 1, 2, 3, 4 chips
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: None
 Other Cache: None
 Memory: 32 GB (16 x 2GB DDR2-5300 ECC)
 Disk Subsystem: 1 x 36 GB SAS, 15000 RPM
 Other Hardware: None

Software

Operating System: SLES 10 (x86_64), 2.6.16.21-0.8-smp
 Compiler: QLogic PathScale Compiler Suite, Release 3.0
 Auto Parallel: No
 File System: ext3
 System State: Multi-user, run level 3
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap 8.1



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = 95.0

IBM System x3755 (AMD Opteron 8218)

SPECint_rate_base2006 = 84.7

CPU2006 license: 11

Test date: Jul-2007

Test sponsor: IBM Corporation

Hardware Availability: Oct-2006

Tested by: IBM Corporation

Software Availability: Mar-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	849	92.1	849	92.0	849	92.1	8	694	113	693	113	693	113
401.bzip2	8	1094	70.6	1092	70.7	1098	70.3	8	1090	70.8	1091	70.8	1092	70.7
403.gcc	8	1091	59.0	1100	58.6	1095	58.8	8	849	75.9	850	75.8	852	75.6
429.mcf	8	1105	66.1	1108	65.9	1108	65.8	8	805	90.6	805	90.7	804	90.8
445.gobmk	8	808	104	807	104	808	104	8	683	123	683	123	684	123
456.hammer	8	733	102	733	102	733	102	8	545	137	544	137	542	138
458.sjeng	8	1017	95.2	1023	94.6	1015	95.4	8	931	104	932	104	931	104
462.libquantum	8	2024	81.9	2019	82.1	2018	82.1	8	2019	82.1	2019	82.1	2020	82.1
464.h264ref	8	1165	152	1166	152	1165	152	8	1133	156	1122	158	1131	157
471.omnetpp	8	801	62.4	803	62.3	802	62.4	8	809	61.8	799	62.6	797	62.7
473.astar	8	828	67.8	828	67.8	826	68.0	8	828	67.8	828	67.8	826	68.0
483.xalanbmk	8	541	102	541	102	540	102	8	536	103	535	103	535	103

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

taskset utility used to bind CPU(s) to processes

Base Compiler Invocation

C benchmarks:
pathcc

C++ benchmarks:
pathCC

Base Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hammer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalanbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = 95.0

IBM System x3755 (AMD Opteron 8218)

SPECint_rate_base2006 = 84.7

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jul-2007

Hardware Availability: Oct-2006

Software Availability: Mar-2007

Base Optimization Flags

C benchmarks:

-Ofast -OPT:malloc_alg=1

C++ benchmarks:

-Ofast -m32 -L/tools/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:

-IPA:max_jobs=2

C++ benchmarks:

-IPA:max_jobs=2

Peak Compiler Invocation

C benchmarks:

pathcc

C++ benchmarks:

pathCC

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
-LNO:opt=0

401.bzip2: -O3 -LNO:ou_prod_max=10 -OPT:Ofast -OPT:alias=disjoint

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = 95.0

IBM System x3755 (AMD Opteron 8218)

SPECint_rate_base2006 = 84.7

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jul-2007

Hardware Availability: Oct-2006

Software Availability: Mar-2007

Peak Optimization Flags (Continued)

403.gcc: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -m32 -O3
-OPT:Ofast

429.mcf: -m32 -O3 -ipa -L/tools/SmartHeap_8.1/lib -lsmartheap

445.gobmk: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
-OPT:alias=disjoint -LNO:simd=0 -LNO:minvariant=off
-WOPT:retype_expr=on

456.hmmr: -O2 -OPT:alias=disjoint -OPT:malloc_alg=1 -CG:cflow=0

458.sjeng: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
-IPA:plimit=50000 -IPA:pu_reorder=2

462.libquantum: -O3 -ipa -CG:local_fwd_sched=on -IPA:space=1000

464.h264ref: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
-IPA:plimit=20000 -OPT:alias=disjoint -LNO:prefetch=0

C++ benchmarks:

471.omnetpp: -Ofast -CG:gcm=off -m32
-L/tools/SmartHeap_8.1/lib -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: -Ofast -m32 -OPT:unroll_times_max=8
-L/tools/SmartHeap_8.1/lib -lsmartheap

Peak Other Flags

C benchmarks:

-IPA:max_jobs=2

C++ benchmarks:

-IPA:max_jobs=2

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.13.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.13.xml



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = 95.0

IBM System x3755 (AMD Opteron 8218)

SPECint_rate_base2006 = 84.7

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jul-2007

Hardware Availability: Oct-2006

Software Availability: Mar-2007

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 12:20:36 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 21 August 2007.