



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor E5320, 1.86GHz)

SPECint_rate2006 = 68.9

SPECint_rate_base2006 = 64.8

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Jul-2007

Hardware Availability: May-2007

Software Availability: May-2007



SPECint_rate_base2006 = 64.8

SPECint_rate2006 = 68.9

Hardware

CPU Name: Intel Xeon E5320
CPU Characteristics: 1.86 GHz, 8 MB L2, 1066 MHz system bus
CPU MHz: 1866
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1 to 2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache: None
Other Cache: None
Memory: 12 GB (12x1 GB) FB-DIMM PC2-4200F ECC CL4
Disk Subsystem: 1x73 GB SAS, 15000 RPM
Other Hardware: None

Software

Operating System: SUSE LINUX Enterprise Server 10
Kernel 2.6.16.21-0.8-smp for x86_64
Compiler: Intel C++ Compiler for Linux32 version 10.0
Build 20070426 Package ID: l_cc_p_10.0.023
Auto Parallel: No
File System: ext2
System State: Multi-user run level 3
Base Pointers: 32-bit
Peak Pointers: 32/64-bit
Other Software: SmartHeap library V8.1
Binutils 2.17.50.0.15



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor E5320, 1.86GHz)

SPECint_rate2006 = 68.9

SPECint_rate_base2006 = 64.8

CPU2006 license: 20

Test date: Jul-2007

Test sponsor: Bull SAS

Hardware Availability: May-2007

Tested by: Bull SAS

Software Availability: May-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	806	97.0	803	97.4	817	95.7	8	687	114	684	114	685	114
401.bzip2	8	1384	55.8	1388	55.6	1377	56.1	8	1335	57.8	1331	58.0	1322	58.4
403.gcc	8	1172	54.9	1161	55.5	1167	55.2	8	1172	54.9	1161	55.5	1167	55.2
429.mcf	8	1711	42.6	1711	42.6	1709	42.7	8	1707	42.7	1704	42.8	1706	42.8
445.gobmk	8	889	94.4	887	94.6	890	94.3	8	824	102	818	103	818	103
456.hammer	8	965	77.4	965	77.4	964	77.4	8	772	96.6	771	96.8	771	96.8
458.sjeng	8	1126	86.0	1125	86.0	1118	86.6	8	1005	96.4	1002	96.6	1004	96.4
462.libquantum	8	4387	37.8	4386	37.8	4386	37.8	8	4204	39.4	4196	39.5	4189	39.6
464.h264ref	8	1182	150	1187	149	1183	150	8	1123	158	1122	158	1122	158
471.omnetpp	8	1542	32.4	1546	32.3	1545	32.4	8	1540	32.5	1540	32.5	1541	32.4
473.astar	8	1163	48.3	1154	48.7	1166	48.2	8	1155	48.6	1150	48.8	1152	48.7
483.xalancbmk	8	714	77.3	714	77.3	716	77.1	8	714	77.3	714	77.3	716	77.1

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs
All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hammer,
for peak, are compiled in 64-bit mode

General Notes

The NovaScale R440 and the NovaScale R460 models are
electronically equivalent.
The results have been measured on a NovaScale R460 model.

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor E5320, 1.86GHz)

SPECint_rate2006 = 68.9

SPECint_rate_base2006 = 64.8

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Jul-2007

Hardware Availability: May-2007

Software Availability: May-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-fast -Wl,-z,muldefs

C++ benchmarks:

-xT -ipo -O3 -no-prec-div -ansi-alias -Wl,-z,muldefs
-L/spec/cpu2006/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/cce/10.0.023/bin/icc
-L/opt/intel/cce/10.0.023/lib
-I/opt/intel/cce/10.0.023/include

456.hmmr: /opt/intel/cce/10.0.023/bin/icc
-L/opt/intel/cce/10.0.023/lib
-I/opt/intel/cce/10.0.023/include

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmr: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor E5320, 1.86GHz)

SPECint_rate2006 = 68.9

SPECint_rate_base2006 = 64.8

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Jul-2007

Hardware Availability: May-2007

Software Availability: May-2007

Peak Portability Flags (Continued)

483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -prof_gen(pass 1) -prof_use(pass 2) -fast -ansi-alias
               -prefetch -Wl,-z,muldefs

401.bzip2: -prof_gen(pass 1) -prof_use(pass 2) -fast -Wl,-z,muldefs

403.gcc: basepeak = yes

429.mcf: -fast -prefetch -Wl,-z,muldefs

445.gobmk: -prof_gen(pass 1) -prof_use(pass 2) -xT -O2 -ipo
            -no-prec_div -ansi-alias -Wl,-z,muldefs

456.hmmr: -prof_gen(pass 1) -prof_use(pass 2) -fast -unroll12
           -ansi-alias -Wl,-z,muldefs

458.sjeng: -prof_gen(pass 1) -prof_use(pass 2) -fast -unroll14
           -Wl,-z,muldefs

462.libquantum: -prof_gen(pass 1) -prof_use(pass 2) -fast -unroll14 -O0
                -prefetch -opt-streaming-stores always -Wl,-z,muldefs

464.h264ref: Same as 456.hmmr
```

C++ benchmarks:

```
471.omnetpp: -prof_gen(pass 1) -prof_use(pass 2) -xT -O3 -ipo
              -no-prec_div -ansi-alias -Wl,-z,muldefs
              -L/spec/cpu2006/lib -lsmartheap

473.astar: Same as 471.omnetpp

483.xalancbmk: basepeak = yes
```

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor E5320,1.86GHz)

SPECint_rate2006 = 68.9

SPECint_rate_base2006 = 64.8

CPU2006 license: 20

Test date: Jul-2007

Test sponsor: Bull SAS

Hardware Availability: May-2007

Tested by: Bull SAS

Software Availability: May-2007

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/EM64T_Intel100_flags.20090714.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/EM64T_Intel100_flags.20090714.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 13:54:09 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 2 October 2007.