



SPEC[®] CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade T6320

SPECint[®]_rate2006 = **NC**
SPECint_rate_base2006 = **NC**

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Oct-2007
Hardware Availability: Oct-2007
Software Availability: Sep-2007

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

- Copies
- 400.perlbench
- 401.bzip2
- 403.gcc
- 429.mcf
- 445.gobmk
- 456.hmmer
- 458.sjeng
- 462.libquantum
- 464.h264ref
- 471.omnetpp
- 473.astar
- 483

Non-Compliant

Hardware

CPU Name: UltraSPARC T2
CPU Characteristics:
CPU MHz: 1417
FPU: Integrated
CPU(s) enabled: 8 cores, 1 chip, 8 cores/chip, 8 threads/core
CPU(s) orderable: 1 chip
Primary Cache: 16 KB I + 8 KB D on chip per core

Continued on next page

Software

Operating System: Solaris 10 8/07 (build s10s_u4wos_12b)
Compiler: Sun Studio 12 (patch build 2007/08/30)
Auto Parallel: No
File System: ufs
System State: Default
Base Pointers: 32-bit
Peak Pointers: 32-bit

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade T6320

SPECint_rate2006 = **NC**
SPECint_rate_base2006 = **NC**

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Oct-2007
Hardware Availability: Oct-2007
Software Availability: Sep-2007

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Secondary Cache: 4 MB I+D on chip per chip
L3 Cache: None
Other Cache: None
Memory: 64 GB (16 x 4 GB)
Disk Subsystem: 1 x SUN72G 10K RPM SAS disk
ufs fragment size 8192 bytes
Other Hardware: None

Other Software: None

Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
400.perlbench	63	NC	NC	NC	NC	NC	NC	63	NC	NC	NC	NC	NC	NC		
401.bzip2	63	NC	NC	NC	NC	NC	NC	63	NC	NC	NC	NC	NC	NC		
403.gcc	63	NC	NC	NC	NC	NC	NC	63	NC	NC	NC	NC	NC	NC		
429.mcf	63	NC	NC	NC	NC	NC	NC	48	NC	NC	NC	NC	NC	NC		
445.gobmk	63	NC	NC	NC	NC	NC	NC	63	NC	NC	NC	NC	NC	NC		
456.hmmer	63	NC	NC	NC	NC	NC	NC	63	NC	NC	NC	NC	NC	NC		
458.sjeng	63	NC	NC	NC	NC	NC	NC	63	NC	NC	NC	NC	NC	NC		
462.libquantum	63	NC	NC	NC	NC	NC	NC	63	NC	NC	NC	NC	NC	NC		
464.h264ref	63	NC	NC	NC	NC	NC	NC	63	NC	NC	NC	NC	NC	NC		
471.omnetpp	63	NC	NC	NC	NC	NC	NC	63	NC	NC	NC	NC	NC	NC		
473.ast	63	NC	NC	NC	NC	NC	NC	63	NC	NC	NC	NC	NC	NC		
483.xalancmk	63	NC	NC	NC	NC	NC	NC	63	NC	NC	NC	NC	NC	NC		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

Compiler patches are available at
http://developers.sun.com/sunstudio/downloads/patches/ss12_patches.jsp



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade T6320

SPECint_rate2006 = **NC**
SPECint_rate_base2006 = **NC**

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Oct-2007
Hardware Availability: Oct-2007
Software Availability: Sep-2007

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Operating System Notes

Processes were bound to cores using "sbind" and "pbind".
ulimit -s 131072 was used to limit the space consumed by the stack (and therefore make more space available to the heap).
The "webconsole" service was turned off using svcadm disable webconsole.

Base Compiler Invocation

C benchmarks:
cc
C++ benchmarks:
CC

Base Portability Flags

400.perlbench: -DSPEC_CPU_SOLARIS_SPARC
402.gcc: -DSPEC_CPU_SOLARIS
402.noquantum: -DSPEC_CPU_SOLARIS
83.xalancbmk: -DSPEC_CPU_SOLARIS

Base Optimization Flags

C benchmarks:
-g -fast -xipo=2 -xpagesize=4M -xprefetch_level=2 -xalias_level=std
C++ benchmarks:
-g0 -library=stlport4 -fast -xipo=2 -xpagesize=4M -xdepend -xprefetch_level=1 -xalias_level=compatible



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade T6320

SPECint_rate2006 = **NC**
SPECint_rate_base2006 = **NC**

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Oct-2007
Hardware Availability: Oct-2007
Software Availability: Sep-2007

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Base Other Flags

C benchmarks:
-xjobs=32 -v
C++ benchmarks:
-xjobs=32 -verbose=diags -version

Peak Compiler Invocation

C benchmarks:
cc
C++ benchmarks:
CC

Peak Portability Flags

400.perlbenc: -DSPEC_CPU_SOLARIS_SPARC
403.gcc: -DSPEC_CPU_SOLARIS
462.libquantum: -DSPEC_CPU_SOLARIS
483.xalanbmk: -DSPEC_CPU_SOLARIS

Peak Optimization Flags

C benchmarks:
400.perlbenc: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-xalias_level=std -xipo=2 -Xc -xrestrict -lfast
401.bzip2: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-xalias_level=strong

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade T6320

SPECint_rate2006 = **NC**
SPECint_rate_base2006 = **NC**

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Oct-2007
Hardware Availability: Oct-2007
Software Availability: Sep-2007

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Peak Optimization Flags (Continued)

403.gcc: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-xalias_level=std -xprefetch_level=2

429.mcf: -g -fast -xpagesize=256M -xipo=2 -xprefetch_level=2
-xrestrict -xalias_level=std -W2,-Apf:llist=3
-W2,-Apf:noindexrllist -lfast

445.gobmk: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-xalias_level=std -xrestrict

456.hmmer: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-xipo=2

458.sjeng: Same as 456.hmmer

462.libquantum: basepeak = yes

464.t264relog: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-xipo=2 -xalias_level=std

C++ benchmarks:

471.omnetpp: basepeak = yes

475.astar: -g0 -library=stlport4 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize_heap=4M
-xpagesize_stack=64K -xdepend -xalias_level=compatible
-xipo=2 -xarch=v8plusb -lfast -lbsdmalloc

483.xalancbmk: -g0 -library=stlport4 -fast -xpagesize=4M -xdepend
-xalias_level=compatible -xipo=2 -xprefetch_level=2 -lfast



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade T6320

SPECint_rate2006 = **NC**
SPECint_rate_base2006 = **NC**

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Oct-2007
Hardware Availability: Oct-2007
Software Availability: Sep-2007

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Peak Other Flags

C benchmarks:
-xjobs=32 -V

C++ benchmarks:
-xjobs=32 -verbose=diags -version

The flags file that was used to format this result can be browsed at
<http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12.20090714.00.html>

You can also download the XML flags source by saving the following link:
<http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12.20090714.00.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.1.
Report generated on Tue Jul 22 14:18:15 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 30 October 2007.