



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant ML350 G5  
(3.0 GHz, Intel Xeon processor X5365)

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

~~SPECint\_rate2006 = 10~~

~~SPECint\_rate\_base2006 = NC~~

Test date: Oct-2007

Hardware Availability: Sep-2007

Software Availability: Nov-2007

**SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.**

	Copies
400.perlbench	
401.bzip2	
403.gcc	
429.mcf	
445.gobmk	
456.hmmer	
458.sjeng	
462.libquantum	
464.h264ref	
471.omnetpp	
473.astar	
483	

	Hardware	Software
CPU Name:	Intel Xeon X5365	SuSE Linux Enterprise Server 10 (x86_64) SP1
CPU Characteristics:	3.0 GHz, 2x4 MB L2 shared, 1333 MHz system bus	kernel 2.6.16.46-0.12-smp
CPU MHz:	3000	Intel C++ Compiler for Linux32 and Linux64
FPU:	Integrated	version 10.1
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip	Build 20070725
CPU(s) orderable:	1,2 chips	Yes
Primary Cache:	32 KB I + 32 KB D on chip per core	ext2
		Multi-user run level 3

Continued on next page

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant ML350 G5  
(3.0 GHz, Intel Xeon processor X5365)

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

~~SPECint\_rate2006 = NC~~

~~SPECint\_rate\_base2006 = NC~~

Test date: Oct-2007

Hardware Availability: Sep-2007

Software Availability: Nov-2007

**SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.**

Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores	Base Pointers:	32-bit
L3 Cache:	None	Link Pointers:	32/64-bit
Other Cache:	None	Other Software:	MicroQuill SmartHeap Library 8.1
Memory:	16 GB (8x2 GB PC2-5300F CL5)		binutils-2.17.50
Disk Subsystem:	1x72 GB 15 K SAS		
Other Hardware:	None		

**Result Table**

Benchmark	Base						Peak					
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	NC	NC	NC	NC	NC	NC	4	NC	NC	NC	NC
401.bzip2	4	NC	NC	NC	NC	NC	NC	4	NC	NC	NC	NC
403.gcc	4	NC	NC	NC	NC	NC	NC	4	NC	NC	NC	NC
429.mcf	4	NC	NC	NC	NC	NC	NC	4	NC	NC	NC	NC
445.gobmk	4	NC	NC	NC	NC	NC	NC	4	NC	NC	NC	NC
456.hmmer	4	NC	NC	NC	NC	NC	NC	4	NC	NC	NC	NC
458sjeng	4	NC	NC	NC	NC	NC	NC	4	NC	NC	NC	NC
462.libquantum	4	NC	NC	NC	NC	NC	NC	1	NC	NC	NC	NC
464.h264ref	4	NC	NC	NC	NC	NC	NC	4	NC	NC	NC	NC
471.omnetpp	4	NC	NC	NC	NC	NC	NC	4	NC	NC	NC	NC
473.astar	4	NC	NC	NC	NC	NC	NC	4	NC	NC	NC	NC
483.xalancbmk	4	NC	NC	NC	NC	NC	NC	4	NC	NC	NC	NC

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to physical,0  
KMP\_STACKSIZE set to 64M



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant ML350 G5  
(3.0 GHz, Intel Xeon processor X5365)

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

~~Specint\_rate2006 = NC~~

~~Specint\_rate\_base2006 = NC~~

Test date: Oct-2007

Hardware Availability: Sep-2007

Software Availability: Nov-2007

**SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.**

## Platform Notes

BIOS configuration:

Power Regulator set to Static High Performance Mode  
Adjacent Sector Prefetch Disabled

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:  
-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:  
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs  
-L/home/cmpllr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

## Base Other Flags

C benchmarks:

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant ML350 G5  
(3.0 GHz, Intel Xeon processor X5365)

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

~~Specint\_rate2006 = NC~~

~~Specint\_rate\_base2006 = NC~~

Test date: Oct-2007

Hardware Availability: Sep-2007

Software Availability: Nov-2007

**SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.**

## Base Other Flag (Continued)

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc  
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib  
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include

456.hmmer: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc  
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib  
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include

C++ benchmarks:

icpc

## Peak Portability Flags

400.perlbmk: -DSPEC\_CPU\_LINUX\_IA32  
-DSPEC\_CPU\_LP64

456.hmmer: -DSPEC\_CPU\_LP64

462.libquantum: -DSPEC\_CPU\_LINUX

483.blancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant ML350 G5  
(3.0 GHz, Intel Xeon processor X5365)

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

**SPECint\_rate2006 = 10**

**SPECint\_rate\_base2006 = NC**

Test date: Oct-2007

Hardware Availability: Sep-2007

Software Availability: Nov-2007

**SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.**

## Peak Optimization Flags (Continued)

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias  
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch

403.gcc: -fast -inline-calloc -opt-alloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo  
-no-prec-div -ansi-alias

456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -O0 -prefetch  
-opt-streaming-stores always -vec-guard-write  
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias

C++ benchmarks:

471.crafty: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec-div -ansi-alias -opt-ra-region-strategy=block  
-Wl,-z,muldefs  
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

475.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine  
-Wl,-z,muldefs  
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

483.xalancbmk: basepeak = yes



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant ML350 G5  
(3.0 GHz, Intel Xeon processor X5365)

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

~~Specint\_rate2006 = NC~~

~~Specint\_rate\_base2006 = NC~~

Test date: Oct-2007

Hardware Availability: Sep-2007

Software Availability: Nov-2007

**SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.**

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to record this result can be browsed at

<http://www.spec.org/cpu2006/flags/HP-Intel-ic10.1-linux-flags.20090714.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/HP-Intel-ic10.1-linux-flags.20090714.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 14:41:09 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 13 November 2007.