



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro Motherborad X7DB3

**SPECint®\_rate2006 = 104**  
**SPECint\_rate\_base2006 = 86.0**

CPU2006 license: 001176


Test sponsor: Supermicro

Tested by: Supermicro

Test date: Oct-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007



### Hardware

CPU Name: Intel Xeon E5405  
 CPU Characteristics: Quad Core, 2.00GHz  
 CPU MHz: 2000  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
 CPU(s) orderable: 1, 2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores  
 L3 Cache: None  
 Other Cache: None  
 Memory: 16 GB (8 \* 2 GB PC2-5300 FBDIMM, CL-5-5-5, ECC)  
 Disk Subsystem: 500GB SATA, 7200RPM  
 Other Hardware: None

### Software

Operating System: SuSE Linux Enterprise Server 10 (x86\_64) SP1, kernel 2.6.16.46-0.12-default  
 Compiler: Intel C++ Compiler for Linux32 and Linux64 version 10.1 Build 20070725  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Multi-user, run level 3  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: SmartHeap library V8.1 Binutils 2.17.50.0.15



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro  
Motherborad X7DB3

SPECint\_rate2006 = 104  
SPECint\_rate\_base2006 = 86.0

CPU2006 license: 001176  
Test sponsor: Supermicro  
Tested by: Supermicro

Test date: Oct-2007  
Hardware Availability: Nov-2007  
Software Availability: Nov-2007

## Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	748	105	739	106	<b>744</b>	<b>105</b>	8	626	125	621	126	<b>623</b>	<b>126</b>
401.bzip2	8	1012	76.3	<b>997</b>	<b>77.4</b>	993	77.8	8	935	82.5	<b>936</b>	<b>82.5</b>	937	82.4
403.gcc	8	778	82.8	781	82.4	<b>779</b>	<b>82.7</b>	8	<b>782</b>	<b>82.4</b>	780	82.5	784	82.1
429.mcf	8	<b>937</b>	<b>77.9</b>	936	77.9	939	77.7	8	<b>931</b>	<b>78.4</b>	929	78.5	931	78.4
445.gobmk	8	786	107	<b>792</b>	<b>106</b>	793	106	8	739	113	735	114	<b>738</b>	<b>114</b>
456.hammer	8	884	84.5	<b>884</b>	<b>84.4</b>	885	84.4	8	516	145	515	145	<b>515</b>	<b>145</b>
458.sjeng	8	971	99.7	<b>970</b>	<b>99.8</b>	968	100	8	886	109	<b>886</b>	<b>109</b>	887	109
462.libquantum	8	3107	53.4	<b>3108</b>	<b>53.3</b>	3109	53.3	1	127	164	127	163	<b>127</b>	<b>163</b>
464.h264ref	8	1059	167	<b>1060</b>	<b>167</b>	1060	167	8	<b>1007</b>	<b>176</b>	1006	176	1008	176
471.omnetpp	8	853	58.6	852	58.7	<b>852</b>	<b>58.7</b>	8	<b>824</b>	<b>60.7</b>	825	60.6	824	60.7
473.astar	8	897	62.6	899	62.4	<b>899</b>	<b>62.5</b>	8	<b>824</b>	<b>68.1</b>	826	68.0	822	68.3
483.xalancbmk	8	<b>518</b>	<b>107</b>	517	107	519	106	8	<b>518</b>	<b>107</b>	517	107	519	106

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

Tested systems can be used with CSE-825TQ-R700LPV case,  
To ensure system stability, a 550W (minimum) ATX power supply  
[4-pin (+12V), 8-pin (+12V) and 24-pin are required]  
Product description located as of  
<http://www.supermicro.com/products/motherboard/Xeon1333/5000/X7DB3.cfm>  
The system bus runs at 1333 MHz

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Supermicro  
Motherborad X7DB3**

**SPECint\_rate2006 = 104**  
**SPECint\_rate\_base2006 = 86.0**

**CPU2006 license:** 001176  
**Test sponsor:** Supermicro  
**Tested by:** Supermicro

**Test date:** Oct-2007  
**Hardware Availability:** Nov-2007  
**Software Availability:** Nov-2007

## Base Optimization Flags

C benchmarks:  
-fast -inline-calloc -opt-malloc-options=3  
C++ benchmarks:  
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs  
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

## Base Other Flags

C benchmarks:  
403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):  
icc  
401.bzip2: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc  
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib  
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include  
456.hmmer: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc  
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib  
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include  
C++ benchmarks:  
icpc

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
401.bzip2: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro  
Motherborad X7DB3

SPECint\_rate2006 = 104  
SPECint\_rate\_base2006 = 86.0

CPU2006 license: 001176  
Test sponsor: Supermicro  
Tested by: Supermicro

Test date: Oct-2007  
Hardware Availability: Nov-2007  
Software Availability: Nov-2007

## Peak Optimization Flags (Continued)

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias  
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo  
-no-prec-div -ansi-alias

456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch  
-opt-streaming-stores always -vec-guard-write  
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec-div -ansi-alias -opt-ra-region-strategy=block  
-Wl,-z,muldefs  
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine  
-Wl,-z,muldefs  
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.34.html>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro  
Motherborad X7DB3

SPECint\_rate2006 = 104

SPECint\_rate\_base2006 = 86.0

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

Test date: Oct-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.34.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.1.  
Report generated on Tue Jul 22 13:36:10 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 28 November 2007.