



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECint®_rate2006 = 81.2

T120Rc-1
(Intel Xeon X5260)

SPECint_rate_base2006 = 69.3

CPU2006 license: 9006


Test date: Feb-2008

Test sponsor: NEC Corporation

Hardware Availability: Jan-2008

Tested by: NEC Corporation

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon X5260
 CPU Characteristics: 3.33 GHz, 6 MB L2, 1333 MHz bus
 CPU MHz: 3325
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 6 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: None
 Memory: 12 GB (12x1 GB PC2-5300F, 2 rank, CL5-5-5, ECC)
 Disk Subsystem: 1x250 GB SATAII, 7200RPM
 Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ Compiler for Linux32 and Linux64 version 10.1 Build 20070913 Package ID: l_cc_p_10.1.008
 Auto Parallel: Yes
 File System: ext2
 System State: Run level 3 (multi-user)
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap library 8.1 binutils-2.17.tar.gz, Version 2.17



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECint_rate2006 = 81.2

T120Rc-1
(Intel Xeon X5260)

SPECint_rate_base2006 = 69.3

CPU2006 license: 9006

Test date: Feb-2008

Test sponsor: NEC Corporation

Hardware Availability: Jan-2008

Tested by: NEC Corporation

Software Availability: Nov-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	470	83.2	<u>471</u>	<u>83.0</u>	475	82.2	4	392	99.8	388	101	<u>390</u>	<u>100</u>
401.bzip2	4	<u>638</u>	<u>60.5</u>	639	60.4	636	60.7	4	611	63.1	<u>609</u>	<u>63.4</u>	605	63.8
403.gcc	4	517	62.2	<u>520</u>	<u>61.9</u>	523	61.6	4	517	62.3	520	61.9	<u>519</u>	<u>62.1</u>
429.mcf	4	560	65.1	564	64.7	<u>564</u>	<u>64.7</u>	4	<u>576</u>	<u>63.3</u>	577	63.3	575	63.5
445.gobmk	4	<u>498</u>	<u>84.3</u>	499	84.1	497	84.4	4	460	91.3	456	92.1	<u>457</u>	<u>91.9</u>
456.hmmer	4	532	70.2	<u>532</u>	<u>70.2</u>	531	70.2	4	<u>310</u>	<u>120</u>	309	121	310	120
458.sjeng	4	626	77.3	624	77.6	<u>624</u>	<u>77.6</u>	4	571	84.8	573	84.5	<u>571</u>	<u>84.8</u>
462.libquantum	4	1625	51.0	1628	50.9	<u>1627</u>	<u>50.9</u>	1	182	114	<u>182</u>	<u>114</u>	182	114
464.h264ref	4	634	140	633	140	<u>633</u>	<u>140</u>	4	608	146	606	146	<u>607</u>	<u>146</u>
471.omnetpp	4	590	42.4	<u>582</u>	<u>43.0</u>	582	43.0	4	553	45.2	552	45.3	<u>552</u>	<u>45.3</u>
473.astar	4	553	50.8	554	50.7	<u>554</u>	<u>50.7</u>	4	<u>518</u>	<u>54.2</u>	519	54.1	518	54.2
483.xalancbmk	4	322	85.8	<u>322</u>	<u>85.7</u>	322	85.7	4	322	85.8	<u>322</u>	<u>85.7</u>	322	85.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores

Platform Notes

Bios settings:
Intel SpeedStep Technology: Disabled

General Notes

All benchmarks compiled in 32-bit mode except 401.bzip2,
456.hmmer, for peak, are compiled in 64-bit mode

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECint_rate2006 = 81.2

T120Rc-1
(Intel Xeon X5260)

SPECint_rate_base2006 = 69.3

CPU2006 license: 9006

Test date: Feb-2008

Test sponsor: NEC Corporation

Hardware Availability: Jan-2008

Tested by: NEC Corporation

Software Availability: Nov-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/opt/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc

401.bzip2: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

456.hmmer: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

C++ benchmarks:
icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECint_rate2006 = 81.2

T120Rc-1
(Intel Xeon X5260)

SPECint_rate_base2006 = 69.3

CPU2006 license: 9006
Test sponsor: NEC Corporation
Tested by: NEC Corporation

Test date: Feb-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Peak Portability Flags (Continued)

483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
-no-prec-div -ansi-alias

456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch
-opt-streaming-stores always -vec-guard-write
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs -L/opt/SmartHeap_8.1/lib -lsmarheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs -L/opt/SmartHeap_8.1/lib -lsmarheap

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

T120Rc-1
(Intel Xeon X5260)

SPECint_rate2006 = 81.2

SPECint_rate_base2006 = 69.3

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Feb-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Peak Other Flags (Continued)

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-INT-ia32-linux-flags.20090714.00.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-INT-ia32-linux-flags.20090714.00.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 15:39:28 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 7 March 2008.