



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems Sun Fire X4150

SPECint®2006 = 27.7
SPECint_base2006 = 24.3

CPU2006 license: 6


Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Jan-2008

Hardware Availability: Feb-2008

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon X5460
 CPU Characteristics: 3.16 GHz, 2x6 MB L2 shared, 1333 MHz system bus
 CPU MHz: 3166
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 (order by number of chips)
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8x2GB DDR2 PC2-5300F 2rank CAS 5-5-5 with ECC)
 Disk Subsystem: SAS, 72 GB, 10K RPM
 Other Hardware: None

Software

Operating System: SUSE LINUX Enterprise Server 10 SP1 for x86_64
 Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1
 Build 20070824
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Multi-user, run level 3
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap library V8.1
 Binutils 2.17.50.0.15



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4150

SPECint2006 = 27.7
SPECint_base2006 = 24.3

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Jan-2008
Hardware Availability: Feb-2008
Software Availability: Nov-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	479	20.4	479	20.4	478	20.4	386	25.3	387	25.2	386	25.3
401.bzip2	566	17.1	563	17.1	566	17.0	524	18.4	524	18.4	524	18.4
403.gcc	508	15.8	504	16.0	509	15.8	395	20.4	396	20.3	395	20.4
429.mcf	377	24.2	377	24.2	376	24.3	376	24.2	375	24.3	375	24.3
445.gobmk	511	20.5	511	20.5	511	20.5	459	22.9	459	22.8	459	22.8
456.hmmcr	563	16.6	563	16.6	563	16.6	323	28.9	323	28.9	323	28.9
458.sjeng	654	18.5	654	18.5	651	18.6	590	20.5	591	20.5	589	20.6
462.libquantum	86.1	241	87.1	238	88.1	235	86.1	241	87.1	238	88.1	235
464.h264ref	674	32.8	674	32.8	675	32.8	630	35.1	629	35.2	630	35.1
471.omnetpp	395	15.8	394	15.9	394	15.8	367	17.0	367	17.0	368	17.0
473.astar	448	15.7	449	15.6	451	15.6	410	17.1	409	17.2	412	17.0
483.xalancbmk	263	26.3	262	26.3	262	26.3	263	26.3	262	26.3	262	26.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited
OMP_NUM_THREADS set to 8
KMP_AFFINITY set to physical,0

Platform Notes

Default BIOS configurations were used.

General Notes

All benchmarks were compiled in 32-bit mode except 401.bzip2 and 456.hmmcr for peak were compiled in 64-bit mode

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4150

SPECint2006 = 27.7
SPECint_base2006 = 24.3

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Jan-2008
Hardware Availability: Feb-2008
Software Availability: Nov-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast -vec-guard-write -parallel -par-runtime-control
C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc
401.bzip2: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/bin/icc
456.hmmer: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/bin/icc
C++ benchmarks:
icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4150

SPECint2006 = 27.7
SPECint_base2006 = 24.3

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Jan-2008
Hardware Availability: Feb-2008
Software Availability: Nov-2007

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
-prefetch

401.bzip2: -L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/lib -I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/include
-prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
-no-prec-div -ansi-alias

456.hmmer: -L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/lib -I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/include
-fast -unroll2 -ansi-alias -opt-multi-version-aggressive
-auto-ilp32

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: basepeak = yes

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4150

SPECint2006 = 27.7
SPECint_base2006 = 24.3

CPU2006 license: 6

Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Jan-2008

Hardware Availability: Feb-2008

Software Availability: Nov-2007

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.26.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.26.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 15:37:33 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 7 March 2008.