



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint®_rate2006 = Not Run

PRIMERGY TX300 S4, Intel Xeon E5430, 2.66 GHz

SPECint_rate_base2006 = 102

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Mar-2008

Hardware Availability: Dec-2007

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E5430
 CPU Characteristics: 1333 MHz system bus
 CPU MHz: 2667
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8x2 GB PC2-5300F, 2 rank, CL 5-5-5, ECC)
 Disk Subsystem: 1x SAS, 73 GB, 15000 rpm
 Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ Compiler for Linux32 and Linux64, Version 10.1, Build 20070913
 Auto Parallel: No
 File System: ext2
 System State: Multi-User Run Level 3
 Base Pointers: 32-bit
 Peak Pointers: Not Applicable
 Other Software: MicroQuill SmartHeap Library, Version 8.1 binutils-2.17.50.0.5-0.1.x86_64



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint_rate2006 = Not Run

PRIMERGY TX300 S4, Intel Xeon E5430, 2.66 GHz

SPECint_rate_base2006 = 102

CPU2006 license: 22

Test date: Mar-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Dec-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	<u>597</u>	<u>131</u>	594	132	597	131							
401.bzip2	8	<u>834</u>	<u>92.6</u>	842	91.7	826	93.5							
403.gcc	8	696	92.6	<u>697</u>	<u>92.4</u>	697	92.4							
429.mcf	8	909	80.2	<u>913</u>	<u>79.9</u>	914	79.8							
445.gobmk	8	629	134	<u>629</u>	<u>133</u>	632	133							
456.hammer	8	682	109	<u>681</u>	<u>110</u>	681	110							
458.sjeng	8	771	126	<u>772</u>	<u>125</u>	772	125							
462.libquantum	8	3259	50.9	3258	50.9	<u>3259</u>	<u>50.9</u>							
464.h264ref	8	<u>795</u>	<u>223</u>	795	223	793	223							
471.omnetpp	8	<u>719</u>	<u>69.5</u>	718	69.6	720	69.5							
473.astar	8	<u>733</u>	<u>76.6</u>	735	76.4	731	76.8							
483.xalancbmk	8	<u>454</u>	<u>122</u>	454	122	454	122							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

Platform Notes

BIOS configuration:
Hardware Prefetch = Disable, Adjacent Sector Prefetch = Disable

General Notes

For information about Fujitsu Siemens Computers please see:
<http://www.fujitsu-siemens.com>

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint_rate2006 = Not Run

PRIMERGY TX300 S4, Intel Xeon E5430, 2.66 GHz

SPECint_rate_base2006 = 102

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Mar-2008

Hardware Availability: Dec-2007

Software Availability: Nov-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/opt/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090713.01.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090713.01.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 17:55:05 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 3 April 2008.