



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECfp®_rate2006 = 78.4

Servidor Itaotec MX221 (Intel Xeon X5460)

SPECfp_rate_base2006 = 71.0

CPU2006 license: 9001


Test sponsor: Itaotec

Tested by: Itaotec

Test date: Mar-2008

Hardware Availability: Dec-2007

Software Availability: Jan-2008



Hardware

CPU Name: Intel Xeon X5460
 CPU Characteristics: 3160
 CPU MHz: Integrated
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ and Fortran Compiler 10.1 for Linux Build 20080112 Package ID: l_cc_p_10.1.012, l_fc_p_10.1.012
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Run level 3 (multi-user)
 Base Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECfp_rate2006 = 78.4

Servidor Itaotec MX221 (Intel Xeon X5460)

SPECfp_rate_base2006 = 71.0

CPU2006 license: 9001
Test sponsor: Itaotec
Tested by: Itaotec

Test date: Mar-2008
Hardware Availability: Dec-2007
Software Availability: Jan-2008

L3 Cache: None
Other Cache: None
Memory: 16 GB (8 * 2 GB PC2-5300 FBDIMM, CL-5-5-5, ECC)
Disk Subsystem: 1 x SCSI, 73GB, 15000 RPM
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: Binutils 2.17.10.50

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3070	35.4	<u>3071</u>	<u>35.4</u>	3073	35.4	4	1524	35.7	<u>1524</u>	<u>35.7</u>	1526	35.6
416.gamess	8	844	186	842	186	<u>843</u>	<u>186</u>	8	<u>830</u>	<u>189</u>	831	188	830	189
433.milc	8	2276	32.3	<u>2281</u>	<u>32.2</u>	2284	32.1	8	<u>2328</u>	<u>31.6</u>	2324	31.6	2328	31.5
434.zeusmp	8	1037	70.2	1032	70.6	<u>1033</u>	<u>70.5</u>	8	<u>1037</u>	<u>70.2</u>	1037	70.2	1036	70.3
435.gromacs	8	<u>376</u>	<u>152</u>	376	152	376	152	8	367	155	<u>364</u>	<u>157</u>	363	158
436.cactusADM	8	1296	73.7	1306	73.2	<u>1298</u>	<u>73.7</u>	1	117	102	117	103	<u>117</u>	<u>102</u>
437.leslie3d	8	2719	27.7	<u>2711</u>	<u>27.7</u>	2705	27.8	4	1336	28.1	<u>1333</u>	<u>28.2</u>	1330	28.3
444.namd	8	483	133	483	133	<u>483</u>	<u>133</u>	8	<u>480</u>	<u>134</u>	480	134	480	134
447.dealII	8	<u>692</u>	<u>132</u>	674	136	696	131	8	655	140	682	134	<u>661</u>	<u>138</u>
450.soplex	8	1750	38.1	1752	38.1	<u>1751</u>	<u>38.1</u>	8	1595	41.8	<u>1592</u>	<u>41.9</u>	1590	42.0
453.povray	8	202	211	<u>204</u>	<u>208</u>	204	208	8	169	252	<u>169</u>	<u>252</u>	168	253
454.calculix	8	539	122	<u>538</u>	<u>123</u>	538	123	8	395	167	<u>395</u>	<u>167</u>	393	168
459.GemsFDTD	8	2915	29.1	2932	29.0	<u>2930</u>	<u>29.0</u>	8	2959	28.7	2952	28.8	<u>2954</u>	<u>28.7</u>
465.tonto	8	652	121	<u>654</u>	<u>120</u>	654	120	8	644	122	646	122	<u>644</u>	<u>122</u>
470.lbm	8	<u>3753</u>	<u>29.3</u>	3751	29.3	3763	29.2	4	<u>1418</u>	<u>38.7</u>	1417	38.8	1419	38.7
481.wrf	8	1730	51.7	<u>1733</u>	<u>51.6</u>	1733	51.6	8	<u>1742</u>	<u>51.3</u>	1744	51.2	1739	51.4
482.sphinx3	8	2241	69.6	<u>2224</u>	<u>70.1</u>	2220	70.2	4	747	104	<u>756</u>	<u>103</u>	756	103

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

OMP_NUM_THREADS set to number of cores
KMP_STACK_SIZE set to 64M
KMP_AFFINITY set to physical,0

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run.
'/usr/bin/taskset' used to bind benchmark copies to processors.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECfp_rate2006 = 78.4

Servidor Itaotec MX221 (Intel Xeon X5460)

SPECfp_rate_base2006 = 71.0

CPU2006 license: 9001
Test sponsor: Itaotec
Tested by: Itaotec

Test date: Mar-2008
Hardware Availability: Dec-2007
Software Availability: Jan-2008

Platform Notes

BIOS configuration:
Hardware Prefetch Disabled

General Notes

This result was measured on the Servidor Itaotec MX201.
The Servidor Itaotec MX221 and the Servidor Itaotec MX201 are electronically equivalent.

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECfp_rate2006 = 78.4

Servidor Itautec MX221 (Intel Xeon X5460)

SPECfp_rate_base2006 = 71.0

CPU2006 license: 9001
Test sponsor: Itautec
Tested by: Itautec

Test date: Mar-2008
Hardware Availability: Dec-2007
Software Availability: Jan-2008

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast

Peak Compiler Invocation

C benchmarks (except as noted below):
/opt/intel/cc/10.1.012/bin/icc -L/opt/intel/cc/10.1.012/lib
-I/opt/intel/cc/10.1.012/include

433.milc: icc

C++ benchmarks (except as noted below):
icpc

450.soplex: /opt/intel/cc/10.1.012/bin/icpc -L/opt/intel/cc/10.1.012/lib
-I/opt/intel/cc/10.1.012/include

Fortran benchmarks (except as noted below):
ifort

437.leslie3d: /opt/intel/fc/10.1.012/bin/ifort -L/opt/intel/fc/10.1.012/lib
-I/opt/intel/fc/10.1.012/include

Benchmarks using both Fortran and C:
icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECfp_rate2006 = 78.4

Servidor Itaotec MX221 (Intel Xeon X5460)

SPECfp_rate_base2006 = 71.0

CPU2006 license: 9001
Test sponsor: Itaotec
Tested by: Itaotec

Test date: Mar-2008
Hardware Availability: Dec-2007
Software Availability: Jan-2008

Peak Portability Flags (Continued)

453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32
470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3
482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32
447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-
450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3
453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch
416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-
434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast
437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3
459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECfp_rate2006 = 78.4

Servidor Itautec MX221 (Intel Xeon X5460)

SPECfp_rate_base2006 = 71.0

CPU2006 license: 9001
Test sponsor: Itautec
Tested by: Itautec

Test date: Mar-2008
Hardware Availability: Dec-2007
Software Availability: Jan-2008

Peak Optimization Flags (Continued)

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Itautec-ic10.1-FP-intel64-linux-flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Itautec-ic10.1-FP-intel64-linux-flags.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.1.
Report generated on Tue Jul 22 16:43:02 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 April 2008.