



SPEC[®] CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECint[®]2006 = 16.2

Bull Escala PL1660 (3.5 GHz, 1 core)

SPECint_base2006 = 13.3

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Mar-2008

Hardware Availability: Oct-2007

Software Availability: Oct-2007



Hardware

CPU Name: POWER6
 CPU Characteristics:
 CPU MHz: 3500
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 2 cores/chip
 CPU(s) orderable: 4,8,12,16 cores
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per core
 L3 Cache: 32 MB I+D off chip per chip
 Other Cache: None
 Memory: 128 GB (64x2 GB) DDR2 667 MHz
 Disk Subsystem: 2x73 GB SAS 15K RPM
 Other Hardware: None

Software

Operating System: IBM AIX 5L V5.3 updated with the 5300-07 Technology Level
 Compiler: XL C/C++ Enterprise Edition V9 for AIX Updated with the Oct2007 PTF.
 Auto Parallel: No
 File System: AIX/JFS2
 System State: Multi-user
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: --



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECint2006 = **16.2**

Bull Escala PL1660 (3.5 GHz, 1 core)

SPECint_base2006 = **13.3**

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Mar-2008
Hardware Availability: Oct-2007
Software Availability: Oct-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	1155	8.46	<u>1154</u>	<u>8.47</u>	1154	8.47	1058	9.23	1059	9.23	<u>1058</u>	<u>9.23</u>
401.bzip2	1052	9.17	1052	9.17	<u>1052</u>	<u>9.17</u>	<u>805</u>	<u>12.0</u>	805	12.0	805	12.0
403.gcc	<u>651</u>	<u>12.4</u>	651	12.4	651	12.4	534	15.1	534	15.1	<u>534</u>	<u>15.1</u>
429.mcf	341	26.7	<u>341</u>	<u>26.7</u>	341	26.7	326	28.0	<u>326</u>	<u>28.0</u>	326	28.0
445.gobmk	890	11.8	<u>890</u>	<u>11.8</u>	890	11.8	769	13.6	<u>769</u>	<u>13.6</u>	769	13.6
456.hammer	<u>1035</u>	<u>9.02</u>	1035	9.02	1035	9.02	733	12.7	<u>733</u>	<u>12.7</u>	733	12.7
458.sjeng	<u>1189</u>	<u>10.2</u>	1188	10.2	1191	10.2	<u>1057</u>	<u>11.4</u>	1057	11.4	1057	11.4
462.libquantum	533	38.9	<u>533</u>	<u>38.9</u>	533	38.9	<u>291</u>	<u>71.3</u>	291	71.3	291	71.3
464.h264ref	1056	21.0	<u>1056</u>	<u>21.0</u>	1056	21.0	954	23.2	<u>954</u>	<u>23.2</u>	954	23.2
471.omnetpp	<u>525</u>	<u>11.9</u>	525	11.9	524	11.9	448	13.9	448	13.9	<u>448</u>	<u>13.9</u>
473.astar	762	9.22	<u>762</u>	<u>9.22</u>	761	9.22	656	10.7	<u>655</u>	<u>10.7</u>	655	10.7
483.xalancbmk	579	11.9	<u>579</u>	<u>11.9</u>	579	11.9	<u>500</u>	<u>13.8</u>	500	13.8	500	13.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

See flags file of details on following settings.
all ulimits set to unlimited.
Environment variables set before executing benchmarks:
MALLOCOPTIONS=pool
MEMORY_AFFINITY=MCM
XLFRTOPTS=intrinths=1
System set to "Enhanced" mode when defining partition on HMC.
Remote console disabled in /etc/inittab.
fdpr binary optimization tool used for:
400.perlbench 401.bzip2 403.gcc 429.mcf 456.hammer
458.sjeng 462.libquantum 464.h264ref 473.astar
Speed run on 1 core partition defined on HMC.
128 16M large pages defined with vmo command

Base Compiler Invocation

C benchmarks:
/usr/vac/bin/xlc -qlanglvl=extc99

C++ benchmarks:
/usr/vacpp/bin/xlC



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECint2006 = 16.2

Bull Escala PL1660 (3.5 GHz, 1 core)

SPECint_base2006 = 13.3

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Mar-2008

Hardware Availability: Oct-2007

Software Availability: Oct-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_AIX
462.libquantum: -DSPEC_CPU_AIX
464.h264ref: -DSPEC_CPU_AIX -qchars=signed
483.xalancbmk: -DSPEC_CPU_AIX

Base Optimization Flags

C benchmarks:
-bmaxdata:0x50000000 -O5 -qlargepage -D_ILS_MACROS -qalias=noansi
-qalloca -blpdata

C++ benchmarks:
-bmaxdata:0x20000000 -O5 -qlargepage -D_ILS_MACROS -qrtti=all
-blpdata

Base Other Flags

C benchmarks:
-qipa=noobject -qipa=threads -qsuppress=1500-036

C++ benchmarks:
-qipa=noobject -qipa=threads -qsuppress=1500-036

Peak Compiler Invocation

C benchmarks:
/usr/vac/bin/xlc -qlanglvl=extc99

C++ benchmarks:
/usr/vacpp/bin/xlC

Peak Portability Flags

400.perlbench: -DSPEC_CPU_AIX
403.gcc: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_AIX
464.h264ref: -DSPEC_CPU_AIX -qchars=signed
483.xalancbmk: -DSPEC_CPU_AIX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECint2006 = 16.2

Bull Escala PL1660 (3.5 GHz, 1 core)

SPECint_base2006 = 13.3

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Mar-2008
Hardware Availability: Oct-2007
Software Availability: Oct-2007

Peak Optimization Flags

C benchmarks:

400.perlbench: -bmaxdata:0x50000000 -qpdf1(pass 1) -qpdf2(pass 2) -O4
-qlargepage -qenablevmx -qvecnvols -D_ILS_MACROS
-qalias=noansi -qfdpr -blpdata

401.bzip2: -bmaxdata:0x4ffffffc -qpdf1(pass 1) -qpdf2(pass 2) -O5
-qlargepage -qenablevmx -qvecnvols -D_ILS_MACROS -qfdpr
-blpdata

403.gcc: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qlargepage
-D_ILS_MACROS -qalloca -qfdpr -q64 -blpdata

429.mcf: -bmaxdata:0x50000000 -O5 -qlargepage -qenablevmx
-qvecnvols -D_ILS_MACROS -qfdpr -blpdata

445.gobmk: -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qlargepage -qenablevmx
-qvecnvols -D_ILS_MACROS -blpdata

456.hmmr: -O5 -qlargepage -D_ILS_MACROS -qfdpr -blpdata

458.sjeng: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qlargepage -qenablevmx
-qvecnvols -D_ILS_MACROS -qfdpr -blpdata

462.libquantum: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qlargepage -qenablevmx
-qvecnvols -D_ILS_MACROS -q64 -qfdpr -blpdata

464.h264ref: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -q64 -D_ILS_MACROS
-qenablevmx -qvecnvols -qfdpr -bdatapsize:64K
-bstacksize:64K -btextpsize:64K

C++ benchmarks:

471.omnetpp: -bmaxdata:0x20000000 -qpdf1(pass 1) -qpdf2(pass 2) -O5
-qlargepage -qenablevmx -qvecnvols -D_ILS_MACROS
-qalign=natural -qrtti=all -qinlglue -blpdata

473.astar: -bmaxdata:0x20000000 -qpdf1(pass 1) -qpdf2(pass 2) -O5
-qlargepage -D_ILS_MACROS -qfdpr -qinlglue
-qalign=natural -blpdata

483.xalancbmk: -bmaxdata:0x20000000 -qpdf1(pass 1) -qpdf2(pass 2) -O5
-qlargepage -D_ILS_MACROS -qinlglue -D__IBM_FAST_VECTOR
-blpdata



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECint2006 = 16.2

Bull Escala PL1660 (3.5 GHz, 1 core)

SPECint_base2006 = 13.3

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Mar-2008
Hardware Availability: Oct-2007
Software Availability: Oct-2007

Peak Other Flags

C benchmarks:

-qipa=noobject -qipa=threads -qsuppress=1500-036

C++ benchmarks:

-qipa=noobject -qipa=threads -qsuppress=1500-036

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090713.06.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090713.06.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 18:36:04 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 15 April 2008.