



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Limited PRIMEQUEST 540A

SPECfp<sup>®</sup>\_rate2006 = 347

SPECfp\_rate\_base2006 = 338

CPU2006 license: 19


Test sponsor: Fujitsu Limited

Tested by: Fujitsu Limited

Test date: Mar-2008

Hardware Availability: May-2008

Software Availability: Feb-2008



### Hardware

CPU Name: Dual-Core Intel Itanium 9130M  
 CPU Characteristics: 1.66GHz/8MB, 667MHz FSB  
 CPU MHz: 1667  
 FPU: Integrated  
 CPU(s) enabled: 32 cores, 16 chips, 2 cores/chip  
 CPU(s) orderable: 2-16 chips  
 Primary Cache: 16 KB I + 16 KB D on chip per core  
 Secondary Cache: 1 MB I + 256 KB D on chip per core

Continued on next page

### Software

Operating System: Red Hat Enterprise Linux 5.1,  
 Kernel 2.6.18-53.el5 on an ia64  
 Compiler: Intel C++ Compiler for Linux 10.1  
 (Build 20080112)  
 Intel Fortran Compiler for Linux 10.1  
 (Build 20080112)  
 Auto Parallel: No  
 File System: ext2

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited  
PRIMEQUEST 540A

SPECfp\_rate2006 = 347  
SPECfp\_rate\_base2006 = 338

CPU2006 license: 19

Test sponsor: Fujitsu Limited

Tested by: Fujitsu Limited

Test date: Mar-2008

Hardware Availability: May-2008

Software Availability: Feb-2008

L3 Cache: 4 MB I+D on chip per core  
Other Cache: None  
Memory: 256 GB (128 x 2GB DDR2-667 DIMMs)  
Disk Subsystem: 2 x 147GB (SCSI Ultra 320, 10000rpm)  
No RAID configuration  
Other Hardware: None

System State: Runlevel 1 (single user mode)  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	32	1444	301	1441	302	<b>1442</b>	<b>302</b>	32	1420	306	1406	309	<b>1411</b>	<b>308</b>
416.gamess	32	1971	318	1971	318	<b>1971</b>	<b>318</b>	32	<b>1751</b>	<b>358</b>	1751	358	1750	358
433.milc	32	<b>1425</b>	<b>206</b>	1423	206	1427	206	32	1431	205	<b>1421</b>	<b>207</b>	1414	208
434.zeusmp	32	818	356	823	354	<b>820</b>	<b>355</b>	32	827	352	801	364	<b>826</b>	<b>353</b>
435.gromacs	32	<b>520</b>	<b>439</b>	517	442	520	439	32	540	423	<b>539</b>	<b>424</b>	538	424
436.cactusADM	32	579	660	<b>578</b>	<b>662</b>	577	662	32	577	663	<b>579</b>	<b>661</b>	581	659
437.leslie3d	32	<b>1210</b>	<b>249</b>	1209	249	1210	249	32	1210	249	<b>1213</b>	<b>248</b>	1219	247
444.namd	32	339	757	339	756	<b>339</b>	<b>757</b>	32	298	860	<b>298</b>	<b>860</b>	298	860
447.dealII	32	897	408	<b>897</b>	<b>408</b>	898	408	32	871	420	<b>867</b>	<b>422</b>	867	422
450.soplex	32	1456	183	1452	184	<b>1453</b>	<b>184</b>	32	1408	190	<b>1405</b>	<b>190</b>	1402	190
453.povray	32	556	306	<b>556</b>	<b>306</b>	557	306	32	481	354	481	354	<b>481</b>	<b>354</b>
454.calculix	32	565	468	<b>559</b>	<b>472</b>	558	473	32	543	487	<b>544</b>	<b>486</b>	544	486
459.GemsFDTD	32	1537	221	<b>1523</b>	<b>223</b>	1522	223	32	<b>1521</b>	<b>223</b>	1517	224	1524	223
465.tonto	32	878	359	876	359	<b>877</b>	<b>359</b>	32	943	334	936	336	<b>943</b>	<b>334</b>
470.lbm	32	1907	231	1906	231	<b>1906</b>	<b>231</b>	32	<b>1906</b>	<b>231</b>	1906	231	1913	230
481.wrf	32	941	380	952	375	<b>945</b>	<b>378</b>	32	<b>943</b>	<b>379</b>	951	376	941	380
482.sphinx3	32	1856	336	1802	346	<b>1812</b>	<b>344</b>	32	1823	342	1776	351	<b>1783</b>	<b>350</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

Processes are bound to CPUs using taskset.

limit stacksize unlimited

Memory system is in "Non Mirror Mode".

The following 2 environment variables were set

MALLOC\_MMAP\_MAX=0

MALLOC\_TRIM\_THRESHOLD=-1

This will cause use of sbrk() calls instead of  
mmap() calls to get memory from the system.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited  
PRIMEQUEST 540A

SPECfp\_rate2006 = 347  
SPECfp\_rate\_base2006 = 338

CPU2006 license: 19  
Test sponsor: Fujitsu Limited  
Tested by: Fujitsu Limited

Test date: Mar-2008  
Hardware Availability: May-2008  
Software Availability: Feb-2008

## Base Compiler Invocation

C benchmarks:  
icc  
C++ benchmarks:  
icpc  
Fortran benchmarks:  
ifort  
Benchmarks using both Fortran and C:  
icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.lelie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX -DSPEC\_CPU\_CASE\_FLAG  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:  
-fast -IPF\_fp\_relaxed -opt-prefetch-next-iteration -ansi-alias  
C++ benchmarks:  
-fast -IPF\_fp\_relaxed -opt-prefetch-next-iteration -ansi-alias  
Fortran benchmarks:  
-fast -IPF-fp-relaxed -opt-prefetch-next-iteration  
Benchmarks using both Fortran and C:  
-fast -IPF\_fp\_relaxed -opt-prefetch-next-iteration -ansi-alias  
-IPF-fp-relaxed



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited  
PRIMEQUEST 540A

SPECfp\_rate2006 = 347  
SPECfp\_rate\_base2006 = 338

CPU2006 license: 19  
Test sponsor: Fujitsu Limited  
Tested by: Fujitsu Limited

Test date: Mar-2008  
Hardware Availability: May-2008  
Software Availability: Feb-2008

## Peak Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: -fast -IPF-fp-relaxed -opt-prefetch-next-iteration  
-fno-alias -ansi-alias

470.lbm: -fast -IPF-fp-relaxed -opt-prefetch-next-iteration  
-ansi-alias

482.sphinx3: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed  
-opt-prefetch-next-iteration -fno-alias  
-no-opt-prefetch-initial-values -ansi-alias

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed  
-opt-prefetch-next-iteration -no-prefetch -auto-ilp32  
-fno-alias -ansi-alias

447.dealIII: -fast -IPF-fp-relaxed -opt-prefetch-next-iteration  
-inline-factor=150 -no-alias-args -no-opt-loadpair  
-ansi-alias

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed  
-opt-prefetch-next-iteration -auto-ilp32 -no-alias-args  
-ansi-alias

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed  
-opt-prefetch-next-iteration -inline-factor=150 -ansi-alias

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu Limited**  
**PRIMEQUEST 540A**

**SPECfp\_rate2006 = 347**

**SPECfp\_rate\_base2006 = 338**

**CPU2006 license:** 19

**Test sponsor:** Fujitsu Limited

**Tested by:** Fujitsu Limited

**Test date:** Mar-2008

**Hardware Availability:** May-2008

**Software Availability:** Feb-2008

## Peak Optimization Flags (Continued)

Fortran benchmarks:

410.bwaves: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed  
-opt-prefetch-next-iteration

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed  
-opt-prefetch-next-iteration -no-prefetch

434.zeusmp: Same as 410.bwaves

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed  
-opt-prefetch-next-iteration -no-opt-loadpair

459.GemsFDTD: -fast -IPF-fp-relaxed -opt-prefetch-next-iteration

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed  
-opt-prefetch-next-iteration -inline-factor=150 -no-prefetch

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed  
-opt-prefetch-next-iteration -no-prefetch -fno-alias  
-ansi-alias

436.cactusADM: -fast -IPF-fp-relaxed -opt-prefetch-next-iteration  
-ansi-alias

454.calculix: -fast -IPF-fp-relaxed -opt-prefetch-next-iteration  
-inline-factor=150 -no-opt-prefetch-initial-values  
-ansi-alias

481.wrf: -fast -IPF-fp-relaxed -opt-prefetch-next-iteration  
-no-opt-loadpair -ansi-alias

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Fujitsu.PQ580A.ipf.linux.flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Fujitsu.PQ580A.ipf.linux.flags.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited  
PRIMEQUEST 540A

SPECfp\_rate2006 = 347

SPECfp\_rate\_base2006 = 338

CPU2006 license: 19

Test sponsor: Fujitsu Limited

Tested by: Fujitsu Limited

Test date: Mar-2008

Hardware Availability: May-2008

Software Availability: Feb-2008

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.1.  
Report generated on Tue Jul 22 18:27:34 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 15 April 2008.