



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp[®]_rate2006 = 36.2

Acer Altos R520 (Intel Xeon E5405)

SPECfp_rate_base2006 = 33.7

CPU2006 license: 97


Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Mar-2008

Hardware Availability: Nov-2007

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E5405
 CPU Characteristics: 1333MHz system bus
 CPU MHz: 2000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1, 2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

Software

Operating System: SuSE Linux Enterprise Server 10 SP1 (x86_64)
 Kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ and Fortran Compiler 10.1 for Linux
 Build 20070913 Package ID: l_cc_p_10.1.008,
 l_fc_p_10.1.008
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Multi-user, level 3
 Base Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp_rate2006 = 36.2

Acer Altos R520 (Intel Xeon E5405)

SPECfp_rate_base2006 = 33.7

CPU2006 license: 97
Test sponsor: Acer Incorporated
Tested by: Acer Incorporated

Test date: Mar-2008
Hardware Availability: Nov-2007
Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5)
Disk Subsystem: 1 x 73GB 10000RPM SAS HDD
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: Binutils 2.17.50.0.15

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	2297	23.7	<u>2302</u>	<u>23.6</u>	2303	23.6	4	<u>2280</u>	<u>23.8</u>	2280	23.8	2280	23.8
416.gamess	4	1335	58.7	<u>1333</u>	<u>58.8</u>	1332	58.8	4	<u>1314</u>	<u>59.6</u>	1312	59.7	1315	59.6
433.milc	4	<u>1777</u>	<u>20.7</u>	1782	20.6	1775	20.7	4	1764	20.8	<u>1764</u>	<u>20.8</u>	1766	20.8
434.zeusmp	4	1028	35.4	<u>1034</u>	<u>35.2</u>	1034	35.2	4	1034	35.2	1036	35.1	<u>1035</u>	<u>35.2</u>
435.gromacs	4	<u>576</u>	<u>49.6</u>	577	49.5	575	49.6	4	562	50.8	<u>562</u>	<u>50.8</u>	564	50.6
436.cactusADM	4	1259	38.0	1264	37.8	<u>1262</u>	<u>37.9</u>	1	<u>256</u>	<u>46.7</u>	257	46.5	254	47.0
437.leslie3d	4	2114	17.8	2088	18.0	<u>2098</u>	<u>17.9</u>	4	2035	18.5	<u>2036</u>	<u>18.5</u>	2039	18.4
444.namd	4	761	42.2	762	42.1	<u>761</u>	<u>42.1</u>	4	<u>756</u>	<u>42.4</u>	757	42.4	755	42.5
447.dealII	4	793	57.7	786	58.2	<u>787</u>	<u>58.1</u>	4	759	60.3	763	60.0	<u>762</u>	<u>60.0</u>
450.soplex	4	1428	23.4	<u>1427</u>	<u>23.4</u>	1427	23.4	4	1286	25.9	<u>1287</u>	<u>25.9</u>	1288	25.9
453.povray	4	<u>315</u>	<u>67.6</u>	314	67.8	321	66.4	4	270	78.9	<u>270</u>	<u>78.8</u>	270	78.8
454.calculix	4	<u>785</u>	<u>42.0</u>	786	42.0	784	42.1	4	555	59.4	553	59.7	<u>555</u>	<u>59.5</u>
459.GemsFDTD	4	2259	18.8	2246	18.9	<u>2254</u>	<u>18.8</u>	4	2266	18.7	<u>2254</u>	<u>18.8</u>	2253	18.8
465.tonto	4	819	48.1	<u>822</u>	<u>47.9</u>	822	47.9	4	795	49.5	<u>796</u>	<u>49.5</u>	801	49.1
470.lbm	4	3384	16.2	<u>3383</u>	<u>16.2</u>	3383	16.2	4	2875	19.1	2875	19.1	<u>2875</u>	<u>19.1</u>
481.wrf	4	<u>1441</u>	<u>31.0</u>	1443	31.0	1436	31.1	4	1444	31.0	1434	31.2	<u>1441</u>	<u>31.0</u>
482.sphinx3	4	2064	37.8	2023	38.5	<u>2056</u>	<u>37.9</u>	4	1936	40.3	<u>1932</u>	<u>40.3</u>	1927	40.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

This result was measured on the Acer Altos R520.
The Altos R720 and Altos R520 are electronically equivalent.

All benchmarks compiled in 64-bit mode except 450.soplex, 470.lbm, 482.sphinx3 and 437.leslie3d, at peak, are compiled in 32-bit mode

BIOS Settings

Hardware Prefetcher set to OFF

Adjacent Cache Line Prefetch set to OFF

All results but peak 436.cactusADM used taskset to bind processes to cores.

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp_rate2006 = 36.2

Acer Altos R520 (Intel Xeon E5405)

SPECfp_rate_base2006 = 33.7

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Mar-2008

Hardware Availability: Nov-2007

Software Availability: Nov-2007

General Notes (Continued)

"ulimit -s unlimited" was set for stacksize unlimited
OMP_NUM_THREADS set to number of cores

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp_rate2006 = 36.2

Acer Altos R520 (Intel Xeon E5405)

SPECfp_rate_base2006 = 33.7

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Mar-2008

Hardware Availability: Nov-2007

Software Availability: Nov-2007

Base Optimization Flags (Continued)

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast

Peak Compiler Invocation

C benchmarks (except as noted below):

/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include

433.milc: icc

C++ benchmarks (except as noted below):

icpc

450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include

Fortran benchmarks (except as noted below):

ifort

437.leslie3d: /opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib
-I/opt/intel/fc/10.1.008/include

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp_rate2006 = 36.2

Acer Altos R520 (Intel Xeon E5405)

SPECfp_rate_base2006 = 33.7

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Mar-2008

Hardware Availability: Nov-2007

Software Availability: Nov-2007

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp_rate2006 = 36.2

Acer Altos R520 (Intel Xeon E5405)

SPECfp_rate_base2006 = 33.7

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Mar-2008

Hardware Availability: Nov-2007

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-fp-linux64-revC.20090713.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-fp-linux64-revC.20090713.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 17:33:30 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 11 June 2008.