



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp®_rate2006 = 44.7

IBM BladeCenter HS12 (Intel Xeon X3353)

SPECfp_rate_base2006 = 40.3

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: May-2008

Hardware Availability: May-2008

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon X3353
 CPU Characteristics: 1333MHz system bus
 CPU MHz: 2667
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

Software

Operating System: SuSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ and Fortran Compiler 10.1 for Linux Build 20070913 Package ID: l_cc_p_10.1.008, l_fc_p_10.1.008
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Multi-user, run level 3
 Base Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 44.7

IBM BladeCenter HS12 (Intel Xeon X3353)

SPECfp_rate_base2006 = 40.3

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: May-2008

Hardware Availability: May-2008

Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 8 GB (4 x 2 GB DDR2-5300 ECC)
Disk Subsystem: 1 x 73 GB SAS, 10000 RPM
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: Binutils 2.17.50.0.15

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	2153	25.2	<u>2140</u>	<u>25.4</u>	2125	25.6	4	2112	25.7	2126	25.6	<u>2115</u>	<u>25.7</u>
416.gamess	4	<u>1000</u>	<u>78.3</u>	1003	78.0	999	78.4	4	985	79.5	<u>986</u>	<u>79.4</u>	987	79.3
433.milc	4	1933	19.0	<u>1933</u>	<u>19.0</u>	1932	19.0	4	1900	19.3	1897	19.4	<u>1898</u>	<u>19.3</u>
434.zeusmp	4	804	45.3	<u>802</u>	<u>45.4</u>	784	46.4	4	<u>792</u>	<u>45.9</u>	779	46.7	796	45.7
435.gromacs	4	417	68.5	<u>417</u>	<u>68.4</u>	417	68.4	4	414	69.0	417	68.5	<u>414</u>	<u>69.0</u>
436.cactusADM	4	<u>973</u>	<u>49.1</u>	967	49.4	979	48.8	1	186	64.3	<u>184</u>	<u>64.8</u>	184	64.8
437.leslie3d	4	2000	18.8	1972	19.1	<u>1981</u>	<u>19.0</u>	2	905	20.8	<u>908</u>	<u>20.7</u>	911	20.6
444.namd	4	570	56.3	<u>570</u>	<u>56.3</u>	569	56.3	4	566	56.6	566	56.7	<u>566</u>	<u>56.6</u>
447.dealII	4	522	87.7	<u>523</u>	<u>87.6</u>	523	87.4	4	<u>500</u>	<u>91.4</u>	500	91.5	501	91.3
450.soplex	4	1306	25.6	<u>1313</u>	<u>25.4</u>	1314	25.4	4	1163	28.7	<u>1165</u>	<u>28.6</u>	1168	28.6
453.povray	4	239	89.2	236	90.0	<u>237</u>	<u>89.8</u>	4	202	105	<u>203</u>	<u>105</u>	205	104
454.calculix	4	<u>590</u>	<u>55.9</u>	588	56.1	594	55.6	4	411	80.3	<u>407</u>	<u>81.0</u>	406	81.2
459.GemsFDTD	4	2446	17.4	<u>2448</u>	<u>17.3</u>	2456	17.3	4	<u>2391</u>	<u>17.8</u>	2396	17.7	2390	17.8
465.tonto	4	626	62.9	634	62.1	<u>629</u>	<u>62.6</u>	4	611	64.5	609	64.6	<u>610</u>	<u>64.5</u>
470.lbm	4	3285	16.7	3291	16.7	<u>3289</u>	<u>16.7</u>	2	1090	25.2	<u>1095</u>	<u>25.1</u>	1099	25.0
481.wrf	4	1208	37.0	1213	36.8	<u>1208</u>	<u>37.0</u>	4	1203	37.1	<u>1204</u>	<u>37.1</u>	1212	36.8
482.sphinx3	4	1811	43.0	<u>1820</u>	<u>42.8</u>	1828	42.6	2	771	50.6	784	49.7	<u>779</u>	<u>50.1</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

All benchmarks compiled in 64-bit mode except 437.leslie3d, 450.soplex, 470.lbm and 482.sphinx3, at peak, are compiled in 32-bit mode
Hardware Sector Prefetch Enabled and Adjacent Sector Prefetch Disabled
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
KMP_STACKSIZE set to 64M
taskset utility used to bind CPU(s) to processes

Base Compiler Invocation

C benchmarks:
icc

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 44.7

IBM BladeCenter HS12 (Intel Xeon X3353)

SPECfp_rate_base2006 = 40.3

CPU2006 license: 11

Test date: May-2008

Test sponsor: IBM Corporation

Hardware Availability: May-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

Base Compiler Invocation (Continued)

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 44.7

IBM BladeCenter HS12 (Intel Xeon X3353)

SPECfp_rate_base2006 = 40.3

CPU2006 license: 11

Test date: May-2008

Test sponsor: IBM Corporation

Hardware Availability: May-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

Peak Compiler Invocation

C benchmarks (except as noted below):

```
/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include
```

Fortran benchmarks (except as noted below):

ifort

```
437.leslie3d: /opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib
-I/opt/intel/fc/10.1.008/include
```

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.deall: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32
```

```
470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 44.7

IBM BladeCenter HS12 (Intel Xeon X3353)

SPECfp_rate_base2006 = 40.3

CPU2006 license: 11

Test date: May-2008

Test sponsor: IBM Corporation

Hardware Availability: May-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealIII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-fp-linux64-revC.20090713.html>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 44.7

IBM BladeCenter HS12 (Intel Xeon X3353)

SPECfp_rate_base2006 = 40.3

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: May-2008

Hardware Availability: May-2008

Software Availability: Nov-2007

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-fp-linux64-revC.20090713.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 17:25:33 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 11 June 2008.