



SPEC[®] CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint[®]_rate2006 = Not Run

ProLiant BL2x220c G5
(3.00 GHz, Intel Xeon E5450)

SPECint_rate_base2006 = 108

CPU2006 license: 3


Test date: Jun-2008

Test sponsor: Hewlett-Packard Company

Hardware Availability: May-2008

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E5450
 CPU Characteristics: 3.0 GHz, 2x6 MB L2 shared, 1333 MHz system bus
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 2,3,4 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (4x4 GB PC2-5300P CL5)
 Disk Subsystem: 1x120 GB 5.4 K RPM 2.5" SFF SATA
 Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ Compiler 10.1 for Linux Build 20070913 Package ID: l_cc_p_10.1.008
 Auto Parallel: No
 File System: ext2
 System State: Run level 3 (multi-user)
 Base Pointers: 32-bit
 Peak Pointers: Not Applicable
 Other Software: MicroQuill SmartHeap Library 8.1 binutils-2.17.50



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = Not Run

ProLiant BL2x220c G5
(3.00 GHz, Intel Xeon E5450)

SPECint_rate_base2006 = 108

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Jun-2008
Hardware Availability: May-2008
Software Availability: Nov-2007

Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	533	147	532	147	534	146							
401.bzip2	8	746	104	747	103	751	103							
403.gcc	8	650	99.1	649	99.2	647	99.5							
429.mcf	8	922	79.2	921	79.2	921	79.2							
445.gobmk	8	568	148	569	148	566	148							
456.hammer	8	609	123	609	123	609	122							
458.sjeng	8	687	141	689	141	689	141							
462.libquantum	8	3585	46.2	3580	46.3	3579	46.3							
464.h264ref	8	708	250	709	250	709	250							
471.omnetpp	8	688	72.7	686	72.9	686	72.8							
473.astar	8	693	81.0	698	80.4	696	80.7							
483.xalancbmk	8	430	128	430	128	431	128							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

Platform Notes

BIOS configuration:
Power Regulator set to Static High Performance Mode
Adjacent Sector Prefetch Disabled
Hardware Prefetcher Disabled

General Notes

The ProLiant BL2x220c G5 is comprised of two independent server nodes in a single chassis. Only one of the server nodes was used for this benchmark; the other server node was idle during the benchmark. The active server node contained all of the CPUs and memory described in this disclosure.

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = Not Run

ProLiant BL2x220c G5
(3.00 GHz, Intel Xeon E5450)

SPECint_rate_base2006 = 108

CPU2006 license: 3

Test date: Jun-2008

Test sponsor: Hewlett-Packard Company

Hardware Availability: May-2008

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/cpu2006/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/HP-Intel-ic10.1-linux-int-flags.20090714.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/HP-Intel-ic10.1-linux-int-flags.20090714.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 17:45:42 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 25 June 2008.