



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp[®]_rate2006 = 602

IBM Power 570 (4.2 GHz, 32 core)

SPECfp_rate_base2006 = 517

CPU2006 license: 11


Test date: Sep-2008

Test sponsor: IBM Corporation

Hardware Availability: Nov-2008

Tested by: IBM Corporation

Software Availability: Nov-2008



Hardware

CPU Name: POWER6+
 CPU Characteristics:
 CPU MHz: 4200
 FPU: Integrated
 CPU(s) enabled: 32 cores, 16 chips, 2 cores/chip, 2 threads/core
 CPU(s) orderable: 4,8,16,24,32 cores
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per core

Continued on next page

Software

Operating System: IBM AIX V6.1
 with the 6100-02 Technology Level
 Compiler: IBM XL C/C++ V10.1 for AIX
 IBM XL Fortran V12.1 for AIX
 Auto Parallel: No
 File System: AIX/JFS2
 System State: Multi-user
 Base Pointers: 32-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 602

IBM Power 570 (4.2 GHz, 32 core)

SPECfp_rate_base2006 = 517

CPU2006 license: 11

Test date: Sep-2008

Test sponsor: IBM Corporation

Hardware Availability: Nov-2008

Tested by: IBM Corporation

Software Availability: Nov-2008

L3 Cache: 32 MB I+D off chip per chip
Other Cache: None
Memory: 128 GB (64x2 GB) DDR2 667 MHz
Disk Subsystem: 4x73 GB 4x146 GB SAS 15K RPM
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	64	<u>2954</u>	<u>294</u>	2952	295	2965	293	64	2835	307	<u>2835</u>	<u>307</u>	2835	307
416.gamess	64	<u>1874</u>	<u>669</u>	1874	669	1891	663	64	<u>1827</u>	<u>686</u>	1826	686	1850	677
433.milc	64	2174	270	<u>2173</u>	<u>270</u>	2172	270	64	<u>2107</u>	<u>279</u>	2108	279	2106	279
434.zeusmp	64	1089	535	1104	528	<u>1093</u>	<u>533</u>	64	832	700	776	751	<u>807</u>	<u>722</u>
435.gromacs	64	<u>1019</u>	<u>449</u>	1017	449	1020	448	64	<u>647</u>	<u>707</u>	646	708	655	697
436.cactusADM	64	1254	610	<u>1254</u>	<u>610</u>	1253	610	64	865	884	868	882	<u>866</u>	<u>883</u>
437.leslie3d	64	2127	283	2134	282	<u>2132</u>	<u>282</u>	32	813	370	<u>812</u>	<u>370</u>	812	370
444.namd	64	648	792	596	861	<u>598</u>	<u>859</u>	64	593	865	<u>597</u>	<u>860</u>	612	838
447.dealII	64	627	1170	634	1150	<u>631</u>	<u>1160</u>	64	627	1170	634	1150	<u>631</u>	<u>1160</u>
450.soplex	64	1386	385	<u>1405</u>	<u>380</u>	1410	379	64	1386	385	<u>1405</u>	<u>380</u>	1410	379
453.povray	64	<u>618</u>	<u>551</u>	619	550	617	551	64	<u>449</u>	<u>758</u>	449	758	450	757
454.calculix	64	762	693	760	695	<u>761</u>	<u>694</u>	64	679	777	677	780	<u>679</u>	<u>778</u>
459.GemsFDTD	64	2953	230	3016	225	<u>2993</u>	<u>227</u>	64	<u>2884</u>	<u>235</u>	2933	231	2880	236
465.tonto	64	1262	499	1261	499	<u>1261</u>	<u>499</u>	64	<u>712</u>	<u>885</u>	712	884	708	889
470.lbm	64	<u>1579</u>	<u>557</u>	1581	556	1578	557	64	<u>1579</u>	<u>557</u>	1581	556	1578	557
481.wrf	64	<u>1208</u>	<u>592</u>	1196	598	1209	591	64	<u>1208</u>	<u>592</u>	1196	598	1209	591
482.sphinx3	64	1104	1130	1087	1150	<u>1097</u>	<u>1140</u>	64	<u>1046</u>	<u>1190</u>	1052	1190	1042	1200

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Peak Tuning Notes

fdpr binary optimization tool used for 410.bwaves

with options -bf -bp -ece -lap -las -nop -nopr -pto -RC -RD -rmte -so -tlo -A 64

-lu 6 -rt 0.10 -ihf 60 -sdpla 32 -sdpms 32 -shci 10 -si -siht 15 -lun 32

fdpr binary optimization tool used for 433.milc 435.gromacs 437.leslie3d 453.povray

454.calculix 482.sphinx3

with options -O4 -vrox -pbsi

fdpr binary optimization tool used for 434.zeusmp

with options -O3 -vrox -sdp 9

fdpr binary optimization tool used for 459.GemsFDTD

with options -bf -bp -ece -hr -lap -nop -pca -RC -rmte -si -tb -tlo -vro -A 32 -rt 0.80

-hrf 0.05 -sdp 5 -sdpms 512 -shci 90 -lun 27 -rcctf 0.70 -rccrf 0.80 -rcaf 2



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 602

IBM Power 570 (4.2 GHz, 32 core)

SPECfp_rate_base2006 = 517

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Sep-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008

Submit Notes

The config file option 'submit' was used to assign benchmark copy to specific kernel thread using the "bindprocessor" command (see flags file for details).

Operating System Notes

all ulimits set to unlimited.
6400 16M large pages defined with vmo command

Platform Notes

System set to "Enhanced" mode when defining partition on HMC.

General Notes

Environment variables set by runspec before the start of the run:

MALLOCOPTIONS = "pool"
MEMORY_AFFINITY = "MCM"
XLFRTEOPTS = "intrinthds=1"

See the flags file for details on settings.

Base Compiler Invocation

C benchmarks:

/usr/vac/bin/xlc -qlanglvl=extc99

C++ benchmarks:

/usr/vacpp/bin/xlC

Fortran benchmarks:

/usr/bin/xlf95

Benchmarks using both Fortran and C:

/usr/vac/bin/xlc -qlanglvl=extc99 /usr/bin/xlf95

Base Portability Flags

410.bwaves: -qfixed
416.gamess: -qfixed
434.zeusmp: -qfixed
435.gromacs: -qfixed -qextname
436.cactusADM: -qfixed -qextname
437.leslie3d: -qfixed
454.calculix: -qfixed -qextname

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 602

IBM Power 570 (4.2 GHz, 32 core)

SPECfp_rate_base2006 = 517

CPU2006 license: 11

Test date: Sep-2008

Test sponsor: IBM Corporation

Hardware Availability: Nov-2008

Tested by: IBM Corporation

Software Availability: Nov-2008

Base Portability Flags (Continued)

481.wrf: -DSPEC_CPU_AIX -DNOUNDERSCORE
482.sphinx3: -qchars=signed

Base Optimization Flags

C benchmarks:

-bmaxdata:0x40000000 -O5 -qlargepage -D_ILS_MACROS -blpdata

C++ benchmarks:

-bmaxdata:0x50000000 -O5 -qlargepage -D_ILS_MACROS -qrtti=all
-D__IBM_FAST_VECTOR -D__IBM_FAST_SET_MAP_ITERATOR -blpdata

Fortran benchmarks:

-bmaxdata:0x60000000 -O5 -qlargepage -qsmallstack=dynlenonheap
-qalias=nostd -blpdata

Benchmarks using both Fortran and C:

-bmaxdata:0x60000000 -O5 -qlargepage -D_ILS_MACROS
-qsmallstack=dynlenonheap -qalias=nostd -blpdata

Base Other Flags

C benchmarks:

-qipa=threads -qipa=noobject -qsuppress=1500-036

C++ benchmarks:

-qipa=threads -qipa=noobject -qsuppress=1500-036

Fortran benchmarks:

-qipa=threads -qipa=noobject -qsuppress=1500-010 -qsuppress=cmpmsg
-qsuppress=1500-036

Benchmarks using both Fortran and C:

-qipa=threads -qipa=noobject -qsuppress=1500-010 -qsuppress=cmpmsg
-qsuppress=1500-036

Peak Compiler Invocation

C benchmarks:

/usr/vac/bin/xlc -qlanglvl=extc99

C++ benchmarks:

/usr/vacpp/bin/xlC

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 602

IBM Power 570 (4.2 GHz, 32 core)

SPECfp_rate_base2006 = 517

CPU2006 license: 11

Test date: Sep-2008

Test sponsor: IBM Corporation

Hardware Availability: Nov-2008

Tested by: IBM Corporation

Software Availability: Nov-2008

Peak Compiler Invocation (Continued)

Fortran benchmarks:

/usr/bin/xlf95

Benchmarks using both Fortran and C:

/usr/vac/bin/xlc -qlanglvl=extc99 /usr/bin/xlf95

Peak Portability Flags

410.bwaves: -qfixed
 416.gamess: -qfixed
 434.zeusmp: -qfixed
 435.gromacs: -qfixed -qextname
 436.cactusADM: -qfixed -qextname
 437.leslie3d: -qfixed
 454.calculix: -qfixed -qextname
 481.wrf: -DSPEC_CPU_AIX -DNOUNDERSCORE
 482.sphinx3: -qchars=signed

Peak Optimization Flags

C benchmarks:

433.milc: -bmaxdata:0x40000000 -O5 -qlargepage -D_ILS_MACROS
-qalign=natural -qfdpr -blpdata

470.lbm: basepeak = yes

482.sphinx3: -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qlargepage
-D_ILS_MACROS -qfdpr -blpdata

C++ benchmarks:

444.namd: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qlargepage
-D_ILS_MACROS -blpdata

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -D_ILS_MACROS
-qalign=natural -qfdpr

Fortran benchmarks:

410.bwaves: -bmaxdata:0x50000000 -O5 -qlargepage -qenablevmx -qvecnvoll
-qfdpr -qsmallstack=dynlenonheap -blpdata

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 602

IBM Power 570 (4.2 GHz, 32 core)

SPECfp_rate_base2006 = 517

CPU2006 license: 11

Test date: Sep-2008

Test sponsor: IBM Corporation

Hardware Availability: Nov-2008

Tested by: IBM Corporation

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

416.gamess: -bmaxdata:0x40000000 -qpdf1(pass 1) -qpdf2(pass 2) -O5
-qlargepage -qalias=nostd -blpdata

434.zeusmp: -bmaxdata:0x40000000 -qpdf1(pass 1) -qpdf2(pass 2) -O3
-qarch=auto -qtune=auto -qlargepage -qenablevmx -qvecnvml
-qxlf90=nosignedzero -qfdpr -blpdata

437.leslie3d: -O5 -qlargepage -qenablevmx -qvecnvml -qfdpr -blpdata

459.GemsFDTD: -O4 -qlargepage -q64 -qfdpr -blpdata

465.tonto: -bmaxdata:0x50000000 -qpdf1(pass 1) -qpdf2(pass 2) -O5
-bdatapsize:64K -bstacksize:64K -btextpsize:64K

Benchmarks using both Fortran and C:

435.gromacs: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -D_ILS_MACROS -qfdpr

436.cactusADM: -bmaxdata:0x60000000 -qpdf1(pass 1) -qpdf2(pass 2) -O2
-qarch=auto -qtune=auto -qlargepage -qenablevmx -qvecnvml
-D_ILS_MACROS -qfdpr -qnostrict -blpdata

454.calculix: -O4 -qlargepage -q64 -D_ILS_MACROS -qfdpr -blpdata

481.wrf: basepeak = yes

Peak Other Flags

C benchmarks:

-qipa=threads -qipa=noobject -qsuppress=1500-036

C++ benchmarks:

-qipa=threads -qipa=noobject -qsuppress=1500-036

Fortran benchmarks:

-qipa=threads -qipa=noobject -qsuppress=1500-010 -qsuppress=cmpmsg
-qsuppress=1500-036

Benchmarks using both Fortran and C:

-qipa=threads -qipa=noobject -qsuppress=1500-010 -qsuppress=cmpmsg
-qsuppress=1500-036

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/IBM-AIX.html>

<http://www.spec.org/cpu2006/flags/IBM-XL.20090713.html>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 602

IBM Power 570 (4.2 GHz, 32 core)

SPECfp_rate_base2006 = 517

CPU2006 license: 11

Test date: Sep-2008

Test sponsor: IBM Corporation

Hardware Availability: Nov-2008

Tested by: IBM Corporation

Software Availability: Nov-2008

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/IBM-AIX.xml>

<http://www.spec.org/cpu2006/flags/IBM-XL.20090713.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Tue Jul 22 20:29:33 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 29 October 2008.