



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**IBM Corporation**

**SPECint®\_rate2006 = Not Run**

**IBM System x3650 (Intel Xeon L5410)**

**SPECint\_rate\_base2006 = 113**

**CPU2006 license:** 11


**Test date:** Oct-2008

**Test sponsor:** IBM Corporation

**Hardware Availability:** Nov-2008

**Tested by:** IBM Corporation

**Software Availability:** Nov-2008



## Hardware

CPU Name: Intel Xeon L5410  
 CPU Characteristics: 1333MHz system bus  
 CPU MHz: 2333  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores  
 L3 Cache: None  
 Other Cache: None  
 Memory: 16 GB (8 x 2 GB DDR2-5300F ECC)  
 Disk Subsystem: 1 x 36 GB SAS, 15000 RPM  
 Other Hardware: None

## Software

Operating System: SuSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smp  
 Compiler: Intel C++ Compiler 11.0 for Linux Build 20080730 Package ID: l\_cproc\_b\_11.0.042  
 Auto Parallel: No  
 File System: ReiserFS  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32-bit  
 Peak Pointers: Not Applicable  
 Other Software: Microquill SmartHeap V8.1 Binutils 2.18.50.0.7.20080502



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

**SPECint\_rate2006 = Not Run**

IBM System x3650 (Intel Xeon L5410)

**SPECint\_rate\_base2006 = 113**

CPU2006 license: 11

Test date: Oct-2008

Test sponsor: IBM Corporation

Hardware Availability: Nov-2008

Tested by: IBM Corporation

Software Availability: Nov-2008

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	610	128	616	127	<b>612</b>	<b>128</b>							
401.bzip2	8	899	85.9	<b>886</b>	<b>87.1</b>	881	87.6							
403.gcc	8	697	92.3	<b>696</b>	<b>92.5</b>	694	92.8							
429.mcf	8	716	102	<b>716</b>	<b>102</b>	716	102							
445.gobmk	8	<b>693</b>	<b>121</b>	693	121	692	121							
456.hmmer	8	<b>619</b>	<b>121</b>	620	120	618	121							
458.sjeng	8	764	127	766	126	<b>765</b>	<b>126</b>							
462.libquantum	8	<b>850</b>	<b>195</b>	851	195	850	195							
464.h264ref	8	<b>860</b>	<b>206</b>	859	206	860	206							
471.omnetpp	8	<b>709</b>	<b>70.5</b>	709	70.5	710	70.4							
473.astar	8	<b>798</b>	<b>70.4</b>	799	70.3	797	70.4							
483.xalancbmk	8	491	113	<b>490</b>	<b>113</b>	490	113							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
taskset was used to bind processes to cores

## General Notes

Hardware Prefetch Disabled, Adjacent Sector Prefetch Disabled  
'ulimit -s unlimited' was used to set the stack size to unlimited prior to run

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32

462.libquantum: -DSPEC\_CPU\_LINUX

483.xalancbmk: -DSPEC\_CPU\_LINUX



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint\_rate2006 = Not Run

IBM System x3650 (Intel Xeon L5410)

SPECint\_rate\_base2006 = 113

CPU2006 license: 11

Test date: Oct-2008

Test sponsor: IBM Corporation

Hardware Availability: Nov-2008

Tested by: IBM Corporation

Software Availability: Nov-2008

## Base Optimization Flags

C benchmarks:

```
-xSSE4.1 -ipo -O3 -no-prec-div -static -inline-calloc  
-opt-malloc-options=3 -opt-prefetch
```

C++ benchmarks:

```
-xSSE4.1 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs  
-L/spec/cpu2006.1.1/lib -lsmartheap
```

## Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revA.20090713.11.html>  
<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090713.03.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revA.20090713.11.xml>  
<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090713.03.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 20:16:58 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 11 November 2008.