



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECint®2006 = 30.2**

Dell Precision T7400 (Intel Xeon X5492, 3.40 GHz)

**SPECint\_base2006 = 27.6**

CPU2006 license: 55


Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Nov-2008

Hardware Availability: Sep-2008

Software Availability: Nov-2008



## Hardware

CPU Name:	Intel Xeon X5492
CPU Characteristics:	1600 MHz Bus Speed
CPU MHz:	3400
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	12 MB I+D on chip per chip, 6 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8x2 GB DDR2-800 FB-DIMM, CL5)
Disk Subsystem:	1 x 80 GB SATA 7200 RPM
Other Hardware:	None

## Software

Operating System:	Windows Vista Business SP1 (64-bit)
Compiler:	Intel C++ Compiler for IA-32, Version 11.0 Build 20080930 Package ID: w_cproc_p_11.0.061 Microsoft Visual Studio 2008 SP1
Auto Parallel:	Yes
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	MicroQuill SmartHeap Library 8.1



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

Dell Precision T7400 (Intel Xeon X5492, 3.40 GHz)

**SPECint2006 = 30.2**

**SPECint\_base2006 = 27.6**

CPU2006 license: 55

Test date: Nov-2008

Test sponsor: Dell Inc.

Hardware Availability: Sep-2008

Tested by: Dell Inc.

Software Availability: Nov-2008

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	441	22.2	<b>441</b>	<b>22.2</b>	440	22.2	323	30.3	<b>323</b>	<b>30.2</b>	323	30.2
401.bzip2	507	19.0	<b>507</b>	<b>19.0</b>	507	19.0	504	19.1	504	19.2	<b>504</b>	<b>19.1</b>
403.gcc	<b>457</b>	<b>17.6</b>	456	17.6	457	17.6	383	21.0	383	21.0	<b>383</b>	<b>21.0</b>
429.mcf	297	30.8	297	30.7	<b>297</b>	<b>30.8</b>	<b>297</b>	<b>30.7</b>	297	30.7	297	30.7
445.gobmk	455	23.0	455	23.1	<b>455</b>	<b>23.1</b>	<b>427</b>	<b>24.6</b>	427	24.6	427	24.6
456.hmmer	485	19.3	485	19.2	<b>485</b>	<b>19.3</b>	399	23.4	<b>399</b>	<b>23.4</b>	399	23.4
458.sjeng	533	22.7	533	22.7	<b>533</b>	<b>22.7</b>	<b>508</b>	<b>23.8</b>	508	23.8	508	23.8
462.libquantum	<b>65.0</b>	<b>319</b>	65.7	315	64.8	320	<b>65.0</b>	<b>319</b>	65.7	315	64.8	320
464.h264ref	589	37.6	<b>589</b>	<b>37.6</b>	589	37.6	565	39.2	<b>565</b>	<b>39.2</b>	566	39.1
471.omnetpp	385	16.2	<b>386</b>	<b>16.2</b>	386	16.2	339	18.4	<b>338</b>	<b>18.5</b>	338	18.5
473.astar	400	17.6	<b>400</b>	<b>17.6</b>	400	17.5	<b>355</b>	<b>19.8</b>	354	19.8	355	19.8
483.xalancbmk	280	24.6	279	24.7	<b>280</b>	<b>24.7</b>	280	24.6	279	24.7	<b>280</b>	<b>24.7</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

Binaries were built on Windows Vista Ultimate (64-bit)

BIOS Settings

Adjacent Cache Line Prefetch set to ON

## Base Compiler Invocation

C benchmarks:

icl -Qvc9 -Qstd=c99

C++ benchmarks:

icl -Qvc9

## Base Portability Flags

403.gcc: -DSPEC\_CPU\_WIN32

464.h264ref: -DSPEC\_CPU\_NO\_INTTYPES -DWIN32

483.xalancbmk: -Qoption\_cpp, --no\_wchar\_t\_keyword



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

Dell Precision T7400 (Intel Xeon X5492, 3.40 GHz)

**SPECint2006 = 30.2**

**SPECint\_base2006 = 27.6**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Nov-2008

**Hardware Availability:** Sep-2008

**Software Availability:** Nov-2008

## Base Optimization Flags

C benchmarks:

```
-QxSSE4.1 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel  
-Qpar-runtime-control -Qvec-guard-write /F512000000
```

C++ benchmarks:

```
-QxSSE4.1 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx_features  
/F512000000 shlw32m.lib  
-link /FORCE:MULTIPLE
```

## Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

## Peak Compiler Invocation

C benchmarks:

```
icl -Qvc9 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc9
```

## Peak Portability Flags

```
403.gcc: -DSPEC_CPU_WIN32  
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32  
483.xalancbmk: -Qoption,cpp,--no_wchar_t_keyword
```

## Peak Optimization Flags

C benchmarks:

```
400.perlbench: -Qprof_gen(pass 1) -QxSSE4.1 -Qprof_use(pass 2) -Qipo -O3  
-Qprec-div- -Qansi-alias -Qopt-prefetch /F512000000  
shlw32m.lib  
-link /FORCE:MULTIPLE
```

```
401.bzip2: -Qprof_gen(pass 1) -QxSSE4.1(pass 2) -Qprof_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch  
/F512000000
```

```
403.gcc: -Qprof_gen(pass 1) -QxSSE4.1 -Qprof_use(pass 2) -Qipo -O3  
-Qprec-div- /F512000000
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECint2006 = 30.2**

Dell Precision T7400 (Intel Xeon X5492, 3.40 GHz)

**SPECint\_base2006 = 27.6**

**CPU2006 license:** 55

**Test date:** Nov-2008

**Test sponsor:** Dell Inc.

**Hardware Availability:** Sep-2008

**Tested by:** Dell Inc.

**Software Availability:** Nov-2008

## Peak Optimization Flags (Continued)

429.mcf: -QxSSE4.1 -Qipo -O3 -Qprec-div- -Qopt-prefetch  
/F512000000

445.gobmk: -Qprof\_gen(pass 1) -QxSSE4.1(pass 2) -Qprof\_use(pass 2)  
-Qipo -O2 -Qprec-div- -Qansi-alias /F512000000

456.hmmr: -QxSSE4.1 -Qipo -O3 -Qprec-div- -Qunroll12 -Qansi-alias  
/F512000000

458.sjeng: -Qprof\_gen(pass 1) -QxSSE4.1(pass 2) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qunroll14 /F512000000

462.libquantum: basepeak = yes

464.h264ref: -Qprof\_gen(pass 1) -QxSSE4.1(pass 2) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qunroll12 -Qansi-alias /F512000000

C++ benchmarks:

471.omnetpp: -Qprof\_gen(pass 1) -QxSSE4.1(pass 2) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qansi-alias  
-Qopt-ra-region-strategy=block /F5120000000 shlw32m.lib  
-link /FORCE:MULTIPLE

473.astar: -Qprof\_gen(pass 1) -QxSSE4.1(pass 2) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qansi-alias  
-Qopt-ra-region-strategy=routine /F5120000000 shlw32m.lib  
-link /FORCE:MULTIPLE

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at  
<http://www.spec.org/cpu2006/flags/dell.ic11.0.windows.flags.html>

You can also download the XML flags source by saving the following link:  
<http://www.spec.org/cpu2006/flags/dell.ic11.0.windows.flags.xml>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECint2006 = 30.2**

Dell Precision T7400 (Intel Xeon X5492, 3.40 GHz)

**SPECint\_base2006 = 27.6**

**CPU2006 license:** 55

**Test date:** Nov-2008

**Test sponsor:** Dell Inc.

**Hardware Availability:** Sep-2008

**Tested by:** Dell Inc.

**Software Availability:** Nov-2008

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 21:31:34 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 24 December 2008.