



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECint®2006 = 27.0**

Dell Precision T3400 (Intel QX9650, 3.00 GHz)

**SPECint\_base2006 = 24.6**

CPU2006 license: 55


Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Nov-2008

Hardware Availability: Jun-2008

Software Availability: Nov-2008



## Hardware

CPU Name: Intel Core 2 Extreme QX9650  
CPU Characteristics: 1333 MHz Bus Speed  
CPU MHz: 3000  
FPU: Integrated  
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
CPU(s) orderable: 1 chip  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores  
L3 Cache: None  
Other Cache: None  
Memory: 8 GB (4x2 GB DDR2-800 ECC, CL6)  
Disk Subsystem: 1 x 160 GB SATA 7200 RPM  
Other Hardware: None

## Software

Operating System: Windows Vista Ultimate (64-bit)  
Compiler: Intel C++ Compiler for IA-32, Version 11.0 Build 20080930 Package ID: w\_cproc\_p\_11.0.061 Microsoft Visual Studio 2008 SP1  
Auto Parallel: Yes  
File System: NTFS  
System State: Default  
Base Pointers: 32-bit  
Peak Pointers: 32-bit  
Other Software: MicroQuill SmartHeap Library 8.1



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECint2006 = 27.0**

Dell Precision T3400 (Intel QX9650, 3.00 GHz)

**SPECint\_base2006 = 24.6**

CPU2006 license: 55

Test date: Nov-2008

Test sponsor: Dell Inc.

Hardware Availability: Jun-2008

Tested by: Dell Inc.

Software Availability: Nov-2008

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
400.perlbench	496	19.7	497	19.7	<b>496</b>	<b>19.7</b>	361	27.1	<b>361</b>	<b>27.1</b>	361	27.1
401.bzip2	564	17.1	<b>564</b>	<b>17.1</b>	564	17.1	<b>562</b>	<b>17.2</b>	<b>563</b>	<b>17.2</b>	<b>562</b>	<b>17.2</b>
403.gcc	442	18.2	431	18.7	<b>434</b>	<b>18.6</b>	368	21.9	367	21.9	<b>368</b>	<b>21.9</b>
429.mcf	288	31.7	288	31.7	<b>288</b>	<b>31.7</b>	<b>289</b>	<b>31.6</b>	289	31.6	288	31.6
445.gobmk	522	20.1	522	20.1	<b>522</b>	<b>20.1</b>	478	21.9	<b>478</b>	<b>21.9</b>	478	21.9
456.hmmer	<b>550</b>	<b>17.0</b>	549	17.0	550	17.0	451	20.7	450	20.7	<b>451</b>	<b>20.7</b>
458.sjeng	591	20.5	<b>591</b>	<b>20.5</b>	591	20.5	564	21.5	564	21.5	<b>564</b>	<b>21.5</b>
462.libquantum	<b>128</b>	<b>162</b>	127	163	128	162	<b>128</b>	<b>162</b>	127	163	128	162
464.h264ref	662	33.5	662	33.4	<b>662</b>	<b>33.4</b>	637	34.7	<b>637</b>	<b>34.7</b>	637	34.7
471.omnetpp	352	17.7	353	17.7	<b>353</b>	<b>17.7</b>	305	20.5	<b>305</b>	<b>20.5</b>	305	20.5
473.astar	438	16.0	<b>438</b>	<b>16.0</b>	438	16.0	386	18.2	<b>386</b>	<b>18.2</b>	387	18.2
483.xalancbmk	<b>297</b>	<b>23.2</b>	297	23.3	297	23.2	<b>297</b>	<b>23.2</b>	<b>297</b>	<b>23.3</b>	297	23.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

Binaries were built on Windows Vista Ultimate (64-bit)

## Base Compiler Invocation

C benchmarks:

icl -Qvc9 -Qstd=c99

C++ benchmarks:

icl -Qvc9

## Base Portability Flags

403.gcc: -DSPEC\_CPU\_WIN32

464.h264ref: -DSPEC\_CPU\_NO\_INTTYPES -DWIN32

483.xalancbmk: -Qoption,cpp,--no\_wchar\_t\_keyword

## Base Optimization Flags

C benchmarks:

-QxSSE4.1 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel  
-Qpar-runtime-control -Qvec-guard-write /F512000000

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECint2006 = 27.0**

Dell Precision T3400 (Intel QX9650, 3.00 GHz)

**SPECint\_base2006 = 24.6**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Nov-2008

**Hardware Availability:** Jun-2008

**Software Availability:** Nov-2008

## Base Optimization Flags (Continued)

C++ benchmarks:

```
-QxSSE4.1 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx_features  
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE
```

## Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

## Peak Compiler Invocation

C benchmarks:

```
icl -Qvc9 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc9
```

## Peak Portability Flags

```
403.gcc: -DSPEC_CPU_WIN32
```

```
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
```

```
483.xalancbmk: -Qoption,cpp,--no_wchar_t_keyword
```

## Peak Optimization Flags

C benchmarks:

```
400.perlbench: -Qprof_gen(pass 1) -QxSSE4.1 -Qprof_use(pass 2) -Qipo -O3  
-Qprec-div- -Qansi-alias -Qopt-prefetch /F512000000  
shlw32m.lib -link /FORCE:MULTIPLE
```

```
401.bzip2: -Qprof_gen(pass 1) -QxSSE4.1(pass 2) -Qprof_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch  
/F512000000
```

```
403.gcc: -Qprof_gen(pass 1) -QxSSE4.1 -Qprof_use(pass 2) -Qipo -O3  
-Qprec-div- /F512000000
```

```
429.mcf: -QxSSE4.1 -Qipo -O3 -Qprec-div- -Qopt-prefetch  
/F512000000
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECint2006 = 27.0**

Dell Precision T3400 (Intel QX9650, 3.00 GHz)

**SPECint\_base2006 = 24.6**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Nov-2008

**Hardware Availability:** Jun-2008

**Software Availability:** Nov-2008

## Peak Optimization Flags (Continued)

445.gobmk: -Qprof\_gen(pass 1) -QxSSE4.1(pass 2) -Qprof\_use(pass 2)  
-Qipo -O2 -Qprec-div- -Qansi-alias /F512000000

456.hmmr: -QxSSE4.1 -Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias  
/F512000000

458.sjeng: -Qprof\_gen(pass 1) -QxSSE4.1(pass 2) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qunroll4 /F512000000

462.libquantum: basepeak = yes

464.h264ref: -Qprof\_gen(pass 1) -QxSSE4.1(pass 2) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias /F512000000

C++ benchmarks:

471.omnetpp: -Qprof\_gen(pass 1) -QxSSE4.1(pass 2) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qansi-alias  
-Qopt-ra-region-strategy=block /F512000000 shlw32m.lib  
-link /FORCE:MULTIPLE

473.astar: -Qprof\_gen(pass 1) -QxSSE4.1(pass 2) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qansi-alias  
-Qopt-ra-region-strategy=routine /F512000000 shlw32m.lib  
-link /FORCE:MULTIPLE

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at  
<http://www.spec.org/cpu2006/flags/dell.ic11.0.windows.flags.html>

You can also download the XML flags source by saving the following link:  
<http://www.spec.org/cpu2006/flags/dell.ic11.0.windows.flags.xml>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECint2006 = 27.0**

Dell Precision T3400 (Intel QX9650, 3.00 GHz)

**SPECint\_base2006 = 24.6**

**CPU2006 license:** 55

**Test date:** Nov-2008

**Test sponsor:** Dell Inc.

**Hardware Availability:** Jun-2008

**Tested by:** Dell Inc.

**Software Availability:** Nov-2008

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 21:42:19 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 24 December 2008.