



SPEC[®] CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/320Fd-MR
(Intel Xeon E5450)

SPECint[®]_rate2006 = 131

SPECint_rate_base2006 = 112

CPU2006 license: 9006


Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Nov-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008



Hardware

CPU Name: Intel Xeon E5450
 CPU Characteristics: 1333 MHz system bus
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips (fault tolerant, see Platform Notes)
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 24 GB (6x4 GB PC2-5300F, 2 rank, CL5-5-5, ECC)
 Disk Subsystem: 2x146.5 GB SAS, 15000 RPM, Software RAID Level1
 Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux Server release 5.2
 Advanced Platform, Kernel 2.6.18-92.1.13.el5 on an x86_64
 Compiler: Intel C++ Compiler 11.0 for Linux
 Build 20081105 Package ID: l_cproc_p_11.0.074
 Auto Parallel: Yes
 File System: ext3
 System State: Run level 3 (multi-user)
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap Library 8.1
 ft Server Control Software 6.0.2-198



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/320Fd-MR
(Intel Xeon E5450)

SPECint_rate2006 = 131

SPECint_rate_base2006 = 112

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Nov-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	491	159	491	159	489	160	8	427	183	426	183	425	184
401.bzip2	8	738	105	741	104	740	104	8	713	108	711	109	712	108
403.gcc	8	693	92.9	690	93.3	693	92.9	8	690	93.3	702	91.7	690	93.4
429.mcf	8	791	92.2	784	93.0	788	92.6	8	791	92.2	784	93.0	788	92.6
445.gobmk	8	569	148	569	147	570	147	8	540	155	538	156	537	156
456.hammer	8	489	153	489	153	491	152	8	390	191	390	191	390	191
458.sjeng	8	627	154	627	154	629	154	8	598	162	600	161	598	162
462.libquantum	8	1970	84.2	1948	85.1	1943	85.3	1	78.7	263	76.8	270	77.6	267
464.h264ref	8	678	261	678	261	676	262	8	644	275	644	275	644	275
471.omnetpp	8	942	53.1	938	53.3	936	53.4	8	933	53.6	936	53.4	934	53.6
473.astar	8	891	63.0	887	63.3	886	63.4	8	819	68.6	823	68.3	821	68.4
483.xalancbmk	8	501	110	502	110	502	110	8	501	110	502	110	502	110

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
taskset was used to bind processes to cores except
for 462.libquantum peak

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to "physical,0"
KMP_STACKSIZE set to 64M

Platform Notes

This Express5800/320Fd-MR is a fault-tolerant server.
Two modules are installed in this server.
Each module physically has "2CPU chips,24GB memory", The total physical configuration is "4CPU chips,48GB memory".
Using fault-tolerant lockstep technology, these two modules communicate with each other and execute the same instructions at the same time, The operating system only sees "2CPU chips,24GB memory" as the other components add only redundancy and do not contribute to any performance benefit.



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/320Fd-MR
(Intel Xeon E5450)

SPECint_rate2006 = 131

SPECint_rate_base2006 = 112

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Nov-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008

General Notes

The NEC Express5800/320Fd-MR(Intel Xeon E5450) and the Bull NovaScale R630 E1 MR(Intel Xeon E5450, 3.00 GHz) models are electronically equivalent. The results have been measured on a NEC Express5800/320Fd-MR(Intel Xeon E5450) model.

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -static -inline-calloc
-opt-malloc-options=3 -opt-prefetch

C++ benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
-L/opt/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/Compiler/11.0/074/bin/intel64/icc
-L/opt/intel/Compiler/11.0/074/ipp/em64t/lib
-I/opt/intel/Compiler/11.0/074/ipp/em64t/include

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/320Fd-MR
(Intel Xeon E5450)

SPECint_rate2006 = 131

SPECint_rate_base2006 = 112

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Nov-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008

Peak Compiler Invocation (Continued)

```
456.hmmer: /opt/intel/Compiler/11.0/074/bin/intel64/icc
           -L/opt/intel/Compiler/11.0/074/ipp/em64t/lib
           -I/opt/intel/Compiler/11.0/074/ipp/em64t/include
```

C++ benchmarks:
icpc

Peak Portability Flags

```
400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
              -no-prec-div -static -ansi-alias -opt-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
           -no-prec-div -static -opt-prefetch -ansi-alias

403.gcc: -xSSE4.1 -ipo -O3 -no-prec-div -static -inline-calloc
         -opt-malloc-options=3

429.mcf: basepeak = yes

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -O2 -ipo
           -no-prec-div -ansi-alias

456.hmmer: -xSSE4.1 -ipo -O3 -no-prec-div -static -unroll2
           -ansi-alias

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
           -no-prec-div -static -unroll4

462.libquantum: -xSSE4.1 -ipo -O3 -no-prec-div -static
               -opt-malloc-options=3 -parallel -par-runtime-control
               -opt-prefetch

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
             -no-prec-div -static -unroll2 -ansi-alias
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/320Fd-MR
(Intel Xeon E5450)

SPECint_rate2006 = 131

SPECint_rate_base2006 = 112

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Nov-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs -L/opt/SmartHeap_8.1/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs -L/opt/SmartHeap_8.1/lib -lsmartheap

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revD.20090713.html>

<http://www.spec.org/cpu2006/flags/NEC-Intel-Linux-Settings-flags-revB.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revD.20090713.xml>

<http://www.spec.org/cpu2006/flags/NEC-Intel-Linux-Settings-flags-revB.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 21:41:02 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 24 December 2008.