



SPEC[®] CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T860 E1
(Intel Xeon X5470, 3.33 GHz)

SPECint[®]_rate2006 = 144

SPECint_rate_base2006 = 130

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Nov-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008



Hardware

CPU Name: Intel Xeon X5470
 CPU Characteristics: 3.33 GHz, 2x6 MB L2 shared, 1333 MHz system bus
 CPU MHz: 3333
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8x2 GB PC2-5300F, 2 rank, CL5-5-5, ECC)
 Disk Subsystem: 1x73.2 GB SAS, 15000RPM
 Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP2, Kernel 2.6.16.60-0.21-smp
 Compiler: Intel C++ Compiler 11.0 for Linux Build 20080730 Package ID: l_cproc_b_11.0.044
 Auto Parallel: Yes
 File System: ext2
 System State: Run level 3 (multi-user)
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap Library 8.1 Binutils 2.18.50.0.7.20080502



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T860 E1
(Intel Xeon X5470, 3.33 GHz)

SPECint_rate2006 = 144

SPECint_rate_base2006 = 130

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: NEC Corporation

Test date: Nov-2008
Hardware Availability: Oct-2008
Software Availability: Nov-2008

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	445	176	443	176	444	176	8	387	202	386	203	389	201
401.bzip2	8	640	121	657	117	653	118	8	631	122	627	123	624	124
403.gcc	8	695	92.6	696	92.6	699	92.2	8	704	91.5	708	90.9	701	91.9
429.mcf	8	732	99.7	732	99.6	732	99.6	8	727	100	727	100	727	100
445.gobmk	8	499	168	501	168	499	168	8	468	179	468	179	471	178
456.hammer	8	424	176	424	176	424	176	8	333	224	333	224	334	224
458.sjeng	8	568	171	569	170	569	170	8	546	177	546	177	546	177
462.libquantum	8	992	167	991	167	992	167	1	72.2	287	72.3	287	72.2	287
464.h264ref	8	603	293	603	294	602	294	8	577	307	578	306	578	306
471.omnetpp	8	1004	49.8	1004	49.8	1004	49.8	8	981	51.0	982	50.9	981	50.9
473.astar	8	694	81.0	707	79.4	708	79.3	8	645	87.0	647	86.8	646	86.9
483.xalancbmk	8	437	126	439	126	439	126	8	437	126	439	126	439	126

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
taskset was used to bind processes to cores except
for 462.libquantum peak

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to "physical,0"
KMP_STACKSIZE set to 64M

Platform Notes

Bios settings:
Hardware Prefetcher: Enabled
Adjacent Cache Line Prefetch: Disabled

General Notes

The NEC Express5800/120Lj(Intel Xeon X5470) and
the Bull NovaScale T860 E1(Intel Xeon X5470, 3.33 GHz) models are electronically equivalent.
The results have been measured on a NEC Express5800/120Lj(Intel Xeon X5470) model.



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T860 E1
(Intel Xeon X5470, 3.33 GHz)

SPECint_rate2006 = 144

SPECint_rate_base2006 = 130

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: NEC Corporation

Test date: Nov-2008
Hardware Availability: Oct-2008
Software Availability: Nov-2008

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-xSSE4.1 -ipo -O3 -no-prec-div -static -inline-alloc
-opt-malloc-options=3 -opt-prefetch

C++ benchmarks:
-xSSE4.1 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
-L/opt/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc

401.bzip2: /opt/intel/Compiler/11.0/044/bin/intel64/icc
-L/opt/intel/Compiler/11.0/044/ipp/em64t/lib
-I/opt/intel/Compiler/11.0/044/ipp/em64t/include

456.hmmer: /opt/intel/Compiler/11.0/044/bin/intel64/icc
-L/opt/intel/Compiler/11.0/044/ipp/em64t/lib
-I/opt/intel/Compiler/11.0/044/ipp/em64t/include

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T860 E1
(Intel Xeon X5470, 3.33 GHz)

SPECint_rate2006 = 144

SPECint_rate_base2006 = 130

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: NEC Corporation

Test date: Nov-2008
Hardware Availability: Oct-2008
Software Availability: Nov-2008

Peak Compiler Invocation (Continued)

C++ benchmarks:
icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -ansi-alias -opt-prefetch
401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -opt-prefetch -ansi-alias
403.gcc: -xSSE4.1 -ipo -O3 -no-prec-div -static -inline-alloc
-opt-malloc-options=3
429.mcf: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -opt-prefetch
445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -O2 -ipo
-no-prec-div -ansi-alias
456.hmmer: -xSSE4.1 -ipo -O3 -no-prec-div -static -unroll2
-ansi-alias
458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll4
462.libquantum: -xSSE4.1 -ipo -O3 -no-prec-div -static
-opt-malloc-options=3 -parallel -par-runtime-control
-opt-prefetch
464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -ansi-alias

C++ benchmarks:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T860 E1
(Intel Xeon X5470, 3.33 GHz)

SPECint_rate2006 = 144

SPECint_rate_base2006 = 130

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Nov-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs -L/opt/SmartHeap_8.1/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs -L/opt/SmartHeap_8.1/lib -lsmartheap

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revD.20090713.html>

<http://www.spec.org/cpu2006/flags/NEC-Intel-Linux-Settings-flags-revB.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revD.20090713.xml>

<http://www.spec.org/cpu2006/flags/NEC-Intel-Linux-Settings-flags-revB.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Tue Jul 22 22:57:30 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 6 January 2009.