



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Sun Microsystems**

Sun Fire X2270 (Intel Xeon E5540 2.53GHz)

**SPECfp®\_rate2006 = 163**

CPU2006 license: 6


Test date: Aug-2009

Hardware Availability: Apr-2009

Software Availability: Nov-2008

Test sponsor: Sun Microsystems

Tested by: Sun Microsystems



## Hardware

CPU Name: Intel Xeon E5540  
CPU Characteristics: Intel Turbo Boost Technology up to 2.80 GHz  
CPU MHz: 2534  
FPU: Integrated  
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip, 2 threads/core  
CPU(s) orderable: 1 or 2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core

## Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP2, Kernel 2.6.16.60-0.21-smp  
Compiler: Intel C++ and Fortran Compiler 11.0 for Linux Build 20080930 Package ID: l\_cproc\_p\_11.0.066, l\_cprof\_p\_11.0.066  
Auto Parallel: No  
File System: ReiserFS  
System State: Run level 3 (multi-user)  
Base Pointers: 64-bit

Continued on next page

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Sun Microsystems

Sun Fire X2270 (Intel Xeon E5540 2.53GHz)

**SPECfp\_rate2006 = 163**

CPU2006 license: 6

Test date: Aug-2009

Test sponsor: Sun Microsystems

Hardware Availability: Apr-2009

Tested by: Sun Microsystems

Software Availability: Nov-2008

L3 Cache: 8 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 24 GB (6 x 4 GB DDR3-1333 downclocked to 1066 MHz)  
 Disk Subsystem: 1 x 1 TB, SATA, 7200 RPM  
 Other Hardware: None

Peak Pointers: 32/64-bit  
 Other Software: Binutils 2.18

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	16	1569	139	1389	157	<b>1390</b>	<b>156</b>	8	687	158	<b>684</b>	<b>159</b>	679	160
416.gamess	16	1732	181	<b>1738</b>	<b>180</b>	1757	178	16	<b>1720</b>	<b>182</b>	1718	182	1757	178
433.milc	16	1017	144	<b>982</b>	<b>149</b>	980	150	16	982	150	1208	122	<b>1061</b>	<b>138</b>
434.zeusmp	16	812	179	822	177	<b>814</b>	<b>179</b>	16	830	176	834	175	<b>833</b>	<b>175</b>
435.gromacs	16	<b>669</b>	<b>171</b>	663	172	670	171	16	644	177	<b>645</b>	<b>177</b>	647	176
436.cactusADM	16	974	196	969	197	<b>974</b>	<b>196</b>	16	<b>1018</b>	<b>188</b>	1012	189	1024	187
437.leslie3d	16	<b>1334</b>	<b>113</b>	1340	112	1331	113	16	<b>1351</b>	<b>111</b>	1357	111	1346	112
444.namd	16	<b>803</b>	<b>160</b>	807	159	802	160	16	790	162	<b>790</b>	<b>162</b>	792	162
447.dealII	16	766	239	<b>751</b>	<b>244</b>	746	245	16	<b>695</b>	<b>263</b>	710	258	692	264
450.soplex	16	1146	116	<b>1107</b>	<b>121</b>	1099	121	8	693	96.3	<b>564</b>	<b>118</b>	523	128
453.povray	16	359	237	360	236	<b>360</b>	<b>236</b>	16	<b>302</b>	<b>282</b>	302	282	301	283
454.calculix	16	647	204	<b>648</b>	<b>204</b>	648	204	16	647	204	647	204	<b>647</b>	<b>204</b>
459.GemsFDTD	16	1780	95.4	<b>1703</b>	<b>99.7</b>	1699	99.9	16	1781	95.3	<b>1914</b>	<b>88.7</b>	1923	88.3
465.tonto	16	868	181	898	175	<b>897</b>	<b>175</b>	16	820	192	839	188	<b>835</b>	<b>189</b>
470.lbm	16	2287	96.1	2175	101	<b>2176</b>	<b>101</b>	8	1161	94.7	1011	109	<b>1011</b>	<b>109</b>
481.wrf	16	956	187	<b>946</b>	<b>189</b>	943	189	16	956	187	<b>946</b>	<b>189</b>	943	189
482.sphinx3	16	2611	119	1930	162	<b>2014</b>	<b>155</b>	16	2323	134	<b>2003</b>	<b>156</b>	1866	167

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
 numactl was used to bind copies to the cores.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

## Platform Notes

Default BIOS settings used.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Sun Microsystems

Sun Fire X2270 (Intel Xeon E5540 2.53GHz)

**SPECfp\_rate2006 = 163**

**CPU2006 license:** 6

**Test date:** Aug-2009

**Test sponsor:** Sun Microsystems

**Hardware Availability:** Apr-2009

**Tested by:** Sun Microsystems

**Software Availability:** Nov-2008

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

Fortran benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Sun Microsystems

Sun Fire X2270 (Intel Xeon E5540 2.53GHz)

**SPECfp\_rate2006 = 163**

CPU2006 license: 6

Test date: Aug-2009

Test sponsor: Sun Microsystems

Hardware Availability: Apr-2009

Tested by: Sun Microsystems

Software Availability: Nov-2008

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc

450.soplex: icpc -m32

Fortran benchmarks (except as noted below):

ifort

437.leslie3d: ifort -m32

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

433.milc: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-fno-alias

470.lbm: -xsse4.2 -ipo -O3 -no-prec-div -static -opt-prefetch  
-auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Sun Microsystems**

Sun Fire X2270 (Intel Xeon E5540 2.53GHz)

**SPECfp\_rate2006 = 163**

**CPU2006 license:** 6

**Test sponsor:** Sun Microsystems

**Tested by:** Sun Microsystems

**Test date:** Aug-2009

**Hardware Availability:** Apr-2009

**Software Availability:** Nov-2008

## Peak Optimization Flags (Continued)

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-fno-alias -auto-ilp32

447.dealII: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -ansi-alias -scalar-rep-

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-malloc-options=3

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)

437.leslie3d: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-malloc-options=3 -opt-prefetch

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -Ob0 -opt-prefetch

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Sun Microsystems**

Sun Fire X2270 (Intel Xeon E5540 2.53GHz)

**SPECfp\_rate2006 = 163**

**CPU2006 license:** 6

**Test date:** Aug-2009

**Test sponsor:** Sun Microsystems

**Hardware Availability:** Apr-2009

**Tested by:** Sun Microsystems

**Software Availability:** Nov-2008

## Peak Optimization Flags (Continued)

436.cactusADM: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -opt-prefetch -auto-ilp32

454.calculix: -xsse4.2 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090915.00.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090915.00.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 02:59:42 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 29 September 2009.