



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## Oracle Corporation

SPECfp<sup>®</sup>\_rate2006 = 573

Sun Fire X4470 (Intel Xeon X7560 2.26GHz)

SPECfp\_rate\_base2006 = 547

CPU2006 license: 6


Test sponsor: Oracle Corporation

Tested by: Oracle Corporation

Test date: May-2010

Hardware Availability: Aug-2010

Software Availability: Jun-2010



### Hardware

CPU Name: Intel Xeon X7560  
 CPU Characteristics: Intel Turbo Boost Technology up to 2.67 GHz  
 CPU MHz: 2266  
 FPU: Integrated  
 CPU(s) enabled: 32 cores, 4 chips, 8 cores/chip, 2 threads/core  
 CPU(s) orderable: 2,4 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: Oracle Solaris 10 10/09  
 Compiler: Oracle Solaris Studio Express 6/10  
 Auto Parallel: Yes  
 File System: zfs  
 System State: Default  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Apache C++ Standard Library V4.2.1



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## Oracle Corporation

SPECfp\_rate2006 = **573**

Sun Fire X4470 (Intel Xeon X7560 2.26GHz)

SPECfp\_rate\_base2006 = **547**

CPU2006 license: 6

Test date: May-2010

Test sponsor: Oracle Corporation

Hardware Availability: Aug-2010

Tested by: Oracle Corporation

Software Availability: Jun-2010

L3 Cache: 24 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 256 GB (64x4GB, DDR3-1066 CL7 dual-rank ECC Reg)  
 Disk Subsystem: 1 x 500 GB, SATA, 7200 RPM  
 Other Hardware: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	64	1769	492	<b><u>1762</u></b>	<b><u>494</u></b>	1759	494	32	851	511	851	511	<b><u>851</u></b>	<b><u>511</u></b>
416.gamess	64	2136	587	2088	600	<b><u>2135</u></b>	<b><u>587</u></b>	64	2062	608	1991	629	<b><u>2061</u></b>	<b><u>608</u></b>
433.milc	64	<b><u>1313</u></b>	<b><u>447</u></b>	1313	447	1313	448	64	1313	448	<b><u>1313</u></b>	<b><u>448</u></b>	1312	448
434.zeusmp	64	<b><u>793</u></b>	<b><u>735</u></b>	791	736	794	734	64	780	747	779	748	<b><u>779</u></b>	<b><u>748</u></b>
435.gromacs	64	789	580	<b><u>792</u></b>	<b><u>577</u></b>	794	575	64	746	612	751	608	<b><u>748</u></b>	<b><u>611</u></b>
436.cactusADM	64	1355	565	1355	564	<b><u>1355</u></b>	<b><u>564</u></b>	64	1356	564	<b><u>1356</u></b>	<b><u>564</u></b>	1356	564
437.leslie3d	64	1659	363	<b><u>1662</u></b>	<b><u>362</u></b>	1666	361	64	1659	363	<b><u>1662</u></b>	<b><u>362</u></b>	1666	361
444.namd	64	<b><u>918</u></b>	<b><u>559</u></b>	932	551	918	559	64	<b><u>918</u></b>	<b><u>559</u></b>	932	551	918	559
447.dealII	64	656	1120	<b><u>656</u></b>	<b><u>1120</u></b>	656	1120	64	656	1120	<b><u>656</u></b>	<b><u>1120</u></b>	656	1120
450.soplex	64	1360	393	<b><u>1355</u></b>	<b><u>394</u></b>	1353	395	64	1266	422	1237	432	<b><u>1237</u></b>	<b><u>432</u></b>
453.povray	64	426	798	426	799	<b><u>426</u></b>	<b><u>799</u></b>	64	368	925	366	931	<b><u>367</u></b>	<b><u>928</u></b>
454.calculix	64	636	831	634	833	<b><u>635</u></b>	<b><u>832</u></b>	64	631	837	<b><u>630</u></b>	<b><u>839</u></b>	630	839
459.GemsFDTD	64	2102	323	2105	323	<b><u>2104</u></b>	<b><u>323</u></b>	32	<b><u>979</u></b>	<b><u>347</u></b>	980	347	978	347
465.tonto	64	971	648	<b><u>973</u></b>	<b><u>647</u></b>	978	644	64	<b><u>922</u></b>	<b><u>683</u></b>	930	677	921	684
470.lbm	64	3123	282	3123	282	<b><u>3123</u></b>	<b><u>282</u></b>	1	38.8	354	38.9	353	<b><u>38.9</u></b>	<b><u>354</u></b>
481.wrf	64	1209	591	1189	601	<b><u>1193</u></b>	<b><u>599</u></b>	64	<b><u>1189</u></b>	<b><u>601</u></b>	1187	602	1202	595
482.sphinx3	64	<b><u>2279</u></b>	<b><u>547</u></b>	2238	557	2298	543	64	<b><u>2217</u></b>	<b><u>563</u></b>	2199	567	2226	560

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

The Apache C++ Standard Library V4.2.1 was installed from  
<http://stdcxx.apache.org/download.html> using:  
 alias gmake=specmake  
 gmake BUILDTYPE=8D CONFIG=sunpro.config

## Submit Notes

The config file option 'submit' was used.



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Oracle Corporation

SPECfp\_rate2006 = 573

Sun Fire X4470 (Intel Xeon X7560 2.26GHz)

SPECfp\_rate\_base2006 = 547

CPU2006 license: 6

Test sponsor: Oracle Corporation

Tested by: Oracle Corporation

Test date: May-2010

Hardware Availability: Aug-2010

Software Availability: Jun-2010

## Operating System Notes

```
ulimit -s unlimited (shell)

/etc/system parameters
tune_t_fsflushr=10
autoup=900
zfs:zfs_arc_max = 0x10000000
lpg_alloc_prefer=1
```

## Platform Notes

Default BIOS settings used.

## General Notes

Environment variables set by runspec before the start of the run:

SUNW\_MP\_PROCBIND = "TRUE"

SUNW\_MP\_THR\_IDLE = "SPIN"

447.dealIII (peak): "apache\_stdccx4\_2\_1" src.alt was used.

447.dealIII (base): "apache\_stdccx4\_2\_1" src.alt was used.

## Base Compiler Invocation

C benchmarks:

cc

C++ benchmarks:

CC

Fortran benchmarks:

f90

Benchmarks using both Fortran and C:

cc f90

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64

416.gamess: -DSPEC\_CPU\_LP64

433.milc: -DSPEC\_CPU\_LP64

434.zeusmp: -DSPEC\_CPU\_LP64

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 3



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Oracle Corporation

SPECfp\_rate2006 = 573

Sun Fire X4470 (Intel Xeon X7560 2.26GHz)

SPECfp\_rate\_base2006 = 547

CPU2006 license: 6

Test date: May-2010

Test sponsor: Oracle Corporation

Hardware Availability: Aug-2010

Tested by: Oracle Corporation

Software Availability: Jun-2010

## Base Portability Flags (Continued)

```

435.gromacs: -DSPEC_CPU_LP64
436.cactusADM: -DSPEC_CPU_LP64
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_WORDS_LITTLEENDIAN
482.sphinx3: -DSPEC_CPU_LP64

```

## Base Optimization Flags

C benchmarks:

-fast -xipo=2 -m64 -xpagesize=2M -xalias\_level=std

C++ benchmarks:

```

-fast -xipo=2 -m64 -xpagesize=2M -xalias_level=compatible
-library=no%Cstd -I/data1/stdcxx-4.2.1/include
-I/data1/stdcxx-4.2.1/build/include -L/data1/stdcxx-4.2.1/build/lib
-R/data1/stdcxx-4.2.1/build/lib -lstd8D

```

Fortran benchmarks:

-fast -xipo=2 -m64 -xpagesize=2M

Benchmarks using both Fortran and C:

-fast(cc) -xipo=2 -m64 -xpagesize=2M -xalias\_level=std -fast(f90)

## Base Other Flags

C benchmarks:

-V -# -xjobs=64

C++ benchmarks:

-verbose=diags,version -xjobs=64

Fortran benchmarks:

-V -v -xjobs=64

Benchmarks using both Fortran and C:

-V -# -xjobs=64 -v



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Oracle Corporation

SPECfp\_rate2006 = 573

Sun Fire X4470 (Intel Xeon X7560 2.26GHz)

SPECfp\_rate\_base2006 = 547

CPU2006 license: 6

Test date: May-2010

Test sponsor: Oracle Corporation

Hardware Availability: Aug-2010

Tested by: Oracle Corporation

Software Availability: Jun-2010

## Peak Compiler Invocation

C benchmarks:

cc

C++ benchmarks:

CC

Fortran benchmarks:

f90

Benchmarks using both Fortran and C:

cc f90

## Peak Portability Flags

436.cactusADM: -DSPEC\_CPU\_LP64  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_WORDS\_LITTLEENDIAN

## Peak Optimization Flags

C benchmarks:

433.milc: -fast -xipo=2 -m64 -xpagesize=2M -xalias\_level=std

470.lbm: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64  
-xpagesize=2M -xautopar -xreduction  
-W2,-Aparallel:nthreads=64

482.sphinx3: -fast -xipo=2 -m64 -xpagesize=2M -xalias\_level=std  
-xunroll=3 -xprefetch=no%auto

C++ benchmarks:

444.namd: basepeak = yes

447.dealII: basepeak = yes

450.soplex: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xipo=2  
-xpagesize=2M -xalias\_level=compatible -library=stlport4  
-m32 -qoption iropt -Rujam -qoption iropt -Rtile

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Oracle Corporation

SPECfp\_rate2006 = 573

Sun Fire X4470 (Intel Xeon X7560 2.26GHz)

SPECfp\_rate\_base2006 = 547

CPU2006 license: 6

Test date: May-2010

Test sponsor: Oracle Corporation

Hardware Availability: Aug-2010

Tested by: Oracle Corporation

Software Availability: Jun-2010

## Peak Optimization Flags (Continued)

453.povray: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64  
-xpagesize=2M -xvector=no%simd -xalias\_level=compatible  
-library=stlport4

Fortran benchmarks:

410.bwaves: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64  
-xpagesize=2M

416.gamess: -fast -xipo=2 -m64 -xpagesize=2M -xunroll=1  
-xvector=no%simd

434.zeusmp: Same as 410.bwaves

437.leslie3d: basepeak = yes

459.GemsFDTD: Same as 410.bwaves

465.tonto: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64  
-xvector=lib -xalias -lbsdmalloc

Benchmarks using both Fortran and C:

435.gromacs: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast(cc) -fast(f90)  
-xipo=2 -m64 -xpagesize=2M -Qoption ube -fsimple=3

436.cactusADM: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -m64 -fast(cc) -fast(f90)  
-xipo=0 -xpagesize=2M -xprefetch\_level=2 -lumem

454.calculix: -fast(cc) -fast(f90) -xipo=2 -m64 -xpagesize=2M  
-xunroll=3 -xprefetch\_level=2  
-xprefetch\_auto\_type=indirect\_array\_access

481.wrf: -fast(cc) -fast(f90) -xipo=2 -m64 -xpagesize=2M

## Peak Other Flags

C benchmarks:

-V -# -xjobs=64

C++ benchmarks:

-verbose=diags,version -xjobs=64

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Oracle Corporation

SPECfp\_rate2006 = 573

Sun Fire X4470 (Intel Xeon X7560 2.26GHz)

SPECfp\_rate\_base2006 = 547

CPU2006 license: 6

Test sponsor: Oracle Corporation

Tested by: Oracle Corporation

Test date: May-2010

Hardware Availability: Aug-2010

Software Availability: Jun-2010

## Peak Other Flags (Continued)

Fortran benchmarks:

-V -v -xjobs=64

Benchmarks using both Fortran and C:

-V -# -xjobs=64 -v

The flags file that was used to format this result can be browsed at

[http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio-x86\\_64.html](http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio-x86_64.html)

You can also download the XML flags source by saving the following link:

[http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio-x86\\_64.xml](http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio-x86_64.xml)

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Sep 13 11:40:27 2016 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 8 July 2010.