



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cryo Performance Computing Ltd  
Cryo Octane EDP-WS

SPECfp®\_rate2006 = 308

SPECfp\_rate\_base2006 = 297

CPU2006 license: 3979


Test sponsor: Cryo Performance Computing Ltd

Tested by: Cryo Performance Computing Ltd

Test date: Mar-2011

Hardware Availability: Dec-2010

Software Availability: Dec-2010



## Hardware

CPU Name: Intel Xeon X5680  
 CPU Characteristics: Intel Turbo Boost Technology disabled  
 CPU MHz: 4500  
 FPU: Integrated  
 CPU(s) enabled: 12 cores, 2 chips, 6 cores/chip, 2 threads/core  
 CPU(s) orderable: 2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

## Software

Operating System: SUSE Linux Enterprise Server 11 (x86\_64) SP1, Kernel 2.6.32.12-0.7-default  
 Compiler: Intel C++ and Fortran Professional Compiler for IA32 and Intel 64, Version 12, Build 12.0.2.137, Package ID: L\_ccomp\_xe\_2011.2.137, L\_fcpxe\_2011.2.137  
 Auto Parallel: No  
 File System: ext3  
 System State: Run level 3 (multi-user)

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cryo Performance Computing Ltd  
Cryo Octane EDP-WS

SPECfp\_rate2006 = 308

SPECfp\_rate\_base2006 = 297

CPU2006 license: 3979

Test sponsor: Cryo Performance Computing Ltd

Tested by: Cryo Performance Computing Ltd

Test date: Mar-2011

Hardware Availability: Dec-2010

Software Availability: Dec-2010

L3 Cache: 12 MB I+D on chip per chip  
Other Cache: None  
Memory: 24 GB (6 x 4 GB 2Rx4 PC3-12800U-9, running at 1440 MHz and CL8)  
Disk Subsystem: 1 x 120 GB Corsair Force Series SSD  
Other Hardware: None

Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	24	1918	170	<b>1577</b>	<b>207</b>	1567	208	24	1918	170	<b>1577</b>	<b>207</b>	1567	208
416.gamess	24	<b>1039</b>	<b>452</b>	1033	455	1047	449	24	<b>1039</b>	<b>452</b>	1033	455	1047	449
433.milc	24	1231	179	<b>1238</b>	<b>178</b>	1244	177	24	1237	178	1117	197	<b>1126</b>	<b>196</b>
434.zeusmp	24	607	360	<b>626</b>	<b>349</b>	626	349	24	607	360	<b>626</b>	<b>349</b>	626	349
435.gromacs	24	407	421	410	418	<b>410</b>	<b>418</b>	24	<b>409</b>	<b>419</b>	410	418	409	419
436.cactusADM	24	771	372	<b>783</b>	<b>366</b>	792	362	24	771	372	<b>783</b>	<b>366</b>	792	362
437.leslie3d	24	1458	155	<b>1459</b>	<b>155</b>	1462	154	12	700	161	699	161	<b>700</b>	<b>161</b>
444.namd	24	<b>488</b>	<b>395</b>	488	395	490	393	24	<b>481</b>	<b>400</b>	481	400	481	400
447.dealII	24	<b>549</b>	<b>500</b>	544	505	555	495	24	<b>549</b>	<b>500</b>	544	505	555	495
450.soplex	24	<b>1283</b>	<b>156</b>	1265	158	1320	152	12	544	184	<b>535</b>	<b>187</b>	535	187
453.povray	24	<b>212</b>	<b>603</b>	212	603	213	600	24	<b>179</b>	<b>714</b>	179	713	178	718
454.calculix	24	399	496	396	500	<b>396</b>	<b>500</b>	24	399	496	396	500	<b>396</b>	<b>500</b>
459.GemsFDTD	24	1762	145	<b>1755</b>	<b>145</b>	1750	146	24	1762	145	<b>1755</b>	<b>145</b>	1750	146
465.tonto	24	<b>644</b>	<b>367</b>	646	366	640	369	24	628	376	624	379	<b>625</b>	<b>378</b>
470.lbm	24	1033	319	<b>1034</b>	<b>319</b>	1034	319	24	1033	319	<b>1034</b>	<b>319</b>	1034	319
481.wrf	24	1310	205	<b>1314</b>	<b>204</b>	1341	200	24	1310	205	<b>1314</b>	<b>204</b>	1341	200
482.sphinx3	24	1875	249	1880	249	<b>1877</b>	<b>249</b>	24	1768	265	<b>1765</b>	<b>265</b>	1765	265

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
numactl was used to bind copies to the cores

## General Notes

OMP\_NUM\_THREADS set to number of cores  
Hyper-Threading Technology Enabled  
KMP\_AFFINITY set to granularity=fine,scatter  
KMP\_STACKSIZE set to 200M



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cryo Performance Computing Ltd  
Cryo Octane EDP-WS

SPECfp\_rate2006 = 308

SPECfp\_rate\_base2006 = 297

CPU2006 license: 3979

Test sponsor: Cryo Performance Computing Ltd

Tested by: Cryo Performance Computing Ltd

Test date: Mar-2011

Hardware Availability: Dec-2010

Software Availability: Dec-2010

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.lelie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

Fortran benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cryo Performance Computing Ltd  
Cryo Octane EDP-WS

SPECfp\_rate2006 = 308

SPECfp\_rate\_base2006 = 297

CPU2006 license: 3979

Test sponsor: Cryo Performance Computing Ltd

Tested by: Cryo Performance Computing Ltd

Test date: Mar-2011

Hardware Availability: Dec-2010

Software Availability: Dec-2010

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m64

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc -m64

450.soplex: icpc -m32

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-fno-alias -opt-prefetch

470.lbm: basepeak = yes

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cryo Performance Computing Ltd  
Cryo Octane EDP-WS

SPECfp\_rate2006 = 308

SPECfp\_rate\_base2006 = 297

CPU2006 license: 3979

Test sponsor: Cryo Performance Computing Ltd

Tested by: Cryo Performance Computing Ltd

Test date: Mar-2011

Hardware Availability: Dec-2010

Software Availability: Dec-2010

## Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-fno-alias -auto-ilp32

447.dealIII: basepeak = yes

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-malloc-options=3

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: -xSSE4.2 -ipo -O3 -no-prec-div -static

459.GemsFDTD: basepeak = yes

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -auto -inline-calloc -opt-malloc-options=3

Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.html>

<http://www.spec.org/cpu2006/flags/Cryo-platform-linux64-revA.html>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cryo Performance Computing Ltd  
Cryo Octane EDP-WS

SPECfp\_rate2006 = 308

SPECfp\_rate\_base2006 = 297

CPU2006 license: 3979

Test sponsor: Cryo Performance Computing Ltd

Tested by: Cryo Performance Computing Ltd

Test date: Mar-2011

Hardware Availability: Dec-2010

Software Availability: Dec-2010

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.xml>  
<http://www.spec.org/cpu2006/flags/Cryo-platform-linux64-revA.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Wed Jul 23 17:24:43 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 8 April 2011.