



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

SPECint®_rate2006 = **NC**

Sun Fire X4470 M2 (Intel Xeon E7-4870 2.40 GHz)

SPECint_rate_base2006 = **NC**

CPU2006 license: 6

Test date: Mar-2011

Test sponsor: Oracle Corporation

Hardware Availability: Jun-2011

Tested by: Oracle Corporation

Software Availability: Nov-2010

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the listed operating system will not be supported on this platform within 3 months of publication.

	Copies
400.perlbench	
401.bzip2	
403.gcc	
429.mcf	
445.gobmk	
456.hmmer	
458.sjeng	
462.libquantum	
464.h264ref	
473.astar	
483.xalanbmk	

Hardware

CPU Name: Intel Xeon E7-4870
CPU Characteristics: Intel Turbo Boost Technology up to 2.80 GHz
CPU MHz: 2400

Continued on next page

Software

Operating System: Oracle Linux 6
kernel 2.6.32-100.28.5.el6.x86_64

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

SPECint_rate2006 = **NC**

Sun Fire X4470 M2 (Intel Xeon E7-4870 2.40 GHz)

SPECint_rate_base2006 = **NC**

CPU2006 license: 6

Test date: Mar-2011

Test sponsor: Oracle Corporation

Hardware Availability: Jun-2011

Tested by: Oracle Corporation

Software Availability: Nov-2010

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the listed operating system will not be supported on this platform within 3 months of publication.

FPU: Integrated
CPU(s) enabled: 40 cores, 4 chips, 10 cores/chip, 3 threads/core
CPU(s) orderable: 2,4 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 256 KB I+D on chip per core
L3 Cache: 30 MB I+D on chip per chip
Other Cache: None
Memory: 512 GB (64 x 8 GB 2Rx8 PC3L-10600R-9, ECC)
Disk Subsystem: 1 x 500 GB, SATA, 7200 RPM
Other Hardware: None

Compiler: Intel C++ Compiler XE for applications running on IA-32
Version 12.0.1.116 Build 20101116
Auto Parallel: No
File System: ext4
System State: Run level 3 (multi-user)
Base Pointers: 32-bit
Peak Pointers: 32/64-bit
Other Software: Microquill SmartHeap V9.01

Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
400.perlbench	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
401.bzip2	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
403.gcc	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
429.mcf	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
445.gobmk	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
456.hm	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
458.sjeng	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
462.libquantum	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
464.h264ref	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
471.omnetpp	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
473.astar	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
483.xalancbmk	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

SPECint_rate2006 = **NC**

Sun Fire X4470 M2 (Intel Xeon E7-4870 2.40 GHz)

SPECint_rate_base2006 = **NC**

CPU2006 license: 6

Test date: Mar-2011

Test sponsor: Oracle Corporation

Hardware Availability: Jun-2011

Tested by: Oracle Corporation

Software Availability: Nov-2010

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the listed operating system will not be supported on this platform within 3 months of publication.

Submit Notes

The config file option 'submit' was used. numactl was used to bind copies to the cores

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
Hugepages was enabled with the following:
'nodemv /mnt/hugepages hugetlbfs defaults 0 0' added to /etc/fstab
echo 36000 > /proc/sys/vm/nr_hugepages
export HUGETLB_MMAP_SCORE=yes
export LD_PRELOAD=/usr/lib64/libhugetlbfs.so
```

Platform Notes

Default BIOS Settings were used.

General Notes

Binaries were compiled on RHEL5.5 with Binutils binutils-2.17.50.0.6-14.el5

Base Compiler Invocation

C benchmark:
icc -m32

C++ benchmarks:
icpc -m32



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

SPECint_rate2006 = **NC**

Sun Fire X4470 M2 (Intel Xeon E7-4870 2.40 GHz)

SPECint_rate_base2006 = **NC**

CPU2006 license: 6

Test date: Mar-2011

Test sponsor: Oracle Corporation

Hardware Availability: Jun-2011

Tested by: Oracle Corporation

Software Availability: Nov-2010

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the listed operating system will not be supported on this platform within 3 months of publication.

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch
-B /usr/share/ldsohugetlbfs/ -Wl,-hugetlbfs-link=BDT

C++ benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
-L/smartheap -smarthheap
-B /usr/share/ldsohugetlbfs/ -Wl,-hugetlbfs-link=BDT

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc -m32

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

SPECint_rate2006 = **NC**

Sun Fire X4470 M2 (Intel Xeon E7-4870 2.40 GHz)

SPECint_rate_base2006 = **NC**

CPU2006 license: 6

Test date: Mar-2011

Test sponsor: Oracle Corporation

Hardware Availability: Jun-2011

Tested by: Oracle Corporation

Software Availability: Nov-2010

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the listed operating system will not be supported on this platform within 3 months of publication.

Peak Compiler Invocation (Continued)

400.perlbench: `icc -m64`

401.bzip2: `icc -m64`

456.hmmer: `icc -m64`

458.sjeng: `icc -m64`

C++ benchmarks:

`icpc -m32`

Peak Portability Flags

400.perlbench: `-DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64`

401.bzip2: `-DSPEC_CPU_LP64`

456.hmmer: `-DSPEC_CPU_LP64`

458.sjeng: `-DSPEC_CPU_LP64`

462.libquantum: `-DSPEC_CPU_LINUX`

463.mcf: `-DSPEC_CPU_LINUX`

Peak Optimization Flags

C benchmarks:

400.perlbench: `-xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)`

`-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)`

`-B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT`

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 5



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

SPECint_rate2006 = **NC**

Sun Fire X4470 M2 (Intel Xeon E7-4870 2.40 GHz)

SPECint_rate_base2006 = **NC**

CPU2006 license: 6

Test date: Mar-2011

Test sponsor: Oracle Corporation

Hardware Availability: Jun-2011

Tested by: Oracle Corporation

Software Availability: Nov-2010

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the listed operating system will not be supported on this platform within 3 months of publication.

Peak Optimization Flags (Continued)

```

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
          -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
          -opt-prefetch -auto-ilp32 -ansi-alias
          -B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

403.gcc: -xSSE4.2 -ipo -no-prec-div
         -B /usr/share/libhugetlbfs/ -Wl,-hugetlbfs-link=BDT

429.mcf: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
         -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
         -ansi-alias -auto-ilp32

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)
          -ansi-alias -auto-ilp32

456.hmme: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -auto-ilp32
         -B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
          -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
          -unroll4 -auto-ilp32
          -B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

462.libquantum: basepeak = yes

464.lib64ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
             -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
             -unroll2 -ansi-alias

```

C++ benchmarks:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

SPECint_rate2006 = **NC**

Sun Fire X4470 M2 (Intel Xeon E7-4870 2.40 GHz)

SPECint_rate_base2006 = **NC**

CPU2006 license: 6

Test date: Mar-2011

Test sponsor: Oracle Corporation

Hardware Availability: Jun-2011

Tested by: Oracle Corporation

Software Availability: Nov-2010

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the listed operating system will not be supported on this platform within 3 months of publication.

Peak Optimization Flags (Continued)

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs
-L/smartheap -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.html>

http://www.spec.org/cpu2006/flags/Oracle-platform-x86_64.20101027.html

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.xml>

http://www.spec.org/cpu2006/flags/Oracle-platform-x86_64.20101027.xml



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

SPECint_rate2006 = NC

Sun Fire X4470 M2 (Intel Xeon E7-4870 2.40 GHz)

SPECint_rate_base2006 = NC

CPU2006 license: 6

Test date: Mar-2011

Test sponsor: Oracle Corporation

Hardware Availability: Jun-2011

Tested by: Oracle Corporation

Software Availability: Nov-2010

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the listed operating system will not be supported on this platform within 3 months of publication.

Non-Compliant

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 19:03:49 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 26 April 2011.