



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp[®]_rate2006 = 36.9

Asus M4A89GTD-PRO (Athlon II X2 255)

SPECfp_rate_base2006 = 36.5

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: May-2011

Hardware Availability: Jul-2010

Software Availability: Apr-2011



Hardware

CPU Name: AMD Athlon II X2 255
 CPU Characteristics:
 CPU MHz: 3100
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core

Continued on next page

Software

Operating System: Windows 7 Ultimate (64-bit)
 Compiler: Intel C++ Compiler XE for Intel 64
 Version 12.0.3.176 Build 20110309
 Intel Visual Fortran Compiler XE for Intel 64
 Version 12.0.3.176 Build 20110309
 Microsoft Visual Studio 2008 Professional SP1
 (for libraries)
 Auto Parallel: No
 File System: NTFS

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

SPECfp_rate2006 = 36.9

Asus M4A89GTD-PRO (Athlon II X2 255)

SPECfp_rate_base2006 = 36.5

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: May-2011

Hardware Availability: Jul-2010

Software Availability: Apr-2011

L3 Cache: None
Other Cache: None
Memory: 4 GB (2 x 2 GB 2Rx8 PC3-10600U-9)
Disk Subsystem: Seagate 1 TB SATA, 7200 RPM
Other Hardware: None

System State: Default
Base Pointers: 32/64-bit
Peak Pointers: 32/64-bit
Other Software: SmartHeap Library Version 9.01 from <http://www.microquill.com/>

Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---------------|--------|------------|-------------|-------------|-------------|------------|-------------|--------|-------------|-------------|-------------|-------------|-------------|-------------|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 2 | <u>539</u> | <u>50.4</u> | 539 | 50.4 | 540 | 50.4 | 2 | <u>539</u> | <u>50.4</u> | 539 | 50.4 | 540 | 50.4 |
| 416.gamess | 2 | 920 | 42.6 | <u>920</u> | <u>42.6</u> | 920 | 42.6 | 2 | 920 | 42.6 | <u>920</u> | <u>42.6</u> | 920 | 42.6 |
| 433.milc | 2 | 386 | 47.6 | <u>386</u> | <u>47.6</u> | 386 | 47.6 | 2 | 386 | 47.6 | <u>386</u> | <u>47.6</u> | 386 | 47.6 |
| 434.zeusmp | 2 | <u>486</u> | <u>37.4</u> | 486 | 37.4 | 487 | 37.4 | 2 | <u>486</u> | <u>37.4</u> | 486 | 37.4 | 487 | 37.4 |
| 435.gromacs | 2 | <u>419</u> | <u>34.0</u> | 419 | 34.0 | 419 | 34.0 | 2 | 420 | 34.0 | 421 | 34.0 | <u>420</u> | <u>34.0</u> |
| 436.cactusADM | 2 | 630 | 38.0 | <u>629</u> | <u>38.0</u> | 629 | 38.0 | 2 | 630 | 38.0 | <u>629</u> | <u>38.0</u> | 629 | 38.0 |
| 437.leslie3d | 2 | 855 | 22.0 | 857 | 22.0 | <u>856</u> | <u>22.0</u> | 2 | 855 | 22.0 | 857 | 22.0 | <u>856</u> | <u>22.0</u> |
| 444.namd | 2 | 494 | 32.4 | <u>494</u> | <u>32.4</u> | 495 | 32.4 | 2 | 488 | 32.8 | <u>488</u> | <u>32.8</u> | 488 | 32.8 |
| 447.dealII | 2 | 600 | 38.2 | <u>595</u> | <u>38.4</u> | 594 | 38.6 | 2 | 611 | 37.4 | <u>614</u> | <u>37.2</u> | 616 | 37.2 |
| 450.soplex | 2 | <u>703</u> | <u>23.8</u> | 706 | 23.6 | 703 | 23.8 | 2 | 696 | 24.0 | 695 | 24.0 | <u>695</u> | <u>24.0</u> |
| 453.povray | 2 | <u>231</u> | <u>46.2</u> | 230 | 46.2 | 231 | 46.2 | 2 | 198 | 53.6 | <u>198</u> | <u>53.8</u> | 198 | 53.8 |
| 454.calculix | 2 | 346 | 47.8 | 347 | 47.6 | <u>347</u> | <u>47.6</u> | 2 | 348 | 47.4 | <u>348</u> | <u>47.4</u> | 347 | 47.6 |
| 459.GemsFDTD | 2 | 1096 | 19.4 | <u>1097</u> | <u>19.4</u> | 1098 | 19.4 | 2 | 1096 | 19.4 | <u>1097</u> | <u>19.4</u> | 1098 | 19.4 |
| 465.tonto | 2 | 506 | 38.8 | 509 | 38.6 | <u>508</u> | <u>38.8</u> | 2 | 494 | 39.8 | <u>495</u> | <u>39.8</u> | 495 | 39.8 |
| 470.lbm | 2 | 652 | 42.2 | <u>650</u> | <u>42.4</u> | 649 | 42.4 | 2 | 652 | 42.2 | <u>650</u> | <u>42.4</u> | 649 | 42.4 |
| 481.wrf | 2 | <u>498</u> | <u>44.8</u> | 498 | 44.8 | 501 | 44.6 | 2 | <u>498</u> | <u>44.8</u> | 498 | 44.8 | 501 | 44.6 |
| 482.sphinx3 | 2 | 1081 | 36.0 | <u>1081</u> | <u>36.0</u> | 1085 | 36.0 | 2 | <u>1082</u> | 36.0 | 1085 | 36.0 | <u>1083</u> | <u>36.0</u> |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
The start command with the /affinity switch was used to bind processes to cores

General Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply

Base Compiler Invocation

C benchmarks:
icl -Qvc9 -Qstd=c99

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp_rate2006 = 36.9

Asus M4A89GTD-PRO (Athlon II X2 255)

SPECfp_rate_base2006 = 36.5

CPU2006 license: 13

Test date: May-2011

Test sponsor: Intel Corporation

Hardware Availability: Jul-2010

Tested by: Intel Corporation

Software Availability: Apr-2011

Base Compiler Invocation (Continued)

C++ benchmarks:

icl -Qvc9

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc9 -Qstd=c99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64 -names:lowercase
 416.gamess: -DSPEC_CPU_P64
 433.milc: -DSPEC_CPU_P64
 434.zeusmp: -DSPEC_CPU_P64
 435.gromacs: -DSPEC_CPU_P64
 436.cactusADM: -DSPEC_CPU_P64 -names:lowercase /assume:underscore
 437.leslie3d: -DSPEC_CPU_P64
 444.namd: -DSPEC_CPU_P64 /TP
 447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
 450.soplex: -DSPEC_CPU_P64
 453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
 454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -names:lowercase
 459.GemsFDTD: -DSPEC_CPU_P64
 465.tonto: -DSPEC_CPU_P64
 470.lbm: -DSPEC_CPU_P64
 481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
 482.sphinx3: -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:

/arch:SSE3 -Qipo -O3 -Qprec-div- -Qansi-alias -Qauto-ilp32
/F1000000000 -link /FORCE:MULTIPLE

C++ benchmarks:

/arch:SSE3 -Qipo -O3 -Qprec-div- -Qansi-alias -Qcxx-features
-Qauto-ilp32 /F1000000000 shlw64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

/arch:SSE3 -Qipo -O3 -Qprec-div- -Qansi-alias /F1000000000
-link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

/arch:SSE3 -Qipo -O3 -Qprec-div- -Qansi-alias -Qauto-ilp32
/F1000000000 -link /FORCE:MULTIPLE



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp_rate2006 = 36.9

Asus M4A89GTD-PRO (Athlon II X2 255)

SPECfp_rate_base2006 = 36.5

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2011
Hardware Availability: Jul-2010
Software Availability: Apr-2011

Peak Compiler Invocation

C benchmarks:
icl -Qvc9 -Qstd=c99
C++ benchmarks:
icl -Qvc9
Fortran benchmarks:
ifort
Benchmarks using both Fortran and C:
icl -Qvc9 -Qstd=c99 ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:
433.milc: basepeak = yes
470.lbm: basepeak = yes
482.sphinx3: /arch:SSE3 -Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE
C++ benchmarks:
444.namd: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000
shlW64M.lib -link /FORCE:MULTIPLE
447.dealII: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias
-Qscalar-rep- -Qauto-ilp32 /F1000000000 shlW64M.lib
-link /FORCE:MULTIPLE
450.soplex: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qauto-ilp32 /F1000000000 shlW64M.lib
-link /FORCE:MULTIPLE
453.povray: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32
/F1000000000 shlW64M.lib -link /FORCE:MULTIPLE

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp_rate2006 = 36.9

Asus M4A89GTD-PRO (Athlon II X2 255)

SPECfp_rate_base2006 = 36.5

CPU2006 license: 13

Test date: May-2011

Test sponsor: Intel Corporation

Hardware Availability: Jul-2010

Tested by: Intel Corporation

Software Availability: Apr-2011

Peak Optimization Flags (Continued)

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 -Qauto /F1000000000
-link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

435.gromacs: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32
/F1000000000 -link /FORCE:MULTIPLE

436.cactusADM: basepeak = yes

454.calculix: /arch:SSE3 -Qipo -O3 -Qprec-div- -Qauto-ilp32
/F1000000000 -link /FORCE:MULTIPLE

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revB.html>

<http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings.20110719.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revB.xml>

<http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings.20110719.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 21:20:03 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 19 July 2011.