



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

SPECint®_rate2006 = NC

Cisco UCS C260 M2 (Intel Xeon E7-2870, 2.40 GHz)

SPECint_rate_base2006 = NC

CPU2006 license: 9019

Test date: Jan-2012

Test sponsor: Cisco Systems

Hardware Availability: May-2011

Tested by: Cisco Systems

Software Availability: Oct-2011

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication.

	Copies
400.perlbench	
401.bzip2	
403.gcc	
429.mcf	
445.gobmk	
456.hmmer	
458.sjeng	
462.libquantum	
464.h264ref	
471.omnetpp	
473.astar	
483	

Non-Compliant

Hardware

CPU Name: Intel Xeon E7-4870
 CPU Characteristics: Intel Turbo Boost Technology up to 2.80 GHz
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 20 cores, 2 chips, 10 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux Server release 6.1 (Santiago)
 2.6.32-131.0.15.el6.x86_64
 Compiler: C/C++: Version 12.1.0.225 of Intel C++ Studio XE for Linux
 Auto Parallel: No
 File System: ext4
 System State: Run level 3 (multi-user)

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

SPECint_rate2006 = **NC**

Cisco UCS C260 M2 (Intel Xeon E7-2870, 2.40 GHz)

SPECint_rate_base2006 = **NC**

CPU2006 license: 9019

Test date: Jan-2012

Test sponsor: Cisco Systems

Hardware Availability: May-2011

Tested by: Cisco Systems

Software Availability: Oct-2011

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication.

Secondary Cache: 256 KB I+D on chip per core
L3 Cache: 30 MB I+D on chip per chip
Other Cache: None
Memory: 512 GB (32 x 16 GB 4Rx4 PC3-8500R-9, ECC)
Disk Subsystem: 600 GB SAS 10K RPM
Other Hardware: None

Base Processors: 32-bit
Link Pointers: 32/64-bit
Other Software: Microquill SmartHeap V9.01

Result Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
400.perlbench	40	NC	NC	NC	NC	NC	NC	40	NC	NC	NC	NC	NC	NC		
401.bzip2	40	NC	NC	NC	NC	NC	NC	40	NC	NC	NC	NC	NC	NC		
403.gcc	40	NC	NC	NC	NC	NC	NC	40	NC	NC	NC	NC	NC	NC		
429.mcf	40	NC	NC	NC	NC	NC	NC	40	NC	NC	NC	NC	NC	NC		
445.gobmk	40	NC	NC	NC	NC	NC	NC	40	NC	NC	NC	NC	NC	NC		
456.hmmer	40	NC	NC	NC	NC	NC	NC	40	NC	NC	NC	NC	NC	NC		
458.sjeng	40	NC	NC	NC	NC	NC	NC	40	NC	NC	NC	NC	NC	NC		
462.libquantum	40	NC	NC	NC	NC	NC	NC	40	NC	NC	NC	NC	NC	NC		
464.h264ref	40	NC	NC	NC	NC	NC	NC	40	NC	NC	NC	NC	NC	NC		
471.omnetpp	40	NC	NC	NC	NC	NC	NC	40	NC	NC	NC	NC	NC	NC		
473.astar	40	NC	NC	NC	NC	NC	NC	40	NC	NC	NC	NC	NC	NC		
483.xs	40	NC	NC	NC	NC	NC	NC	40	NC	NC	NC	NC	NC	NC		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

SPECint_rate2006 = NC

Cisco UCS C260 M2 (Intel Xeon E7-2870, 2.40 GHz)

SPECint_rate_base2006 = NC

CPU2006 license: 9019

Test date: Jan-2012

Test sponsor: Cisco Systems

Hardware Availability: May-2011

Tested by: Cisco Systems

Software Availability: Oct-2011

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

Sysinfo program /opt/cpu2006/config/sysinfo.rev6800
\$Rev: 6800 \$ \$Date:: 2011-10-11 # \$ 6f2e...5032aaa42e583f96b07f99d3
running on localhost.localdomain Tue Jan 3 19:35:00 2012

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see: <http://www.spec.org/cpu2006/config.html#sysinfo>

From /proc/cpuinfo
model name : Intel(R) Xeon(R) CPU E7- 4870 @ 2.40GHz
2 "physical id" (chips)
40 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following excerpt from /proc/cpuinfo might not be reliable. Use with caution.)
cpu cores : 40
siblings : 40
physical 0: cores 0 1 2 8 9 16 17 18 24 25
physical 1: cores 0 1 2 8 9 16 17 18 24 25
cache size : 30720 KB

MemTotal: 529190808 kB
PagePages_Total: 0
Hugepagesize: 2048 kB

/usr/bin/lsb_release -d
Red Hat Enterprise Linux Server release 6.1 (Santiago)

From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.1 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.1 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

SPECint_rate2006 = NC

Cisco UCS C260 M2 (Intel Xeon E7-2870, 2.40 GHz)

SPECint_rate_base2006 = NC

CPU2006 license: 9019

Test date: Jan-2012

Test sponsor: Cisco Systems

Hardware Availability: May-2011

Tested by: Cisco Systems

Software Availability: Oct-2011

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication.

Platform Notes (Continued)

```

uname -a:
  Linux localhost.localdomain 2.6.32-1300.0.15.el6.x86_64 #1 SMP Tue May 10
  15:42:40 EDT 2011 x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Jan 3 18:08

SPEC is set to: /opt/cpu2006
  Filesystem      Type      Size  Used Avail Use% Mounted on
  /dev/sdal       ext4      50G   5.6G  5.6G   2% /

Additional information from /dev/decode:

(End of data from sysinfo program)

```

General Notes

```

Environment variables set by runspec before the start of the run:
LD_LIBRARY_PATH = "/opt/cpu2006/libs/32:/opt/cpu2006/libs/64"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB
memory using RHEL5.
Transparent Huge Pages enabled with:
echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
Filesystem page cache cleared with:
echo 1 > /proc/sys/vm/drop_caches
numactl was invoked through numactl i.e.:
numactl --interleave=all runspec <etc>

```

Base Compiler Invocation

```

C benchmarks:
  icc -m32

C++ benchmarks:
  icpc -m32

```



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

SPECint_rate2006 = NC

Cisco UCS C260 M2 (Intel Xeon E7-2870, 2.40 GHz)

SPECint_rate_base2006 = NC

CPU2006 license: 9019

Test date: Jan-2012

Test sponsor: Cisco Systems

Hardware Availability: May-2011

Tested by: Cisco Systems

Software Availability: Oct-2011

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication.

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3
C++ benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3
-Wl,-z,muldefs -L/smarteap -lsmartheap

Base Other Flags

C benchmarks:
403.gcc -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc -m32
400.perlbench: icc -m64
401.bzip2: icc -m64
456.hmmer: icc -m64

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

SPECint_rate2006 = NC

Cisco UCS C260 M2 (Intel Xeon E7-2870, 2.40 GHz)

SPECint_rate_base2006 = NC

CPU2006 license: 9019

Test date: Jan-2012

Test sponsor: Cisco Systems

Hardware Availability: May-2011

Tested by: Cisco Systems

Software Availability: Oct-2011

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication.

Peak Compiler Invocation (Continued)

458.sjeng: icc -m64

C++ benchmarks:

icpc -m32

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64

401.bzip2: -DSPEC_CPU_LP64

456.hmmr: -DSPEC_CPU_LP64

458.sjeng: -DSPEC_CPU_LP64

462.libquantum: -DSPEC_CPU_LINUX

483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-auto-ilp32

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-opt-prefetch -auto-ilp32 -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div

429.mcf: basepeak = yes

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)
-ansi-alias -opt-mem-layout-trans=3

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

SPECint_rate2006 = NC

Cisco UCS C260 M2 (Intel Xeon E7-2870, 2.40 GHz)

SPECint_rate_base2006 = NC

CPU2006 license: 9019

Test date: Jan-2012

Test sponsor: Cisco Systems

Hardware Availability: May-2011

Tested by: Cisco Systems

Software Availability: Oct-2011

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication.

Peak Optimization Flags (Continued)

456.hmmmer: -xSSE4.2 -ipo -O3 -no-prec-div -unroll12 -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-unroll14 -auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-unroll12 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-ansi-alias -t-ra-region-strategy=block -Wl,-z,muldefs
-L/smackheap -lsmartheap

473.astar: basepeak = yes

483.balancbm: basepeak = yes

Peak Other Flags

C benchmarks:

402.gcc: -Dalloca=_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.html>

<http://www.spec.org/cpu2006/flags/Cisco-Platform-Settings-V1.2.html>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

SPECint_rate2006 = NC

Cisco UCS C260 M2 (Intel Xeon E7-2870, 2.40 GHz)

SPECint_rate_base2006 = NC

CPU2006 license: 9019

Test date: Jan-2012

Test sponsor: Cisco Systems

Hardware Availability: May-2011

Tested by: Cisco Systems

Software Availability: Oct-2011

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication.

You can also download the XML flags source by using the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux.201111.xml>
<http://www.spec.org/cpu2006/flags/Cisco-Platform-Settings-V1.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Jul 24 03:42:27 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 15 February 2012.