



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

SPECint®_rate2006 = 2070

SuperServer 5086B-TRF (X8OBN-F, Intel E7-8870)

SPECint_rate_base2006 = 1960

CPU2006 license: 001176


Test date: May-2012

Test sponsor: Supermicro

Hardware Availability: Jan-2012

Tested by: Supermicro

Software Availability: Dec-2011



Hardware

CPU Name: Intel Xeon E7-8870
 CPU Characteristics: Intel Turbo Boost Technology up to 2.80 GHz
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 80 cores, 8 chips, 10 cores/chip, 2 threads/core
 CPU(s) orderable: 1-8 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 30 MB I+D on chip per chip
 Other Cache: None
 Memory: 1 TB (64 x 16 GB 2Rx4 PC3-10600R-9, ECC)
 Disk Subsystem: 1 x 2 TB SATA II, 7200 RPM
 Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux Server Release 6.2, Kernel 2.6.32-220.el6.x86_64
 Compiler: C/C++; Version 12.1.0.225 of Intel C++ Studio XE for Linux
 Auto Parallel: No
 File System: ext4
 System State: Run level 3 (multi-user)
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: Microquill SmartHeap V9.01



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

SPECint_rate2006 = 2070

SuperServer 5086B-TRF (X8OBN-F, Intel E7-8870)

SPECint_rate_base2006 = 1960

CPU2006 license: 001176

Test date: May-2012

Test sponsor: Supermicro

Hardware Availability: Jan-2012

Tested by: Supermicro

Software Availability: Dec-2011

Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	160	944	1660	<u>945</u>	<u>1650</u>	946	1650	160	810	1930	819	1910	<u>817</u>	<u>1910</u>
401.bzip2	160	1338	1150	<u>1338</u>	<u>1150</u>	1339	1150	160	<u>1286</u>	<u>1200</u>	1289	1200	1283	1200
403.gcc	160	<u>934</u>	<u>1380</u>	931	1380	936	1380	160	934	1380	<u>935</u>	<u>1380</u>	936	1380
429.mcf	160	642	2270	640	2280	<u>641</u>	<u>2280</u>	160	642	2270	640	2280	<u>641</u>	<u>2280</u>
445.gobmk	160	891	1880	<u>892</u>	<u>1880</u>	892	1880	160	852	1970	851	1970	<u>851</u>	<u>1970</u>
456.hammer	160	562	2660	561	2660	<u>561</u>	<u>2660</u>	160	<u>436</u>	<u>3430</u>	439	3400	435	3430
458.sjeng	160	<u>1087</u>	<u>1780</u>	1088	1780	1087	1780	160	1000	1940	<u>1001</u>	<u>1930</u>	1001	1930
462.libquantum	160	259	12800	<u>259</u>	<u>12800</u>	258	12800	160	259	12800	<u>259</u>	<u>12800</u>	258	12800
464.h264ref	160	1378	2570	1382	2560	<u>1380</u>	<u>2570</u>	160	1382	2560	1373	2580	<u>1376</u>	<u>2570</u>
471.omnetpp	160	998	1000	<u>997</u>	<u>1000</u>	997	1000	160	957	1040	<u>956</u>	<u>1050</u>	956	1050
473.astar	160	<u>984</u>	<u>1140</u>	983	1140	986	1140	160	<u>984</u>	<u>1140</u>	983	1140	986	1140
483.xalancbmk	160	673	1640	<u>674</u>	<u>1640</u>	674	1640	160	673	1640	<u>674</u>	<u>1640</u>	674	1640

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

General Notes

Environment variables set by runspec before the start of the run:
LD_LIBRARY_PATH = "/usr/cpu2006/libs/32:/usr/cpu2006/libs/64"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RHEL5.5
Transparent Huge Pages enabled with:
echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
Filesystem page cache cleared with:
echo 1> /proc/sys/vm/drop_caches
runspec command invoked through numactl i.e.:
numactl --interleave=all runspec <etc>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

SPECint_rate2006 = 2070

SuperServer 5086B-TRF (X8OBN-F, Intel E7-8870)

SPECint_rate_base2006 = 1960

CPU2006 license: 001176

Test date: May-2012

Test sponsor: Supermicro

Hardware Availability: Jan-2012

Tested by: Supermicro

Software Availability: Dec-2011

Base Compiler Invocation

C benchmarks:

`icc -m32`

C++ benchmarks:

`icpc -m32`

Base Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_IA32`
462.libquantum: `-DSPEC_CPU_LINUX`
483.xalancbmk: `-DSPEC_CPU_LINUX`

Base Optimization Flags

C benchmarks:

`-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3`

C++ benchmarks:

`-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3
-Wl,-z,muldefs -L/smartheap -lsmartheap`

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks (except as noted below):

`icc -m32`

400.perlbench: `icc -m64`

401.bzip2: `icc -m64`

456.hmmer: `icc -m64`

458.sjeng: `icc -m64`

C++ benchmarks:

`icpc -m32`



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

SPECint_rate2006 = 2070

SuperServer 5086B-TRF (X8OBN-F, Intel E7-8870)

SPECint_rate_base2006 = 1960

CPU2006 license: 001176

Test date: May-2012

Test sponsor: Supermicro

Hardware Availability: Jan-2012

Tested by: Supermicro

Software Availability: Dec-2011

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
 401.bzip2: -DSPEC_CPU_LP64
 456.hmmer: -DSPEC_CPU_LP64
 458.sjeng: -DSPEC_CPU_LP64
 462.libquantum: -DSPEC_CPU_LINUX
 483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
 -auto-ilp32

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
 -opt-prefetch -auto-ilp32 -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div

429.mcf: basepeak = yes

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)
 -ansi-alias -opt-mem-layout-trans=3

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
 -unroll4 -auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
 -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
 -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs
 -L/smartheap -lsmartheap

473.astar: basepeak = yes

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

SPECint_rate2006 = 2070

SuperServer 5086B-TRF (X8OBN-F, Intel E7-8870)

SPECint_rate_base2006 = 1960

CPU2006 license: 001176

Test date: May-2012

Test sponsor: Supermicro

Hardware Availability: Jan-2012

Tested by: Supermicro

Software Availability: Dec-2011

Peak Optimization Flags (Continued)

483.xalanbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Jul 24 11:20:01 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 31 July 2012.