



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECint®\_rate2006 = 386

Servidor Itaotec MX215 (Intel Xeon E5-2620)

SPECint\_rate\_base2006 = 374

CPU2006 license: 9001


Test date: Jun-2012

Test sponsor: Itaotec

Hardware Availability: Jun-2012

Tested by: Itaotec

Software Availability: Dec-2011



## Hardware

CPU Name: Intel Xeon E5-2620  
 CPU Characteristics: Intel Turbo Boost Technology up to 2.50 GHz  
 CPU MHz: 2000  
 FPU: Integrated  
 CPU(s) enabled: 12 cores, 2 chips, 6 cores/chip, 2 threads/core  
 CPU(s) orderable: 1,2 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 15 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 64 GB (16 x 4 GB 2Rx4 PC3-10600R-9, ECC)  
 Disk Subsystem: 500 GB, SATA-2, 7200 RPM  
 Other Hardware: None

## Software

Operating System: Red Hat Enterprise Linux Server Release 6.2, Kernel 2.6.32-220.el6.x86\_64  
 Compiler: C/C++: Version 12.1.0 of Intel Compiler XE Build 20111011  
 Auto Parallel: No  
 File System: ext4  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Microquill SmartHeap V8.1



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECint\_rate2006 = 386

Servidor Itaotec MX215 (Intel Xeon E5-2620)

SPECint\_rate\_base2006 = 374

CPU2006 license: 9001  
Test sponsor: Itaotec  
Tested by: Itaotec

Test date: Jun-2012  
Hardware Availability: Jun-2012  
Software Availability: Dec-2011

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	24	880	266	<b>886</b>	<b>265</b>	948	247	24	748	314	753	311	<b>753</b>	<b>311</b>
401.bzip2	24	1144	202	<b>1143</b>	<b>203</b>	1142	203	24	1101	210	<b>1104</b>	<b>210</b>	1105	210
403.gcc	24	<b>630</b>	<b>307</b>	633	305	629	307	24	633	305	<b>630</b>	<b>307</b>	630	307
429.mcf	24	360	608	<b>362</b>	<b>604</b>	363	602	24	360	608	<b>362</b>	<b>604</b>	363	602
445.gobmk	24	904	278	916	275	<b>911</b>	<b>276</b>	24	905	278	<b>886</b>	<b>284</b>	886	284
456.hammer	24	489	458	490	457	<b>489</b>	<b>458</b>	24	489	458	490	457	<b>489</b>	<b>458</b>
458.sjeng	24	1052	276	<b>1051</b>	<b>276</b>	1051	276	24	1004	289	<b>1006</b>	<b>289</b>	1019	285
462.libquantum	24	227	2190	<b>227</b>	<b>2190</b>	227	2190	24	227	2190	<b>227</b>	<b>2190</b>	227	2190
464.h264ref	24	1165	456	<b>1164</b>	<b>456</b>	1139	466	24	1119	475	1158	459	<b>1142</b>	<b>465</b>
471.omnetpp	24	654	229	656	229	<b>655</b>	<b>229</b>	24	613	245	612	245	<b>613</b>	<b>245</b>
473.astar	24	752	224	<b>757</b>	<b>223</b>	760	222	24	752	224	<b>757</b>	<b>223</b>	760	222
483.xalancbmk	24	386	428	387	427	<b>387</b>	<b>428</b>	24	386	428	387	427	<b>387</b>	<b>428</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
numactl was used to bind copies to the cores

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run.  
Large pages were not enabled for this run

## Platform Notes

Sysinfo program /home/rcaneca/cpu2006/Docs/sysinfo  
\$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ 8787f7622badcf24e01c368b1db4377c  
running on localhost Thu Jun 14 19:56:00 2012

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:  
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo  
model name : Intel(R) Xeon(R) CPU E5-2620 0 @ 2.00GHz  
2 "physical id"s (chips)  
24 "processors"  
cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)  
cpu cores : 6  
siblings : 12

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECint\_rate2006 = 386

Servidor Itautec MX215 (Intel Xeon E5-2620)

SPECint\_rate\_base2006 = 374

CPU2006 license: 9001  
Test sponsor: Itautec  
Tested by: Itautec

Test date: Jun-2012  
Hardware Availability: Jun-2012  
Software Availability: Dec-2011

## Platform Notes (Continued)

```
physical 0: cores 0 1 2 3 4 5
physical 1: cores 0 1 2 3 4 5
cache size : 15360 KB
```

```
From /proc/meminfo
MemTotal:      65918268 kB
HugePages_Total: 0
Hugepagesize:  2048 kB
```

```
/usr/bin/lsb_release -d
Red Hat Enterprise Linux Server release 6.2 (Santiago)
```

```
From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.2 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.2 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server
```

```
uname -a:
Linux localhost 2.6.32-220.el6.x86_64 #1 SMP Wed Nov 9 08:03:13 EST 2011
x86_64 x86_64 x86_64 GNU/Linux
```

```
run-level 3 Jun 14 19:40
```

```
SPEC is set to: /home/rcaneca/cpu2006
Filesystem      Type      Size  Used Avail Use% Mounted on
/dev/mapper/vg_it5rh-lv_home
                ext4      193G  5.4G  178G   3% /home
```

(End of data from sysinfo program)

## General Notes

This result was measured on the Servidor Itautec MX215.  
The Servidor Itautec MX215 and the Servidor Itautec MX225  
are electronically equivalent.

## Base Compiler Invocation

C benchmarks:  
icc -m32

C++ benchmarks:  
icpc -m32



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECint\_rate2006 = 386

Servidor Itaotec MX215 (Intel Xeon E5-2620)

SPECint\_rate\_base2006 = 374

CPU2006 license: 9001  
Test sponsor: Itaotec  
Tested by: Itaotec

Test date: Jun-2012  
Hardware Availability: Jun-2012  
Software Availability: Dec-2011

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:  
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3

C++ benchmarks:  
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3  
-Wl,-z,muldefs -L/home/rcaneca/sh/SmartHeap\_8.1/lib -lsmartheap

## Base Other Flags

C benchmarks:  
403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):  
icc -m32

400.perlbench: icc -m64

401.bzip2: icc -m64

458.sjeng: icc -m64

C++ benchmarks:  
icpc -m32

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
401.bzip2: -DSPEC\_CPU\_LP64  
458.sjeng: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECint\_rate2006 = 386

Servidor Itaotec MX215 (Intel Xeon E5-2620)

SPECint\_rate\_base2006 = 374

CPU2006 license: 9001  
Test sponsor: Itaotec  
Tested by: Itaotec

Test date: Jun-2012  
Hardware Availability: Jun-2012  
Software Availability: Dec-2011

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-B /usr/share/libhugetlbfs/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfs-link=BDT

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32 -ansi-alias  
-B /usr/share/libhugetlbfs/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfs-link=BDT

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div

429.mcf: basepeak = yes

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)  
-ansi-alias -auto-ilp32

456.hmmcr: basepeak = yes

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll14 -auto-ilp32  
-B /usr/share/libhugetlbfs/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfs-link=BDT

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll12 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs  
-L/home/rcaneca/sh/SmartHeap\_8.1/lib -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECint\_rate2006 = 386

Servidor Itaotec MX215 (Intel Xeon E5-2620)

SPECint\_rate\_base2006 = 374

CPU2006 license: 9001

Test sponsor: Itaotec

Tested by: Itaotec

Test date: Jun-2012

Hardware Availability: Jun-2012

Software Availability: Dec-2011

The flags files that were used to format this result can be browsed at

[http://www.spec.org/cpu2006/flags/Itaotec-Servidor\\_Itaotec-Intel-Linux-Platform.html](http://www.spec.org/cpu2006/flags/Itaotec-Servidor_Itaotec-Intel-Linux-Platform.html)

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.html>

You can also download the XML flags sources by saving the following links:

[http://www.spec.org/cpu2006/flags/Itaotec-Servidor\\_Itaotec-Intel-Linux-Platform.xml](http://www.spec.org/cpu2006/flags/Itaotec-Servidor_Itaotec-Intel-Linux-Platform.xml)

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Thu Jul 24 09:38:09 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 3 July 2012.