



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint®2006 = 51.1

Intel DH77KC motherboard (Intel Core i5-3570)

SPECint_base2006 = 48.5

CPU2006 license: 13


Test date: May-2012

Test sponsor: Intel Corporation

Hardware Availability: Apr-2012

Tested by: Intel Corporation

Software Availability: Apr-2011



Hardware

CPU Name: Intel Core i5-3570
 CPU Characteristics: Intel Turbo Boost Technology up to 3.80 GHz
 CPU MHz: 3400
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 6 MB I+D on chip per chip
 Other Cache: None
 Memory: 8 GB (2 x 4 GB 2Rx4 PC3-12800U-11)
 Disk Subsystem: 1 TB Seagate SATA, 7200 RPM
 Other Hardware: None

Software

Operating System: Microsoft Windows 7 Ultimate (64-bit) 6.1.7601 Service Pack 1 Build 7601
 Compiler: C/C++: Version 12.1.0.229 of Intel C++ Studio XE for Windows;
 Libraries: Version 15.00.30729.01 of Microsoft Visual Studio 2008 Professional SP1
 Auto Parallel: Yes
 File System: NTFS
 System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 9.01 from <http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 51.1

Intel DH77KC motherboard (Intel Core i5-3570)

SPECint_base2006 = 48.5

CPU2006 license: 13

Test date: May-2012

Test sponsor: Intel Corporation

Hardware Availability: Apr-2012

Tested by: Intel Corporation

Software Availability: Apr-2011

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	319	30.6	<u>319</u>	<u>30.6</u>	319	30.6	<u>242</u>	<u>40.4</u>	242	40.4	241	40.5
401.bzip2	372	26.0	371	26.0	<u>372</u>	<u>26.0</u>	361	26.8	361	26.7	<u>361</u>	<u>26.8</u>
403.gcc	267	30.2	<u>267</u>	<u>30.1</u>	267	30.1	252	31.9	<u>252</u>	<u>31.9</u>	252	32.0
429.mcf	<u>127</u>	<u>71.6</u>	127	71.8	129	71.0	<u>127</u>	<u>71.6</u>	127	71.8	129	71.0
445.gobmk	380	27.6	<u>380</u>	<u>27.6</u>	380	27.6	345	30.4	<u>345</u>	<u>30.4</u>	345	30.4
456.hammer	145	64.5	<u>145</u>	<u>64.5</u>	145	64.4	145	64.5	<u>145</u>	<u>64.5</u>	145	64.4
458.sjeng	407	29.8	<u>407</u>	<u>29.7</u>	407	29.7	407	29.8	<u>407</u>	<u>29.7</u>	407	29.7
462.libquantum	22.3	929	<u>22.3</u>	<u>929</u>	22.4	925	22.3	929	<u>22.3</u>	<u>929</u>	22.4	925
464.h264ref	350	63.2	<u>350</u>	<u>63.2</u>	351	63.1	313	70.7	313	70.8	<u>313</u>	<u>70.8</u>
471.omnetpp	<u>253</u>	<u>24.7</u>	254	24.7	252	24.8	240	26.1	241	25.9	<u>240</u>	<u>26.1</u>
473.astar	231	30.5	<u>231</u>	<u>30.4</u>	232	30.2	231	30.5	<u>231</u>	<u>30.4</u>	232	30.2
483.xalancbmk	<u>164</u>	<u>42.1</u>	164	42.0	163	42.3	<u>164</u>	<u>42.1</u>	164	42.0	163	42.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

To compile these binaries, the Intel Compiler was set up to generate 64-bit binaries with the command:
"ipsxe-comp-vars.bat intel64 vs2008" (shortcut provided in the Intel(r) Parallel Studio XE 2011 program folder)

Platform Notes

Sysinfo program C:\CPU200~1.17A\Docs\sysinfo
\$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c
running on CltE840F20AA52E Fri May 18 17:41:42 2012

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
Trying 'systeminfo'
OS Name       : Microsoft Windows 7 Ultimate
OS Version    : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: INTEL_
System Model   : DH77KC__
Processor(s)  : 1 Processor(s) Installed.
               [01]: Intel64 Family 6 Model 58 Stepping 9 GenuineIntel ~3401 Mhz
BIOS Version  : Intel Corp. KCH7710H.86A.0069.2012.0224.1825, 2/24/2012
Total Physical Memory: 8,090 MB
```

```
Trying 'wmic cpu get /value'
DeviceID      : CPU0
L2CacheSize  : 1024
L3CacheSize  : 6144
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 51.1

Intel DH77KC motherboard (Intel Core i5-3570)

SPECint_base2006 = 48.5

CPU2006 license: 13

Test date: May-2012

Test sponsor: Intel Corporation

Hardware Availability: Apr-2012

Tested by: Intel Corporation

Software Availability: Apr-2011

Platform Notes (Continued)

MaxClockSpeed : 3401
Name : Intel(R) Core(TM) i5-3570 CPU @ 3.40GHz
NumberOfCores : 4
NumberOfLogicalProcessors: 4

(End of data from sysinfo program)

Component Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply

General Notes

OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter
Binaries compiled on a system with 1x Intel Core i7-860 CPU
+ 8GB memory using Windows 7 Enterprise 64-bit

Base Compiler Invocation

C benchmarks:
icl -Qvc9 -Qstd=c99

C++ benchmarks:
icl -Qvc9

Base Portability Flags

400.perlbench: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64_X64
-DSPEC_CPU_NO_NEED_VA_COPY
401.bzip2: -DSPEC_CPU_P64
403.gcc: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
429.mcf: -DSPEC_CPU_P64
445.gobmk: -DSPEC_CPU_P64
456.hmmer: -DSPEC_CPU_P64
458.sjeng: -DSPEC_CPU_P64
462.libquantum: -DSPEC_CPU_P64
464.h264ref: -DSPEC_CPU_P64 -DWIN32 -DSPEC_CPU_NO_INTTYPES
471.omnetpp: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
473.astar: -DSPEC_CPU_P64
483.xalancbmk: -DSPEC_CPU_P64 -Qoption, cpp, --no_wchar_t_keyword



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 51.1

Intel DH77KC motherboard (Intel Core i5-3570)

SPECint_base2006 = 48.5

CPU2006 license: 13

Test date: May-2012

Test sponsor: Intel Corporation

Hardware Availability: Apr-2012

Tested by: Intel Corporation

Software Availability: Apr-2011

Base Optimization Flags

C benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel -Qauto-ilp32 /F512000000

C++ benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features -Qauto-ilp32 /F512000000 shlw64M.lib -link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:

icl -Qvc9 -Qstd=c99

C++ benchmarks:

icl -Qvc9

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

400.perlbench: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch -Qauto-ilp32 /F512000000 shlw64M.lib -link /FORCE:MULTIPLE

401.bzips2: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias -Qauto-ilp32 /F512000000

403.gcc: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qauto-ilp32 /F512000000

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 51.1

Intel DH77KC motherboard (Intel Core i5-3570)

SPECint_base2006 = 48.5

CPU2006 license: 13

Test date: May-2012

Test sponsor: Intel Corporation

Hardware Availability: Apr-2012

Tested by: Intel Corporation

Software Availability: Apr-2011

Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O2 -Qprec-div- -Qansi-alias -Qauto-ilp32 /F512000000

456.hmmer: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O3 -Qprec-div- -Qunroll2 -Qansi-alias -Qauto-ilp32
/F512000000

C++ benchmarks:

471.omnetpp: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O3 -Qprec-div- -Qansi-alias
-Qopt-ra-region-strategy=block -Qauto-ilp32 /F512000000
shlw64M.lib -link /FORCE:MULTIPLE

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-windows.20120117.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-windows.20120117.xml>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 51.1

Intel DH77KC motherboard (Intel Core i5-3570)

SPECint_base2006 = 48.5

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: May-2012

Hardware Availability: Apr-2012

Software Availability: Apr-2011

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Jul 24 09:27:15 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 18 July 2012.