



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

SPECint®2006 = 44.9

Intel DH77KC motherboard (Intel Core i5-3570T)

SPECint\_base2006 = 42.3

CPU2006 license: 13


Test date: May-2012

Test sponsor: Intel Corporation

Hardware Availability: Apr-2012

Tested by: Intel Corporation

Software Availability: Apr-2011



### Hardware

CPU Name: Intel Core i5-3570T  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.30 GHz  
 CPU MHz: 2300  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 6 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 8 GB (2 x 4 GB 2Rx4 PC3-12800U-11)  
 Disk Subsystem: 1 TB Seagate SATA, 7200 RPM  
 Other Hardware: None

### Software

Operating System: Microsoft Windows 7 Ultimate (64-bit) 6.1.7601 Service Pack 1 Build 7601  
 Compiler: C/C++: Version 12.1.0.229 of Intel C++ Studio XE for Windows;  
 Libraries: Version 15.00.30729.01 of Microsoft Visual Studio 2008 Professional SP1  
 Auto Parallel: Yes  
 File System: NTFS  
 System State: Default  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: SmartHeap Library Version 9.01 from <http://www.microquill.com/>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 44.9

Intel DH77KC motherboard (Intel Core i5-3570T)

SPECint\_base2006 = 42.3

CPU2006 license: 13

Test date: May-2012

Test sponsor: Intel Corporation

Hardware Availability: Apr-2012

Tested by: Intel Corporation

Software Availability: Apr-2011

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	<b>365</b>	<b>26.8</b>	364	26.8	365	26.8	278	35.2	279	35.0	<b>278</b>	<b>35.1</b>
401.bzip2	429	22.5	428	22.5	<b>429</b>	<b>22.5</b>	417	23.2	<b>417</b>	<b>23.2</b>	417	23.2
403.gcc	<b>299</b>	<b>26.9</b>	299	27.0	299	26.9	282	28.6	<b>282</b>	<b>28.6</b>	283	28.5
429.mcf	142	64.5	<b>142</b>	<b>64.3</b>	142	64.2	142	64.5	<b>142</b>	<b>64.3</b>	142	64.2
445.gobmk	458	22.9	458	22.9	<b>458</b>	<b>22.9</b>	397	26.4	<b>397</b>	<b>26.4</b>	397	26.4
456.hammer	<b>167</b>	<b>55.8</b>	167	55.9	168	55.7	<b>167</b>	<b>55.8</b>	167	55.9	168	55.7
458.sjeng	<b>465</b>	<b>26.0</b>	464	26.1	465	26.0	<b>465</b>	<b>26.0</b>	464	26.1	465	26.0
462.libquantum	26.0	797	<b>26.0</b>	<b>797</b>	26.0	797	26.0	797	<b>26.0</b>	<b>797</b>	26.0	797
464.h264ref	<b>435</b>	<b>50.8</b>	435	50.9	435	50.8	362	61.2	362	61.2	<b>362</b>	<b>61.2</b>
471.omnetpp	270	23.2	270	23.2	<b>270</b>	<b>23.2</b>	<b>256</b>	<b>24.4</b>	256	24.4	257	24.4
473.astar	<b>262</b>	<b>26.8</b>	262	26.8	264	26.6	<b>262</b>	<b>26.8</b>	262	26.8	264	26.6
483.xalancbmk	<b>186</b>	<b>37.1</b>	187	37.0	186	37.2	<b>186</b>	<b>37.1</b>	187	37.0	186	37.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

To compile these binaries, the Intel Compiler was set up to generate 64-bit binaries with the command:  
"ipsxe-comp-vars.bat intel64 vs2008" (shortcut provided in the Intel(r) Parallel Studio XE 2011 program folder)

## Platform Notes

Sysinfo program C:\CPU200~1.17A\Docs\sysinfo  
\$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c  
running on CltE840F20A9F08 Tue May 15 15:56:56 2012

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:  
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
Trying 'systeminfo'
OS Name       : Microsoft Windows 7 Ultimate
OS Version    : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: INTEL_
System Model   : DH77KC__
Processor(s)  : 1 Processor(s) Installed.
               [01]: Intel64 Family 6 Model 58 Stepping 9 GenuineIntel ~2301 Mhz
BIOS Version  : Intel Corp. KCH7710H.86A.0069.2012.0224.1825, 2/24/2012
Total Physical Memory: 8,090 MB
```

```
Trying 'wmic cpu get /value'
DeviceID      : CPU0
L2CacheSize  : 1024
L3CacheSize  : 6144
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 44.9

Intel DH77KC motherboard (Intel Core i5-3570T)

SPECint\_base2006 = 42.3

CPU2006 license: 13

Test date: May-2012

Test sponsor: Intel Corporation

Hardware Availability: Apr-2012

Tested by: Intel Corporation

Software Availability: Apr-2011

## Platform Notes (Continued)

MaxClockSpeed : 2301  
Name : Intel(R) Core(TM) i5-3570T CPU @ 2.30GHz  
NumberOfCores : 4  
NumberOfLogicalProcessors: 4

(End of data from sysinfo program)

## Component Notes

Tested systems can be used with Shin-G ATX case,  
PC Power and Cooling 1200W power supply

## General Notes

OMP\_NUM\_THREADS set to number of processors cores  
KMP\_AFFINITY set to granularity=fine,scatter  
Binaries compiled on a system with 1x Intel Core i7-860 CPU  
+ 8GB memory using Windows 7 Enterprise 64-bit

## Base Compiler Invocation

C benchmarks:  
icl -Qvc9 -Qstd=c99

C++ benchmarks:  
icl -Qvc9

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_WIN64\_X64  
-DSPEC\_CPU\_NO\_NEED\_VA\_COPY  
401.bzip2: -DSPEC\_CPU\_P64  
403.gcc: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_WIN64  
429.mcf: -DSPEC\_CPU\_P64  
445.gobmk: -DSPEC\_CPU\_P64  
456.hmmer: -DSPEC\_CPU\_P64  
458.sjeng: -DSPEC\_CPU\_P64  
462.libquantum: -DSPEC\_CPU\_P64  
464.h264ref: -DSPEC\_CPU\_P64 -DWIN32 -DSPEC\_CPU\_NO\_INTTYPES  
471.omnetpp: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_WIN64  
473.astar: -DSPEC\_CPU\_P64  
483.xalancbmk: -DSPEC\_CPU\_P64 -Qoption,cpp,--no\_wchar\_t\_keyword



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 44.9

Intel DH77KC motherboard (Intel Core i5-3570T)

SPECint\_base2006 = 42.3

CPU2006 license: 13

Test date: May-2012

Test sponsor: Intel Corporation

Hardware Availability: Apr-2012

Tested by: Intel Corporation

Software Availability: Apr-2011

## Base Optimization Flags

C benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel -Qauto-ilp32 /F512000000

C++ benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features -Qauto-ilp32 /F512000000 shlw64M.lib -link /FORCE:MULTIPLE

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks:

icl -Qvc9 -Qstd=c99

C++ benchmarks:

icl -Qvc9

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

400.perlbench: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch -Qauto-ilp32 /F512000000 shlw64M.lib -link /FORCE:MULTIPLE

401.bzip2: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias -Qauto-ilp32 /F512000000

403.gcc: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo -O3 -Qprec-div- -Qauto-ilp32 /F512000000

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 44.9

Intel DH77KC motherboard (Intel Core i5-3570T)

SPECint\_base2006 = 42.3

CPU2006 license: 13

Test date: May-2012

Test sponsor: Intel Corporation

Hardware Availability: Apr-2012

Tested by: Intel Corporation

Software Availability: Apr-2011

## Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo  
-O2 -Qprec-div- -Qansi-alias -Qauto-ilp32 /F512000000

456.hmmer: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo  
-O3 -Qprec-div- -Qunroll2 -Qansi-alias -Qauto-ilp32  
/F512000000

C++ benchmarks:

471.omnetpp: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo  
-O3 -Qprec-div- -Qansi-alias  
-Qopt-ra-region-strategy=block -Qauto-ilp32 /F512000000  
shlw64M.lib -link /FORCE:MULTIPLE

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-windows.20120117.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-windows.20120117.xml>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 44.9

Intel DH77KC motherboard (Intel Core i5-3570T)

SPECint\_base2006 = 42.3

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: May-2012

Hardware Availability: Apr-2012

Software Availability: Apr-2011

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Thu Jul 24 09:25:31 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 18 July 2012.