



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ACTION S.A.**

**SPECint®\_rate2006 = 223**

ACTINA SOLAR 210 S5 (Intel Xeon E5-2630)

**SPECint\_rate\_base2006 = 214**

CPU2006 license: 9008


**Test date:** Oct-2012

**Test sponsor:** ACTION S.A.

**Hardware Availability:** Mar-2012

**Tested by:** ACTION S.A.

**Software Availability:** Feb-2012



**SPECint\_rate\_base2006 = 214**

**SPECint\_rate2006 = 223**

## Hardware

CPU Name: Intel Xeon E5-2630  
CPU Characteristics: Intel Turbo Boost Technology up to 2.80 GHz  
CPU MHz: 2300  
FPU: Integrated  
CPU(s) enabled: 6 cores, 1 chip, 6 cores/chip, 2 threads/core  
CPU(s) orderable: 1,2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core  
L3 Cache: 15 MB I+D on chip per chip  
Other Cache: None  
Memory: 64 GB (8 x 8 GB 2Rx4 PC3-12800R-11, ECC, running at 1333 MHz and CL9)  
Disk Subsystem: 1 x 2 TB SATA, 7200 RPM  
Other Hardware: None

## Software

Operating System: SUSE Linux Enterprise Server 11 SP2 (x86\_64) 3.0.13-0.27-default  
Compiler: C/C++: Version 12.1.0.225 of Intel C++ Studio XE for Linux  
Auto Parallel: No  
File System: ext3  
System State: Run level 3 (multi-user)  
Base Pointers: 32-bit  
Peak Pointers: 32/64-bit  
Other Software: Microquill SmartHeap V9.01



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.	<b>SPECint_rate2006 =</b>	<b>223</b>
ACTINA SOLAR 210 S5 (Intel Xeon E5-2630)	<b>SPECint_rate_base2006 =</b>	<b>214</b>
CPU2006 license: 9008	Test date:	Oct-2012
Test sponsor: ACTION S.A.	Hardware Availability:	Mar-2012
Tested by: ACTION S.A.	Software Availability:	Feb-2012

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	12	<b>762</b>	<b>154</b>	761	154	763	154	12	<b>650</b>	<b>180</b>	651	180	647	181
401.bzip2	12	<b>968</b>	<b>120</b>	975	119	963	120	12	<b>932</b>	<b>124</b>	937	124	931	124
403.gcc	12	549	176	552	175	<b>551</b>	<b>175</b>	12	<b>552</b>	<b>175</b>	552	175	553	175
429.mcf	12	321	341	<b>321</b>	<b>341</b>	321	341	12	321	341	<b>321</b>	<b>341</b>	321	341
445.gobmk	12	816	154	806	156	<b>808</b>	<b>156</b>	12	804	157	790	159	<b>796</b>	<b>158</b>
456.hammer	12	431	260	429	261	<b>431</b>	<b>260</b>	12	358	313	357	313	<b>357</b>	<b>313</b>
458.sjeng	12	<b>941</b>	<b>154</b>	945	154	939	155	12	<b>905</b>	<b>161</b>	907	160	891	163
462.libquantum	12	201	1240	<b>201</b>	<b>1240</b>	201	1240	12	201	1240	<b>201</b>	<b>1240</b>	201	1240
464.h264ref	12	<b>976</b>	<b>272</b>	975	272	989	269	12	993	268	970	274	<b>989</b>	<b>269</b>
471.omnetpp	12	556	135	555	135	<b>556</b>	<b>135</b>	12	<b>524</b>	<b>143</b>	525	143	524	143
473.astar	12	654	129	<b>655</b>	<b>129</b>	655	129	12	654	129	<b>655</b>	<b>129</b>	655	129
483.xalancbmk	12	362	229	<b>360</b>	<b>230</b>	360	230	12	362	229	<b>360</b>	<b>230</b>	360	230

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The taskset mechanism was used to bind copies to processors. The config file option 'submit' was used to generate taskset commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

```
Sysinfo program /cpu2006.1.2/config/sysinfo.rev6800
$Rev: 6800 $ $Date::: 2011-10-11 #$
running on linux-k141 Mon Sep 10 22:32:34 2012
```

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name : Intel(R) Xeon(R) CPU E5-2630 0 @ 2.30GHz
  1 "physical id"s (chips)
  12 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
  cpu cores : 6
  siblings  : 12
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.	<b>SPECint_rate2006 =</b>	<b>223</b>
ACTINA SOLAR 210 S5 (Intel Xeon E5-2630)	<b>SPECint_rate_base2006 =</b>	<b>214</b>
<b>CPU2006 license:</b> 9008	<b>Test date:</b>	Oct-2012
<b>Test sponsor:</b> ACTION S.A.	<b>Hardware Availability:</b>	Mar-2012
<b>Tested by:</b> ACTION S.A.	<b>Software Availability:</b>	Feb-2012

## Platform Notes (Continued)

```
physical 0: cores 0 1 2 3 4 5
cache size : 15360 KB

From /proc/meminfo
MemTotal:       65951348 kB
HugePages_Total:        0
Hugepagesize:     2048 kB

/usr/bin/lsb_release -d
SUSE Linux Enterprise Server 11 (x86_64)

From /etc/*release* /etc/*version*
SuSE-release:
      SUSE Linux Enterprise Server 11 (x86_64)
VERSION = 11
PATCHLEVEL = 2

uname -a:
Linux linux-k141 3.0.13-0.27-default #1 SMP Wed Feb 15 13:33:49 UTC 2012
(d73692b) x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Sep 10 22:31 last=S

SPEC is set to: /cpu2006.1.2
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sda2        ext3  1.8T   19G  1.8T   1%  /


Additional information from dmidecode:

(End of data from sysinfo program)
```

## General Notes

Environment variables set by runspec before the start of the run:  
LD\_LIBRARY\_PATH = "/cpu2006.1.2/libs/32:/cpu2006.1.2/libs/64"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB  
memory using RHEL5.5

## Base Compiler Invocation

C benchmarks:  
icc -m32

C++ benchmarks:  
icpc -m32



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.	<b>SPECint_rate2006 =</b>	<b>223</b>
ACTINA SOLAR 210 S5 (Intel Xeon E5-2630)	<b>SPECint_rate_base2006 =</b>	<b>214</b>
<b>CPU2006 license:</b> 9008	<b>Test date:</b>	Oct-2012
<b>Test sponsor:</b> ACTION S.A.	<b>Hardware Availability:</b>	Mar-2012
<b>Tested by:</b> ACTION S.A.	<b>Software Availability:</b>	Feb-2012

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:  
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3

C++ benchmarks:  
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3  
-Wl,-z,muldefs -L/smarterheap -lsmarterheap

## Base Other Flags

C benchmarks:  
403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):  
icc -m32

400.perlbench: icc -m64

401.bzip2: icc -m64

456.hmmmer: icc -m64

458.sjeng: icc -m64

C++ benchmarks:  
icpc -m32

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
401.bzip2: -DSPEC\_CPU\_LP64  
456.hmmmer: -DSPEC\_CPU\_LP64  
458.sjeng: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.	<b>SPECint_rate2006 =</b>	<b>223</b>
ACTINA SOLAR 210 S5 (Intel Xeon E5-2630)	<b>SPECint_rate_base2006 =</b>	<b>214</b>
<b>CPU2006 license:</b> 9008	<b>Test date:</b>	Oct-2012
<b>Test sponsor:</b> ACTION S.A.	<b>Hardware Availability:</b>	Mar-2012
<b>Tested by:</b> ACTION S.A.	<b>Software Availability:</b>	Feb-2012

## Peak Portability Flags (Continued)

462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

```
400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
               -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
               -auto-ilp32

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
            -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
            -opt-prefetch -auto-ilp32 -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div

429.mcf: basepeak = yes

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)
            -ansi-alias -opt-mem-layout-trans=3

456.hmmmer: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
            -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
            -unroll4 -auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
               -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
               -unroll2 -ansi-alias
```

C++ benchmarks:

```
471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
               -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
               -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs
               -L/smartheap -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes
```



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.	<b>SPECint_rate2006 =</b>	<b>223</b>
ACTINA SOLAR 210 S5 (Intel Xeon E5-2630)	<b>SPECint_rate_base2006 =</b>	<b>214</b>
<b>CPU2006 license:</b> 9008	<b>Test date:</b>	Oct-2012
<b>Test sponsor:</b> ACTION S.A.	<b>Hardware Availability:</b>	Mar-2012
<b>Tested by:</b> ACTION S.A.	<b>Software Availability:</b>	Feb-2012

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Thu Jul 24 13:52:42 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 23 October 2012.