



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

SPECfp®_rate2006 = 381

Cisco UCS C260 M2 (Intel Xeon E7-2870, 2.40 GHz)

SPECfp_rate_base2006 = 373

CPU2006 license: 9019


Test date: Oct-2012

Test sponsor: Cisco Systems

Hardware Availability: Jun-2011

Tested by: Cisco Systems

Software Availability: Dec-2011



Hardware

CPU Name: Intel Xeon E7-2870
 CPU Characteristics: Intel Turbo Boost Technology up to 2.80 GHz
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 20 cores, 2 chips, 10 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux Server release 6.2 (Santiago)
 2.6.32-220.el6.x86_64
 Compiler: C/C++: Version 12.1.0.225 of Intel C++ Studio XE for Linux
 Auto Parallel: No
 File System: ext4
 System State: Run level 3 (multi-user)
 Base Pointers: 32-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

SPECfp_rate2006 = **381**

Cisco UCS C260 M2 (Intel Xeon E7-2870, 2.40 GHz)

SPECfp_rate_base2006 = **373**

CPU2006 license: 9019

Test date: Oct-2012

Test sponsor: Cisco Systems

Hardware Availability: Jun-2011

Tested by: Cisco Systems

Software Availability: Dec-2011

L3 Cache: 30 MB I+D on chip per chip
Other Cache: None
Memory: 512 GB (32 x 16 GB 4Rx4 PC3-8500R-9, ECC)
Disk Subsystem: 1 X 146 GB 15000 RPM SAS
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: Microquill SmartHeap V9.01

Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---------------|--------|-------------|------------|-------------|------------|------------|------------|--------|-------------|------------|-------------|------------|-------------|------------|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 40 | 1859 | 292 | 1862 | 292 | 1858 | 293 | 40 | 1859 | 292 | 1862 | 292 | 1858 | 293 |
| 416.gamess | 40 | 1895 | 413 | 1882 | 416 | 1915 | 409 | 40 | 1839 | 426 | 1859 | 421 | 1858 | 422 |
| 433.milc | 40 | 1202 | 306 | 1202 | 305 | 1202 | 306 | 40 | 1204 | 305 | 1204 | 305 | 1204 | 305 |
| 434.zeusmp | 40 | 873 | 417 | 863 | 422 | 867 | 420 | 40 | 873 | 417 | 863 | 422 | 867 | 420 |
| 435.gromacs | 40 | 736 | 388 | 737 | 387 | 735 | 388 | 40 | 731 | 391 | 730 | 391 | 730 | 391 |
| 436.cactusADM | 40 | 1132 | 422 | 1132 | 422 | 1115 | 429 | 40 | 1132 | 422 | 1132 | 422 | 1115 | 429 |
| 437.leslie3d | 40 | 1767 | 213 | 1767 | 213 | 1766 | 213 | 40 | 1767 | 213 | 1769 | 213 | 1765 | 213 |
| 444.namd | 40 | 873 | 368 | 878 | 365 | 875 | 366 | 40 | 864 | 371 | 857 | 374 | 857 | 374 |
| 447.dealII | 40 | 651 | 702 | 651 | 703 | 654 | 700 | 40 | 651 | 702 | 651 | 703 | 654 | 700 |
| 450.soplex | 40 | 1358 | 246 | 1356 | 246 | 1356 | 246 | 40 | 1243 | 268 | 1243 | 268 | 1245 | 268 |
| 453.povray | 40 | 383 | 556 | 377 | 565 | 376 | 566 | 40 | 326 | 652 | 326 | 652 | 324 | 656 |
| 454.calculix | 40 | 678 | 487 | 677 | 488 | 679 | 486 | 40 | 678 | 487 | 677 | 488 | 679 | 486 |
| 459.GemsFDTD | 40 | 2019 | 210 | 2019 | 210 | 2020 | 210 | 40 | 2019 | 210 | 2019 | 210 | 2020 | 210 |
| 465.tonto | 40 | 844 | 466 | 834 | 472 | 826 | 476 | 40 | 799 | 493 | 800 | 492 | 801 | 491 |
| 470.lbm | 40 | 1308 | 420 | 1308 | 420 | 1309 | 420 | 40 | 1308 | 420 | 1308 | 420 | 1309 | 420 |
| 481.wrf | 40 | 1229 | 364 | 1226 | 365 | 1234 | 362 | 40 | 1205 | 371 | 1206 | 371 | 1206 | 370 |
| 482.sphinx3 | 40 | 2119 | 368 | 2119 | 368 | 2122 | 367 | 40 | 2046 | 381 | 2046 | 381 | 2048 | 381 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

Sysinfo program /opt/cpul2.1/config/sysinfo.rev6800
\$Rev: 6800 \$ \$Date:: 2011-10-11 #\$ 6f2ebdff5032aaa42e583f96b07f99d3
running on localhost.localdomain Wed Oct 3 12:20:16 2012

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

SPECfp_rate2006 = 381

Cisco UCS C260 M2 (Intel Xeon E7-2870, 2.40 GHz)

SPECfp_rate_base2006 = 373

CPU2006 license: 9019

Test date: Oct-2012

Test sponsor: Cisco Systems

Hardware Availability: Jun-2011

Tested by: Cisco Systems

Software Availability: Dec-2011

Platform Notes (Continued)

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see: <http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```

From /proc/cpuinfo
model name      : Intel(R) Xeon(R) CPU E7- 2870 @ 2.40GHz
 2 "physical id"s (chips)
 40 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
  cpu cores    : 10
  siblings     : 20
  physical 0   : cores 0 1 2 8 9 16 17 18 24 25
  physical 1   : cores 0 1 2 8 9 16 17 18 24 25
cache size    : 30720 KB

```

```

From /proc/meminfo
MemTotal:      529155220 kB
HugePages_Total: 0
Hugepagesize:  2048 kB

```

```

/usr/bin/lsb_release -d
Red Hat Enterprise Linux Server release 6.2 (Santiago)

```

```

From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.2 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.2 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server

```

```

uname -a:
Linux localhost.localdomain 2.6.32-220.el6.x86_64 #1 SMP Wed Nov 9 08:03:13
EST 2011 x86_64 x86_64 x86_64 GNU/Linux

```

run-level 3 Oct 3 09:41

```

SPEC is set to: /opt/cpul2.1
Filesystem      Type      Size  Used Avail Use% Mounted on
/dev/sdal       ext4      134G  15G  113G  12% /

```

Additional information from dmidecode:

(End of data from sysinfo program)

General Notes

Environment variables set by runspec before the start of the run:

LD_LIBRARY_PATH = "/opt/cpul2.1/libs/32:/opt/cpul2.1/libs/64"

Intel HT Technology=enable

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RHEL5.5

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

SPECfp_rate2006 = 381

Cisco UCS C260 M2 (Intel Xeon E7-2870, 2.40 GHz)

SPECfp_rate_base2006 = 373

CPU2006 license: 9019

Test date: Oct-2012

Test sponsor: Cisco Systems

Hardware Availability: Jun-2011

Tested by: Cisco Systems

Software Availability: Dec-2011

General Notes (Continued)

Transparent Huge Pages disabled with:
 echo never > /sys/kernel/mm/redhat_transparent_hugepage/enabled
 Filesystem page cache cleared with:
 echo 1> /proc/sys/vm/drop_caches
 runspec command invoked through numactl i.e.:
 numactl --interleave=all runspec <etc>

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64 -nofor_main
 436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64
 450.soplex: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -nofor_main
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
 482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

SPECfp_rate2006 = 381

Cisco UCS C260 M2 (Intel Xeon E7-2870, 2.40 GHz)

SPECfp_rate_base2006 = 373

CPU2006 license: 9019

Test date: Oct-2012

Test sponsor: Cisco Systems

Hardware Availability: Jun-2011

Tested by: Cisco Systems

Software Availability: Dec-2011

Base Optimization Flags (Continued)

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

Fortran benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m64

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc -m64

450.soplex: icpc -m32

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

SPECfp_rate2006 = 381

Cisco UCS C260 M2 (Intel Xeon E7-2870, 2.40 GHz)

SPECfp_rate_base2006 = 373

CPU2006 license: 9019

Test date: Oct-2012

Test sponsor: Cisco Systems

Hardware Availability: Jun-2011

Tested by: Cisco Systems

Software Availability: Dec-2011

Peak Portability Flags (Continued)

481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -static -auto-ilp32

470.lbm: basepeak = yes

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -opt-mem-layout-trans=3
-unroll2

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -fno-alias -auto-ilp32

447.dealII: basepeak = yes

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -opt-malloc-options=3

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

459.GemsFDTD: basepeak = yes

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -auto
-inline-calloc -opt-malloc-options=3

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

SPECfp_rate2006 = 381

Cisco UCS C260 M2 (Intel Xeon E7-2870, 2.40 GHz)

SPECfp_rate_base2006 = 373

CPU2006 license: 9019

Test date: Oct-2012

Test sponsor: Cisco Systems

Hardware Availability: Jun-2011

Tested by: Cisco Systems

Software Availability: Dec-2011

Peak Optimization Flags (Continued)

Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -opt-prefetch -static -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: -xSSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20120425.html>

<http://www.spec.org/cpu2006/flags/Cisco-Platform-Settings-V1.2.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20120425.xml>

<http://www.spec.org/cpu2006/flags/Cisco-Platform-Settings-V1.2.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Thu Jul 24 14:00:08 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 7 November 2012.