



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## ACTION S.A.

ACTINA SOLAR 210 X5 (Intel Xeon E5-2609 v2, 2.50 GHz)

**SPECint®\_rate2006 = 248**

**SPECint\_rate\_base2006 = 240**

CPU2006 license: 9008


Test sponsor: ACTION S.A.

Tested by: ACTION S.A.

Test date: Apr-2014

Hardware Availability: Oct-2013

Software Availability: Sep-2013



### Hardware

CPU Name: Intel Xeon E5-2609 v2  
 CPU Characteristics:  
 CPU MHz: 2500  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 10 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 128 GB (16 x 8 GB 2Rx4 PC3-14900R-13, ECC, running at 1333 MHz and CL9)  
 Disk Subsystem: 1 x 240 GB SATA II SSD  
 Other Hardware: None

### Software

Operating System: Red Hat Enterprise Linux Server release 6.4 (Santiago)  
 2.6.32-358.11.1.el6.x86\_64  
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux  
 Auto Parallel: No  
 File System: ext4  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Microquill SmartHeap V10.0



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## ACTION S.A.

ACTINA SOLAR 210 X5 (Intel Xeon E5-2609 v2, 2.50 GHz)

SPECint\_rate2006 = 248

SPECint\_rate\_base2006 = 240

CPU2006 license: 9008  
Test sponsor: ACTION S.A.  
Tested by: ACTION S.A.

Test date: Apr-2014  
Hardware Availability: Oct-2013  
Software Availability: Sep-2013

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	452	173	<b><u>452</u></b>	<b><u>173</u></b>	451	173	8	365	214	365	214	<b><u>365</u></b>	<b><u>214</u></b>
401.bzip2	8	641	120	644	120	<b><u>643</u></b>	<b><u>120</u></b>	8	624	124	<b><u>624</u></b>	<b><u>124</u></b>	626	123
403.gcc	8	333	194	<b><u>333</u></b>	<b><u>193</u></b>	334	193	8	334	193	<b><u>334</u></b>	<b><u>193</u></b>	334	193
429.mcf	8	184	396	<b><u>184</u></b>	<b><u>397</u></b>	184	398	8	184	396	<b><u>184</u></b>	<b><u>397</u></b>	184	398
445.gobmk	8	<b><u>558</u></b>	<b><u>150</u></b>	558	150	559	150	8	550	153	551	152	<b><u>550</u></b>	<b><u>153</u></b>
456.hammer	8	<b><u>235</u></b>	<b><u>318</u></b>	235	318	235	318	8	221	338	<b><u>219</u></b>	<b><u>340</u></b>	217	344
458.sjeng	8	<b><u>593</u></b>	<b><u>163</u></b>	593	163	593	163	8	576	168	<b><u>575</u></b>	<b><u>168</u></b>	575	168
462.libquantum	8	101	1640	<b><u>101</u></b>	<b><u>1640</u></b>	101	1640	8	101	1640	<b><u>101</u></b>	<b><u>1640</u></b>	101	1640
464.h264ref	8	546	324	<b><u>545</u></b>	<b><u>325</u></b>	545	325	8	533	332	<b><u>531</u></b>	<b><u>333</u></b>	530	334
471.omnetpp	8	362	138	<b><u>363</u></b>	<b><u>138</u></b>	364	137	8	356	140	<b><u>356</u></b>	<b><u>140</u></b>	356	140
473.astar	8	<b><u>400</u></b>	<b><u>141</u></b>	399	141	400	140	8	<b><u>400</u></b>	<b><u>141</u></b>	399	141	400	140
483.xalancbmk	8	190	290	191	289	<b><u>191</u></b>	<b><u>290</u></b>	8	190	290	191	289	<b><u>191</u></b>	<b><u>290</u></b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

### Bios Settings:

System Acoustic and Performance Configuration = Performance  
Select Memory RAS Configuration = Maximum Performance  
Intel(R) Turbo Boost Technology = Enabled  
Processor C3 = Disabled  
Processor C6 = Disabled

Sysinfo program /cpu2006.1.2/config/sysinfo.rev6818  
\$Rev: 6818 \$ \$Date:: 2012-07-17 #\$ e86d102572650a6e4d596a3cee98f191  
running on localhost.localdomain Tue Apr 1 10:16:16 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## ACTION S.A.

**SPECint\_rate2006 = 248**

ACTINA SOLAR 210 X5 (Intel Xeon E5-2609 v2, 2.50 GHz)

**SPECint\_rate\_base2006 = 240**

**CPU2006 license:** 9008

**Test date:** Apr-2014

**Test sponsor:** ACTION S.A.

**Hardware Availability:** Oct-2013

**Tested by:** ACTION S.A.

**Software Availability:** Sep-2013

### Platform Notes (Continued)

```

model name : Intel(R) Xeon(R) CPU E5-2609 v2 @ 2.50GHz
 2 "physical id"s (chips)
 8 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
  cpu cores : 4
  siblings  : 4
  physical 0: cores 0 1 2 3
  physical 1: cores 0 1 2 3
 cache size : 10240 KB

```

```

From /proc/meminfo
MemTotal:      132053000 kB
HugePages_Total:    0
Hugepagesize:    2048 kB

```

```

/usr/bin/lsb_release -d
Red Hat Enterprise Linux Server release 6.4 (Santiago)

```

```

From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server

```

```

uname -a:
Linux localhost.localdomain 2.6.32-358.11.1.el6.x86_64 #1 SMP Tue Nov 19
17:43:04 CET 2013 x86_64 x86_64 x86_64 GNU/Linux

```

run-level 3 Mar 27 14:51

```

SPEC is set to: /cpu2006.1.2
Filesystem      Type      Size      Used Avail Use% Mounted on
/dev/sdal       ext4      193G      50G  133G  28% /

```

```

Additional information from dmidecode:
BIOS Intel Corp. SE5C600.86B.02.02.0002.122320131210 12/23/2013
Memory:
 16x 8 GB
 16x Hynix HMT31GR7EFR4C-RD 8 GB 1867 MHz 2 rank

```

(End of data from sysinfo program)  
dmidecode does not properly detect memory modules  
16 modules of 8 GB were used to run the test (128 GB total).  
Memory modules operate at speed 1333 MHz while dmidecode shows 1867 MHz

### General Notes

Environment variables set by runspec before the start of the run:  
LD\_LIBRARY\_PATH = "/cpu2006.1.2/libs/32:/cpu2006.1.2/libs/64:/cpu2006.1.2/sh"

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ACTION S.A.**

**SPECint\_rate2006 = 248**

ACTINA SOLAR 210 X5 (Intel Xeon E5-2609 v2, 2.50 GHz)

**SPECint\_rate\_base2006 = 240**

**CPU2006 license:** 9008

**Test date:** Apr-2014

**Test sponsor:** ACTION S.A.

**Hardware Availability:** Oct-2013

**Tested by:** ACTION S.A.

**Software Availability:** Sep-2013

## General Notes (Continued)

Transparent Huge Pages enabled with:  
 echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled  
 Filesystem page cache cleared with:  
 echo 1> /proc/sys/vm/drop\_caches  
 runspec command invoked through numactl i.e.:  
 numactl --interleave=all runspec <etc>  
 Binaries compiled on a system with 2x Xeon E5-2650 v2 chips + 256 GB memory  
 using RedHat EL 6.4

## Base Compiler Invocation

C benchmarks:  
 icc -m32  
  
 C++ benchmarks:  
 icpc -m32

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
 462.libquantum: -DSPEC\_CPU\_LINUX  
 483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:  
 -xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3  
  
 C++ benchmarks:  
 -xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3  
 -Wl,-z,muldefs -L/cpu2006.1.2/sh -lsmartheap

## Base Other Flags

C benchmarks:  
  
 403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):  
 icc -m32

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ACTION S.A.**

ACTINA SOLAR 210 X5 (Intel Xeon E5-2609 v2, 2.50 GHz)

**SPECint\_rate2006 = 248**

**SPECint\_rate\_base2006 = 240**

**CPU2006 license:** 9008

**Test sponsor:** ACTION S.A.

**Tested by:** ACTION S.A.

**Test date:** Apr-2014

**Hardware Availability:** Oct-2013

**Software Availability:** Sep-2013

## Peak Compiler Invocation (Continued)

400.perlbench: `icc -m64`

401.bzip2: `icc -m64`

456.hmmer: `icc -m64`

458.sjeng: `icc -m64`

C++ benchmarks:

`icpc -m32`

## Peak Portability Flags

400.perlbench: `-DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64`

401.bzip2: `-DSPEC_CPU_LP64`

456.hmmer: `-DSPEC_CPU_LP64`

458.sjeng: `-DSPEC_CPU_LP64`

462.libquantum: `-DSPEC_CPU_LINUX`

483.xalancbmk: `-DSPEC_CPU_LINUX`

## Peak Optimization Flags

C benchmarks:

400.perlbench: `-xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -auto-ilp32`

401.bzip2: `-xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -opt-prefetch -auto-ilp32 -ansi-alias`

403.gcc: `-xSSE4.2 -ipo -O3 -no-prec-div`

429.mcf: `basepeak = yes`

445.gobmk: `-xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -ansi-alias -opt-mem-layout-trans=3`

456.hmmer: `-xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -auto-ilp32`

458.sjeng: `-xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -auto-ilp32`

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ACTION S.A.**

**SPECint\_rate2006 = 248**

ACTINA SOLAR 210 X5 (Intel Xeon E5-2609 v2, 2.50 GHz)

**SPECint\_rate\_base2006 = 240**

**CPU2006 license:** 9008

**Test date:** Apr-2014

**Test sponsor:** ACTION S.A.

**Hardware Availability:** Oct-2013

**Tested by:** ACTION S.A.

**Software Availability:** Sep-2013

## Peak Optimization Flags (Continued)

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs  
-L/cpu2006.1.2/sh -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>

<http://www.spec.org/cpu2006/flags/ACTION.SA-Platform-Flags-RevB-apr-2014-For-Intel-Platform.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>

<http://www.spec.org/cpu2006/flags/ACTION.SA-Platform-Flags-RevB-apr-2014-For-Intel-Platform.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Thu Jul 24 23:19:26 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 22 April 2014.