



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Cisco Systems

Cisco UCS B260 M4 (Intel Xeon E7-4870 v2, 2.30 GHz)

**SPECint\_rate2006 = 1040**

**SPECint\_rate\_base2006 = 1000**

**CPU2006 license:** 9019


**Test sponsor:** Cisco Systems

**Tested by:** Cisco Systems

**Test date:** Apr-2014

**Hardware Availability:** May-2014

**Software Availability:** Sep-2013



### Hardware

CPU Name:	Intel Xeon E7-4870 v2
CPU Characteristics:	Intel Turbo Boost Technology up to 2.90 GHz
CPU MHz:	2300
FPU:	Integrated
CPU(s) enabled:	30 cores, 2 chips, 15 cores/chip, 2 threads/core
CPU(s) orderable:	1,2 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	30 MB I+D on chip per chip
Other Cache:	None
Memory:	256 GB (32 x 8 GB 2Rx4 PC3L-12800R-11, ECC)
Disk Subsystem:	1 X 300 GB 15000 RPM SAS
Other Hardware:	None

### Software

Operating System:	Red Hat Enterprise Linux Server release 6.5 (Santiago) 2.6.32-431.el6.x86_64
Compiler:	C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux
Auto Parallel:	No
File System:	ext4
System State:	Run level 3 (multi-user)
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	Microquill SmartHeap V10.0



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Cisco Systems

Cisco UCS B260 M4 (Intel Xeon E7-4870 v2, 2.30 GHz)

**SPECint\_rate2006 = 1040**

**SPECint\_rate\_base2006 = 1000**

**CPU2006 license:** 9019

**Test date:** Apr-2014

**Test sponsor:** Cisco Systems

**Hardware Availability:** May-2014

**Tested by:** Cisco Systems

**Software Availability:** Sep-2013

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	60	736	796	730	803	<b>731</b>	<b>802</b>	60	618	948	<b>619</b>	<b>947</b>	621	944
401.bzip2	60	1137	509	1138	509	<b>1137</b>	<b>509</b>	60	1122	516	<b>1122</b>	<b>516</b>	1121	517
403.gcc	60	645	748	641	753	<b>642</b>	<b>752</b>	60	643	751	650	743	<b>649</b>	<b>744</b>
429.mcf	60	395	1380	<b>395</b>	<b>1380</b>	395	1380	60	395	1380	<b>395</b>	<b>1380</b>	395	1380
445.gobmk	60	792	795	793	794	<b>792</b>	<b>795</b>	60	774	813	761	827	<b>762</b>	<b>826</b>
456.hammer	60	389	1440	388	1440	<b>388</b>	<b>1440</b>	60	363	1540	363	1540	<b>363</b>	<b>1540</b>
458.sjeng	60	<b>927</b>	<b>783</b>	926	784	927	783	60	888	817	884	821	<b>886</b>	<b>820</b>
462.libquantum	60	<b>174</b>	<b>7130</b>	174	7140	174	7130	60	<b>174</b>	<b>7130</b>	174	7140	174	7130
464.h264ref	60	<b>991</b>	<b>1340</b>	989	1340	997	1330	60	989	1340	982	1350	<b>982</b>	<b>1350</b>
471.omnetpp	60	776	483	<b>776</b>	<b>483</b>	775	484	60	743	505	742	505	<b>742</b>	<b>505</b>
473.astar	60	752	560	<b>752</b>	<b>560</b>	749	562	60	752	560	<b>752</b>	<b>560</b>	749	562
483.xalancbmk	60	<b>388</b>	<b>1070</b>	390	1060	388	1070	60	<b>388</b>	<b>1070</b>	390	1060	388	1070

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

Intel HT Technology = Enabled  
CPU performance set to HPC  
Power Technology set to Custom  
CPU Power State C6 set to Disabled  
CPU Power State C1 Enhanced set to Disabled  
Memory RAS configuration set to Maximum Performance  
DRAM Clock Throttling Set to Performance  
Sysinfo program /opt/cpu2006-1.4/config/sysinfo.rev6818  
\$Rev: 6818 \$ \$Date:: 2012-07-17 #\\$ e86d102572650a6e4d596a3cee98f191  
running on yos Thu Apr 10 02:32:54 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:  
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo  
model name : Intel(R) Xeon(R) CPU E7-4870 v2 @ 2.30GHz  
Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Cisco Systems

Cisco UCS B260 M4 (Intel Xeon E7-4870 v2, 2.30 GHz)

**SPECint\_rate2006 = 1040**

**SPECint\_rate\_base2006 = 1000**

**CPU2006 license:** 9019

**Test date:** Apr-2014

**Test sponsor:** Cisco Systems

**Hardware Availability:** May-2014

**Tested by:** Cisco Systems

**Software Availability:** Sep-2013

## Platform Notes (Continued)

```

2 "physical id"s (chips)
 60 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
  cpu cores : 15
  siblings   : 30
  physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
  physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
cache size : 30720 KB

From /proc/meminfo
MemTotal:      263968032 kB
HugePages_Total:       0
Hugepagesize:     2048 kB

/usr/bin/lsb_release -d
 Red Hat Enterprise Linux Server release 6.5 (Santiago)

From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.5 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.5 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server

uname -a:
Linux yos 2.6.32-431.el6.x86_64 #1 SMP Sun Nov 10 22:19:54 EST 2013 x86_64
x86_64 x86_64 GNU/Linux

run-level 3 Apr 10 02:32

SPEC is set to: /opt/cpu2006-1.4
Filesystem      Type  Size  Used  Avail Use% Mounted on
/dev/sdal      ext4  275G   12G  249G   5%  /

Additional information from dmidecode:
BIOS Cisco Systems, Inc. EXM4-1.2.2.1.15.022020141613 02/20/2014
Memory:
 32x 8 GB
 32x 0xCE00 M393B1K70QB0-YK0 8 GB 1333 MHz 2 rank
 16x NO DIMM NO DIMM

(End of data from sysinfo program)

```

## General Notes

Environment variables set by runspec before the start of the run:

LD\_LIBRARY\_PATH = "/opt/cpu2006-1.4/libs/32:/opt/cpu2006-1.4/libs/64:/opt/cpu2006-1.4/sh"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4

Transparent Huge Pages enabled with:

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Cisco Systems

Cisco UCS B260 M4 (Intel Xeon E7-4870 v2, 2.30 GHz)

**SPECint\_rate2006 = 1040**

**SPECint\_rate\_base2006 = 1000**

**CPU2006 license:** 9019

**Test sponsor:** Cisco Systems

**Tested by:** Cisco Systems

**Test date:** Apr-2014

**Hardware Availability:** May-2014

**Software Availability:** Sep-2013

## General Notes (Continued)

```
echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
Filesystem page cache cleared with:
echo 1> /proc/sys/vm/drop_caches
runspec command invoked through numactl i.e.:
numactl --interleave=all runspec <etc>
```

## Base Compiler Invocation

C benchmarks:

```
icc -m32
```

C++ benchmarks:

```
icpc -m32
```

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32

462.libquantum: -DSPEC\_CPU\_LINUX

483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

```
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3
```

C++ benchmarks:

```
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3
-Wl,-z,muldefs -L/sh -lsmartheap
```

## Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

## Peak Compiler Invocation

C benchmarks (except as noted below):

```
icc -m32
```

400.perlbench: icc -m64

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Cisco Systems

Cisco UCS B260 M4 (Intel Xeon E7-4870 v2, 2.30 GHz)

**SPECint\_rate2006 = 1040**

**SPECint\_rate\_base2006 = 1000**

**CPU2006 license:** 9019

**Test sponsor:** Cisco Systems

**Tested by:** Cisco Systems

**Test date:** Apr-2014

**Hardware Availability:** May-2014

**Software Availability:** Sep-2013

## Peak Compiler Invocation (Continued)

401.bzip2: icc -m64

456.hmmmer: icc -m64

458.sjeng: icc -m64

C++ benchmarks:

icpc -m32

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64

401.bzip2: -DSPEC\_CPU\_LP64

456.hmmmer: -DSPEC\_CPU\_LP64

458.sjeng: -DSPEC\_CPU\_LP64

462.libquantum: -DSPEC\_CPU\_LINUX

483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-auto-ilp32

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32 -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div

429.mcf: basepeak = yes

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)  
-ansi-alias -opt-mem-layout-trans=3

456.hmmmer: -xSSE4.2 -ipo -O3 -no-prec-div -unroll12 -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll14 -auto-ilp32

462.libquantum: basepeak = yes

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Cisco Systems

Cisco UCS B260 M4 (Intel Xeon E7-4870 v2, 2.30 GHz)

**SPECint\_rate2006 = 1040**

**SPECint\_rate\_base2006 = 1000**

**CPU2006 license:** 9019

**Test sponsor:** Cisco Systems

**Tested by:** Cisco Systems

**Test date:** Apr-2014

**Hardware Availability:** May-2014

**Software Availability:** Sep-2013

## Peak Optimization Flags (Continued)

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll12 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs  
-L/sh -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>  
<http://www.spec.org/cpu2006/flags/Cisco-Platform-Settings-V1.2.20140311.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>  
<http://www.spec.org/cpu2006/flags/Cisco-Platform-Settings-V1.2.20140311.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Thu Jul 24 22:14:52 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 6 May 2014.