# SPEC® CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS Z170MPLUS motherboard (Intel Core i7-6700)

SPECint®_rate2006 = 235

SPECint_rate_base2006 = 226

**CPU2006 license:** 13
**Test sponsor:** Intel Corporation
**Tested by:** Intel Corporation

**Test date:** Oct-2015
**Hardware Availability:** Sep-2015
**Software Availability:** Aug-2015




## Hardware

| | |
|---|---|
| CPU Name: | Intel Core i7-6700 |
| CPU Characteristics: | Intel Turbo Boost Technology up to 4.00 GHz |
| CPU MHz: | 3400 |
| FPU: | Integrated |
| CPU(s) enabled: | 4 cores, 1 chip, 4 cores/chip, 2 threads/core |
| CPU(s) orderable: | 1 chip |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |
| L3 Cache: | 8 MB I+D on chip per chip |
| Other Cache: | None |
| Memory: | 8 GB (2 x 4 GB 2Rx4 PC4-2133P-U) |
| Disk Subsystem: | 1 TB Seagate SATA HDD, 7200 RPM |
| Other Hardware: | None |

## Software

| | |
|---|---|
| Operating System: | Microsoft Windows 10 Pro 10.0.10240 N/A Build 10240 |
| Compiler: | C/C++: Version 16.0.0.110 of Intel C++ Studio XE for Windows; Libraries: Version 18.00.30723 of Microsoft Visual Studio 2013 |
| Auto Parallel: | No |
| File System: | NTFS |
| System State: | Default |
| Base Pointers: | 32-bit |
| Peak Pointers: | 32/64-bit |
| Other Software: | SmartHeap Library Version 11.0 from http://www.microquill.com/ |

# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

ASUS Z170MPLUS motherboard (Intel Core i7-6700)

SPECint_rate2006 = 235

SPECint_rate_base2006 = 226

**CPU2006 license:** 13
**Test sponsor:** Intel Corporation
**Tested by:** Intel Corporation

**Test date:** Oct-2015
**Hardware Availability:** Sep-2015
**Software Availability:** Aug-2015

## Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 400.perlbench | 8 | 420 | 186 | 415 | 188 | **415** | **188** | 8 | **353** | **222** | 353 | 222 | 352 | 222 |
| 401.bzip2 | 8 | 687 | 113 | 682 | 113 | **684** | **113** | 8 | 678 | 114 | **676** | **114** | 674 | 114 |
| 403.gcc | 8 | **369** | **174** | 372 | 173 | 366 | 176 | 8 | **361** | **178** | 362 | 178 | 357 | 180 |
| 429.mcf | 8 | **413** | **177** | 440 | 166 | 406 | 180 | 8 | **413** | **177** | 440 | 166 | 406 | 180 |
| 445.gobmk | 8 | **503** | **166** | 503 | 167 | 504 | 166 | 8 | **490** | **171** | 489 | 172 | 490 | 171 |
| 456.hmmer | 8 | 200 | 374 | 199 | 375 | **200** | **374** | 8 | 161 | 465 | **161** | **464** | 161 | 464 |
| 458.sjeng | 8 | 561 | 173 | **561** | **173** | 560 | 173 | 8 | 559 | 174 | **559** | **174** | 559 | 173 |
| 462.libquantum | 8 | 64.7 | 2560 | 64.6 | 2570 | **64.6** | **2570** | 8 | 64.8 | 2560 | **64.9** | **2550** | 64.9 | 2550 |
| 464.h264ref | 8 | **575** | **308** | 575 | 308 | 574 | 309 | 8 | **575** | **308** | 575 | 308 | 574 | 309 |
| 471.omnetpp | 8 | 482 | 104 | **482** | **104** | 483 | 104 | 8 | 461 | 109 | **461** | **109** | 461 | 109 |
| 473.astar | 8 | **460** | **122** | 460 | 122 | 461 | 122 | 8 | 463 | 122 | 463 | 122 | **463** | **122** |
| 483.xalancbmk | 8 | 221 | 250 | 221 | 250 | **221** | **250** | 8 | 221 | 250 | 221 | 250 | **221** | **250** |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

```
To compile these binaries, the Intel Compiler 16.0 was set up to
generate 32-bit binaries with the command:
"ipsxe-comp-vars.bat ia32 vs2010" (shortcut provided in the Intel(r)
Parallel Studio XE 2016 program folder)
```

## Platform Notes

```
Sysinfo program C:\SPEC16.0/Docs/sysinfo
$Rev: 6775 $ $Date:: 2011-08-16 #$ \8787f7622badcf24e01c368b1db4377c
running on DESKTOP-C8BQEO8 Thu Oct 15 22:24:19 2015

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/cpu2006/Docs/config.html#sysinfo

Trying 'systeminfo'
OS Name       : Microsoft Windows 10 Pro
OS Version    : 10.0.10240 N/A Build 10240
System Manufacturer: System manufacturer
System Model  : System Product Name
Processor(s)  : 1 Processor(s) Installed.
     [01]: Intel64 Family 6 Model 94 Stepping 3 GenuineIntel ~3401 Mhz
BIOS Version  : American Megatrends Inc. 0408, 8/28/2015
Total Physical Memory: 8,084 MB

Trying 'wmic cpu get /value'
DeviceID      : CPU0
```

Continued on next page

## Platform Notes (Continued)

```
L2CacheSize   : 1024
L3CacheSize   : 8192
MaxClockSpeed : 3401
Name          : Intel(R) Core(TM) i7-6700 CPU @ 3.40GHz
NumberOfCores : 4
NumberOfLogicalProcessors: 8

(End of data from sysinfo program)
```

## Component Notes

```
Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply
```

## General Notes

```
Binaries compiled on a system with 1x Intel Xeon E5-2699 v3 CPU
+ 64GB memory using Windows 8.1 Enterprise 64-bit
```

# Base Compiler Invocation

C benchmarks:
```
icl -Qvc12 -Qstd=c99
```

C++ benchmarks:
```
icl -Qvc12
```

# Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DWIN32`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

# Base Optimization Flags

C benchmarks:
```
-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F256000000
```

C++ benchmarks:
```
-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features
/F256000000 shlW32M.lib            -link /FORCE:MULTIPLE
```

## Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

## Peak Compiler Invocation

C benchmarks (except as noted below):
`icl -Qvc12 -Qstd=c99`

C++ benchmarks (except as noted below):
`icl -Qvc12`

## Peak Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
456.hmmer: `-DSPEC_CPU_P64`
458.sjeng: `-DSPEC_CPU_P64`
462.libquantum: `-DSPEC_CPU_P64`
464.h264ref: `-DWIN32`
473.astar: `-DSPEC_CPU_P64`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

## Peak Optimization Flags

C benchmarks:

400.perlbench: `-QxCORE-AVX2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2)
`-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch`
`/F256000000 shlW32M.lib -link /FORCE:MULTIPLE`

401.bzip2: `-QxCORE-AVX2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2)
`-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias`
`/F256000000`

403.gcc: `-QxCORE-AVX2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2)
`-Qipo -O3 -Qprec-div- -Qopt-prefetch /F256000000`

429.mcf: `basepeak = yes`

445.gobmk: `-QxCORE-AVX2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2)
`-Qipo -O2 -Qprec-div- -Qansi-alias /F256000000`

464.h264ref: `basepeak = yes`

Continued on next page

## Peak Optimization Flags (Continued)

C++ benchmarks:

471.omnetpp: `-QxCORE-AVX2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-ra-region-strategy=block /F256000000 shlW32M.lib -link /FORCE:MULTIPLE`

483.xalancbmk: `basepeak = yes`

## Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.xml`


SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Nov 17 19:18:11 2015 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 17 November 2015.