



SPEC® CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECint®2006 = 66.3

ASUS Z97M-PLUS Motherboard (Intel Core i7-5775C)

SPECint_base2006 = 64.1

CPU2006 license: 13


Test date: Oct-2015

Test sponsor: Intel Corporation

Hardware Availability: Jun-2015

Tested by: Intel Corporation

Software Availability: Aug-2015



Hardware

CPU Name: Intel Core i7-5775C
 CPU Characteristics: Intel Turbo Boost Technology up to 3.70 GHz
 CPU MHz: 3300
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip, 2 threads/core
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 6 MB I+D on chip per chip
 Other Cache: None
 Memory: 8 GB (2 x 4 GB 2Rx4 PC3-14900U-10, running at 1600MHz)
 Disk Subsystem: 1 TB Seagate SATA HDD, 7200 RPM
 Other Hardware: None

Software

Operating System: Microsoft Windows 10 Pro
 10.0.10240 N/A Build 10240
 Compiler: C/C++: Version 16.0.0.110 of Intel C++ Studio XE for Windows;
 Libraries: Version 18.00.30723 of Microsoft Visual Studio 2013
 Auto Parallel: Yes
 File System: NTFS
 System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 11.0 from <http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECint2006 = 66.3

ASUS Z97M-PLUS Motherboard (Intel Core i7-5775C)

SPECint_base2006 = 64.1

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Oct-2015
Hardware Availability: Jun-2015
Software Availability: Aug-2015

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	252	38.8	<u>253</u>	<u>38.7</u>	253	38.6	205	47.7	204	47.8	<u>205</u>	<u>47.8</u>
401.bzip2	355	27.2	355	27.2	<u>355</u>	<u>27.2</u>	347	27.8	<u>347</u>	<u>27.8</u>	347	27.8
403.gcc	212	38.0	211	38.1	<u>212</u>	<u>38.1</u>	201	40.0	201	40.1	<u>201</u>	<u>40.1</u>
429.mcf	119	76.5	<u>119</u>	<u>76.6</u>	118	77.5	119	76.5	<u>119</u>	<u>76.6</u>	118	77.5
445.gobmk	340	30.9	<u>340</u>	<u>30.8</u>	340	30.8	323	32.5	322	32.5	<u>322</u>	<u>32.5</u>
456.hammer	102	91.6	102	91.2	<u>102</u>	<u>91.5</u>	102	91.6	102	91.2	<u>102</u>	<u>91.5</u>
458.sjeng	<u>352</u>	<u>34.4</u>	351	34.4	352	34.4	<u>352</u>	<u>34.4</u>	351	34.4	352	34.4
462.libquantum	9.60	2160	<u>9.60</u>	<u>2160</u>	9.60	2160	9.60	2160	<u>9.60</u>	<u>2160</u>	9.60	2160
464.h264ref	<u>288</u>	<u>76.9</u>	288	76.9	288	77.0	<u>288</u>	<u>76.9</u>	288	76.9	288	77.0
471.omnetpp	152	41.1	<u>152</u>	<u>41.1</u>	152	41.1	144	43.5	<u>144</u>	<u>43.6</u>	143	43.6
473.astar	194	36.2	193	36.4	<u>194</u>	<u>36.3</u>	194	36.2	193	36.4	<u>194</u>	<u>36.3</u>
483.xalancbmk	105	65.5	105	65.8	<u>105</u>	<u>65.7</u>	105	65.5	105	65.8	<u>105</u>	<u>65.7</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

To compile these binaries, the Intel Compiler 16.0 was set up to generate 64-bit binaries with the command:
"psxevars.bat intel64" (shortcut provided in the Intel(r) Parallel Studio XE 2016 program folder)

Platform Notes

Sysinfo program C:\SPEC16.0/Docs/sysinfo
\$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c
running on DESKTOP-K1NMJC0 Tue Oct 13 14:28:09 2015

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
Trying 'systeminfo'
OS Name       : Microsoft Windows 10 Pro
OS Version    : 10.0.10240 N/A Build 10240
System Manufacturer: ASUS
System Model   : All Series
Processor(s)  : 1 Processor(s) Installed.
               [01]: Intel64 Family 6 Model 71 Stepping 1 GenuineIntel ~3300 Mhz
BIOS Version  : American Megatrends Inc. 2802, 5/19/2015
Total Physical Memory: 8,063 MB
```

```
Trying 'wmic cpu get /value'
DeviceID      : CPU0
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECint2006 = 66.3

ASUS Z97M-PLUS Motherboard (Intel Core i7-5775C)

SPECint_base2006 = 64.1

CPU2006 license: 13

Test date: Oct-2015

Test sponsor: Intel Corporation

Hardware Availability: Jun-2015

Tested by: Intel Corporation

Software Availability: Aug-2015

Platform Notes (Continued)

L2CacheSize : 1024
L3CacheSize : 6144
MaxClockSpeed : 3301
Name : Intel(R) Core(TM) i7-5775C CPU @ 3.30GHz
NumberOfCores : 4
NumberOfLogicalProcessors: 8

(End of data from sysinfo program)

Component Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply

General Notes

OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter
Binaries compiled on a system with 1x Intel Xeon E5-2699 v3 CPU
+ 64GB memory using Windows 8.1 Enterprise 64-bit

Base Compiler Invocation

C benchmarks:

icl -Qvc12 -Qstd=c99

C++ benchmarks:

icl -Qvc12

Base Portability Flags

400.perlbench: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64_X64
401.bzip2: -DSPEC_CPU_P64
403.gcc: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
429.mcf: -DSPEC_CPU_P64
445.gobmk: -DSPEC_CPU_P64
456.hmmer: -DSPEC_CPU_P64
458.sjeng: -DSPEC_CPU_P64
462.libquantum: -DSPEC_CPU_P64
464.h264ref: -DSPEC_CPU_P64 -DWIN32
471.omnetpp: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
473.astar: -DSPEC_CPU_P64
483.xalancbmk: -DSPEC_CPU_P64 -Qoption,cpp,--no_wchar_t_keyword -DWIN64



SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECint2006 = 66.3

ASUS Z97M-PLUS Motherboard (Intel Core i7-5775C)

SPECint_base2006 = 64.1

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Oct-2015
Hardware Availability: Jun-2015
Software Availability: Aug-2015

Base Optimization Flags

C benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel
-Qauto-ilp32 /F64000000

C++ benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features
-Qauto-ilp32 /F64000000 shlw64M.lib -link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:

icl -Qvc12 -Qstd=c99

C++ benchmarks:

icl -Qvc12

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

400.perlbench: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F64000000 shlw64M.lib
/F256000000 -link /FORCE:MULTIPLE

401.bzip2: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias
-Qauto-ilp32 /F64000000

403.gcc: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qauto-ilp32 /F64000000

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECint2006 = 66.3

ASUS Z97M-PLUS Motherboard (Intel Core i7-5775C)

SPECint_base2006 = 64.1

CPU2006 license: 13

Test date: Oct-2015

Test sponsor: Intel Corporation

Hardware Availability: Jun-2015

Tested by: Intel Corporation

Software Availability: Aug-2015

Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O2 -Qprec-div- -Qansi-alias -Qauto-ilp32
/F64000000

456.hmmer: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qansi-alias
-Qopt-ra-region-strategy=block -Qauto-ilp32 /F64000000
shlW64M.lib -link /FORCE:MULTIPLE

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.html>

You can also download the XML flags source by saving the following link:
<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.xml>



SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECint2006 = 66.3

ASUS Z97M-PLUS Motherboard (Intel Core i7-5775C)

SPECint_base2006 = 64.1

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Oct-2015
Hardware Availability: Jun-2015
Software Availability: Aug-2015

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Dec 1 17:42:34 2015 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 1 December 2015.